RIDER HEIGHT (FEET & INCHES)

SIZING: PROPEL

INSIDE LEG (INCHES)

	27"	28"	29"	30"	31"	32"	33"	34"	35"	36"	37"
5'5"		S	S								
5′6"	S	S	S	S	S						
5'7"		S	S	S	S	S					
5'8"		S	S	М	М	М					
5'9"			М	М	М	М	М				
5' 10"			М	М	М	М	М				
5'11"				М	М	M/L	M/L	M/L			
6'0"				M/L	M/L	M/L	M/L	M/L			
6'1"					M/L	M/L	M/L	L	L		
6'2"					L	L	L	L	L		
6'3"						L	L	L	L	L	
6'4"							L	L	XL	XL	XL
6'5"							XL	XL	XL	XL	XL

USAGE: HIGH PERFORMANCE ROAD

INTENDED USAGE & WEIGHT LIMITS

Bikes designed for riding on a paved surface where the tyres do not lose ground contact.

INTENDED: To be ridden on paved roads only

NOT INTENDED: For off-road, cyclocross or touring with racks and panniers

TRADE OFF: Material used is optimised to deliver light weight & specific performance. You must understand that (1) these bikes are intended to give an aggressive racer or competitive cyclist a performance advantage over a relatively short product life (2) a less aggressive rider will enjoy longer frame life (3) you are choosing light weight (shorter frame life) over more frame weight and a longer frame life (4) you are choosing light weight over more dent resistant or rugged frames that weigh more. All frames that are very light need frequent inspection. These frames are likely to be damanged or broken in a crash. They are not designed to take abuse or be a rugged workhorse.

Maximum Weight Limit

Rider	*Luggage	Total		
275lbs / 125kg	10lbs / 4.5kg	285lbs / 129kg		

*Seat bag / handlebar bag only

Please read your bicycles instruction manual carefully and if in doubt contact Giant or your local authorised Giant / Liv retailer.