



Crumbwool Carpet Underlay

Technical Data Sheet

Fibre composition:	100% recycled fibre & 100% recycled rubber crumb. Wool rich carpet threads and rubber crumb. (The colours may vary depending on the threads recycled.)
Accreditation:	Wools of New Zealand® accredited underlay, recommended as the ideal underlay to install with Wools of New Zealand® and Laneve™ branded carpets.
Product conformity:	British Standard 5808: Specification of underlays for textile floor coverings.
Thickness:	10mm +/- 0.5mm
Weight:	2100g/m ² (62oz/yd ²) +/- 10%
Roll dimensions:	1.37m wide x 7.3 linear metres
Roll area:	10m ²
Flame retardancy: (BS5808, BS4790 Hot metal nut test)	Low radius of char.
Compression performance: (BS5808, BS4098)	12% Thickness loss after 24 hours compression and 24 hours recovery.
Thermal insulation performance: (BS4745)	3.2 tog <i>indicative</i> .
Sound insulation performance: (ISO 140-8)	36db sound impact reduction <i>indicative</i> .
Product guarantee:	Lifetime of the initial carpet installation.
Recommended application:	High traffic domestic areas.
Suitable rooms:	Halls, bedroom, living room, stairs, dining room, kitchen.



Sales of Crumbwool support



Helping to protect our forests and the creatures that live in them



Anglo Recycling Technology Ltd

Tong Lane, Whitworth
Rochdale, Lancashire, OL12 8BG

Tel: +44 (0)1706 853513 Fax: +44 (0)1706 853625

Email: info@anglore recycling.com

Web: www.anglore recycling.com

Note: This sheet is for guidance only and is not intended as a product specification