



EN 10255 (BS 1387) Steel Tube

Nominal Size	Thread Size (in)	Approx OD	Medium			Heavy		
			Outside Diameter		Thickness	Outside Diameter		Thickness
			Min.	Max.		Min.	Max.	
8	1/4"	13.5	13.9	13.3	2.3	13.9	13.3	2.9
10	3/8"	17.2	17.4	16.8	2.3	17.4	16.8	2.9
15	1/2"	21.3	21.7	21.1	2.6	21.7	21.1	3.2
20	3/4"	26.9	27.2	26.6	2.6	27.2	26.6	3.2
25	1"	33.7	34.2	33.4	3.2	34.2	33.4	4
32	1.1/4"	42.4	42.9	42.1	3.2	42.9	42.1	4
40	1.1/2"	48.3	48.8	48	3.2	48.8	48	4
50	2"	60.3	60.8	59.8	3.6	60.8	59.8	4.5
65	2.1/2"	76.1	76.6	75.4	3.6	76.6	75.4	4.5
80	3"	88.9	89.5	88.1	4	89.5	88.1	5
100	4"	114.9	114.9	113.3	4.5	114.9	113.3	5.4
125	5"	139.7	140.6	138.7	5	140.6	138.7	5.4
150	6"	165.1	166.1	164.1	5	166.1	164.1	5.4

All dimensions above are shown in mm.

Install is manufactured fully in accordance with BS 1387 and ISO 65.

Light weight tubes are also available (equivalent to ISO 65 light series II).

Packing and Identification

Tubes are supplied in standard metal strapped bundles.

Tubes are colour coded with bands as follows:

Medium - Blue

Heavy - Red

Install comes with tubes screwed taper thread and sockets parallel thread, unless otherwise specified.

Lengths	Half Lengths mtrs	Full Lengths mtrs
1	3.25	6.5
2	6.5	13
3	9.75	19.5
4	13	26
5	16.25	32.5
6	19.5	39
7	22.75	45.5
8	26	52
9	29.25	58.5
10	32.5	65

