

**Owensboro Specialty Polymers, Inc.** 5529 Highway 2830 Owensboro, KY 42303 www.onssp.com Contact us at info@onssp.com

## **EVERFLEX<sup>®</sup> SP1084**

## Paint/Coating Emulsion

Everflex SP1084 is a high molecular weight polyvinyl acetate emulsion polymer. It has excellent strength and durability as well as high tensile strength both green and in the final product.

Everflex SP1084 is stabilized with hydrolyzed polyvinyl alcohol (PVOH) which imparts better shelf life with less settling.

Everflex SP1084 is designed for use as a concrete additive for improved adhesion and compressive strength.

52.5-54.5%

4.5-5.5

## PRODUCT SPECIFICATIONS

**Total Solids** pН Viscosity **Residual Monomer** 

## **TYPICAL LATEX PROPERTIES**

Description Average Particle Size Weight/gallon, Emulsion Weight/gallon, Solids Specific Gravity Mechanical Stability Borax Compatibility Freeze Thaw Stability Shelf Life Recommendation<sup>1</sup> **Recommended Storage Temperature** 

**TYPICAL FILM PROPERTIES** 

Color/Clarity Gloss Odor Water Resistance Light Stability Aging Characteristics Film Consolidation Τg

300-700 cps (Brookfield #3 spindle, 60 rpm, 25° C) <1% Milky white liquid with a slight vinegar odor

<2.0 microns (approximate) 9.05 pounds 9.85 pounds 1.18 20+ minutes No No 1 year 35-85° F

Clear with a very slight haze Medium None Good Excellent Excellent Good-Excellent 14° C

Maximum recommended shelf life under optimal storage conditions. Shelf life will vary depending on storage conditions. 1. Literature code OSP\_TDS\_EverflexSP1084\_Rev4 Issue Date: April 28, 2015

The information presented herein is based on the best available data and is believed to be true and accurate. Please read all statements, recommendations, or suggestions in conjunction with our conditions of sale which apply to all goods supplied by us. No responsibility for the use of these statements, recommendations, or suggestions is assumed by the supplier, nor are they intended as a recommendation for any use which would infringe any patent or copyright. The buyer bears sole responsibility for determining suitability of the product for their application.