Material Safety Data Sheet **PC - NAT/BLK** 

Product Name: Chemical Name: CAS NO: Product Use: Company Identification: PC POLYCARBONATE 25971-63-5 (POLYMER) Engineering Plastic Stock Shape for Machining PSR Industrial Ltd. Namdongseo-ro, Namdong-Gu, Incheon-City, Korea (TEL:82-32-677-2971, FAX:82-32-677-2974)

## **Hazard Identification**

#### **Emergency Overview**

NFPA Rating : Health = 1, Flammability = 1, Reactivity = 0

### Eye

Dust and particles, like other inert materials, are mechanically irritating to eyes.

#### Skin

Hot and molten material has the potential to cause thermal burns.

### Inhalation

Shapes not respirable.

Ingestion

No specific information available on the product.

## Composition, information on Ingredients

Additives not hazardous by 29 CFR 1910.1200.

Identity	CAS#	Concentration(%)
Polycarbonate	25971-63-5	>99
Other additives	-	<1

## **First Aid Measures**

Eye

Immediately flush eyes with plenty of water. Seek medical attention if discomfort persists.

### Skin

If polycarbonate is stuck to skin, do not remove, and seek medical attention. And allow adhered polycarbonate to come off naturally.

### Inhalation

Polycarbonate is not likely to be inhaled due to physical form. When gas from molten polycarbonate is inhaled, move to fresh air.

#### Ingestion

PSR Industrial Limited, 19 – 21 Beler Way, Leicester Road Ind. Est., Melton Mowbray, Leicestershire, LE13 0DG Tel: +44 (0) 1664 56540, Fax: +44 (0) 1664 560030, sales@psrplastics.co.uk, www.psrplastics.co.uk



**PSR Plastics** Components to Industry

Page 1/4 Revision Date: 2014.12.12 (Rev.0)

Material Safety Data Sheet **PC - NAT/BLK** 

P

**PSR Plastics** Components to Industry

Page 2/4 Revision Date: 2014.12.12 (Rev.0)

If a significant quantity has been swallowed, give plenty of water to dilute. Seek medical attention.

### Note to Physicians

Processing vapors may cause irritation to the eyes, skin and respiratory tract. In cases of severe exposure, nausea and headache can also occur.

## **Fire Fighting Measures**

Flash Point: 382°C (720°F)

Autoignition Temperature : 630°C (1166°F)

Unusual Fire, Explosion Hazards : None Known.

Hazardous Product of Combustion Carbon oxide and hydrocarbon fragments.

Extinguishing Media : Foam or water spray.

**Unsuitable Extinguishing Media** : Carbon dioxide and dry chemical are not recommended because of their lack of cooling capacity may permit re-ignition.

## **Firefighting Instructions**

Firefighters should wear self-contained breathing apparatus and full fire-fighting turn-out gear (bunker gear). Product burns with a very hot, but very faint blue flame. Water, foam and dry chemical may cause damage to electrical equipment.

# **Accidental Release Measures**

**Personal precaution** Sweeping to prevent fall.

Environmental protection

## No special measures.

## Handling and Storage

### Handling

During machining of the stock shapes, evacuate swarf to prevent slipping hazard.

## Storage

Store in well-ventilated area away from heat and sunlight.

## **Exposure Controls / Personal Protection**

Material Safety Data Sheet **PC - NAT/BLK** 

**PSR Plastics** Components to Industry

Page 3/4 Revision Date: 2014.12.12 (Rev.0)

### **Engineering Controls**

A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended.

### **Protective Equipment**

*Eyes:* Wear safety glasses with side shields should be sufficient for most processing and machining runs. *Skin*: When thermal or melt processing, wear long pants, long sleeves and well insulated gloves.

### **Dust Limit Value**

Respirable dust : 6mg/cm<sup>3</sup>. Inhalable dust : 10mg/cm<sup>3</sup>.

## **Physical and Chemical Properties**

Appearance:	Solid
Smell:	None
PH:	Not applicable
Water Solubility:	Insoluble
Boiling Point:	Not applicable
Melting Point:	Not applicable
Vapor Pressure:	Not applicable
Specific Gravity:	1.19 ~ 1.22g/cm <sup>3</sup>

# **Stability and Reactivity**

## **Chemical Stability**

Stable under normal conditions of use and storage.

## Condition to Avoid

Heating above 320°C (608°F).

## **Hazardous Decomposition Products**

Carbon monoxide, carbon dioxide, bisphenol-A, diphenylcarbonate and phenol derivatives.

# **Toxicological Information**

No specific information available on the product.

Material Safety Data Sheet **PC - NAT/BLK** 

## **Ecological Information**

**Ecotoxicity** No specific information available on the product.

**Environmental Information** This material is considered to be non-biodegradable.

Aquatic Toxicity Toxicity is expected to be low based on insolubility of polymer in water.

# **Disposal Considerations**

Recycling is encouraged. Dispose in accordance with local regulations.

# **Transportation Information**

This product is not subject to transport regulations.

# **Regulatory Information**

## Section 313 Supplier Notification

This product does not contain any toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

## Labeling Information(EEC)

Not subject to labeling.

# **Other Information**

This product is not intended for use in medical applications involving permanent implantation in the human body. The information contained herein is based on the present state of our knowledge. We don't suggest or guarantee that any hazards listed herein are the only ones that exist. PSR Industrial Ltd. Makes no warranty of any kind concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and this material may aggravate the effects of other materials.

Users have the sole responsibility to determine the suitability of the materials of any use and the manner of use contemplated. Users must meet all applicable safety and health standards.



**PSR Plastics** Components to Industry

Page 4/4 Revision Date: 2014.12.12 (Rev.0)