

# TEC-GUARD

# ARMOR

## TEC-GUARD SYNTHETIC BLEND HIGH MILEAGE PASSENGER CAR MOTOR OILS

**TEC-GUARD® Armor High Mileage motor oils** are superior synthetic blend oils formulated to provide long engine life and premium protection for vehicles with more than 75,000 miles.

They meet modern engine performance demands for improved resistance to oxidation, deposit control, wear protection, prevent oil leakage, helps remove built up of sludge deposits and are backward compatible with earlier API/ILSAC performance levels.

**TEC-GUARD® Armor High Mileage Synthetic Blend 10W-30** meets or exceeds the following performance requirements and industry specifications: API SN PLUS, API SN, API SM, API SL, API SJ, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, GM® 6094M. Always consult your owner's manual for specific recommendations.



- Extended Drain Capabilities
- Resists Thermal Breakdown
- Engine Cleanliness
- Maximizes Power Output
- Extra Protection for Emission Systems
- Reduces Oil Consumption

| Test Method                         |      | Product Numbers |                |
|-------------------------------------|------|-----------------|----------------|
| NOVACK Volatility                   | <12% | Bulk            | 10425203310W30 |
| ASTM D92 - Flash Point, °C          | 232  | Drum            | 10425213310W30 |
| ASTM D97 - Pour Point, °C           | -42  | Pail            | 10425243310W30 |
| ASTM D445 - Viscosity @ 40° C, cST  | 68.2 | Tote            | 10425203310W30 |
| ASTM D445 - Viscosity @ 100° C, cST | 10.5 | 4/1 Gallon      | 10425113310W30 |
| ASTM D2270 - Viscosity Index        | 141  | 12/1 Quart      | 10425263310W30 |
| ASTM D4052 - Density, ppg           | 7.17 |                 |                |

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.