Trade name / Substance name: Argen Lab Anti-Mold Spray

SAFETY DATA SHEET

(*) concerns only chemical notification

(**) either 3.1 or 3.2 must be filled

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name / Substance name

Argen Lab Anti-Mold Spray

Company product code

AL13

REACH Registration number

Not applicable, because the product is a mixture.

1.2 Relevant identified uses of the substance or mixture and uses advised against

The uses of the chemical

Removal and prevention of molds.

Classification of economic activities (NACE) (*)

Use categories (UC62) (*)

The chemical can be used by the general public (*)

The chemical is used by the general public only (*)

1.3 Details of the supplier of the Safety Data Sheet

SupplierArgen Lab OyStreet addressPallotie 2

Postcode and post office FI-33470 Ylöjärvi, Finland

Post-office box

Postcode and post office

 Telephone number
 +358 3 255 4441

 Telefax
 +358 9 4159 2320

E-mail address info@argenlabglobal.com

Finnish Business ID (Y code) (*) F125368581

1.4 Emergency telephone number

Denmark	National emergency number: 82 12 12 12 (Giftlinjen, Bispebjerg Hospital).
Taiwan	National emergency number: 119

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

F+; R12

2.2 Label elements

Active ingredient: Silver chloride (<0,1 %)

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – no smoking. Keep out of the reach of children.

According to 1999/45/EC

Trade name / Substance name: Argen Lab Anti-Mold Spray

F+ Extremely flammable R phrases

R12 Extremely flammable

S phrases

S2 Keep out of the reach of children

S13 Keep away from food, drink and animal foodstuffs S16 Keep away from sources of ignition - No smoking

Do not breathe spray S23

Use only in well-ventilated areas S51

2.3 Other hazards

None.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances (**)

3.2 Mixtures (**)				
Substance name	CAS- or EC-	REACH Registration	Concentration	Classification
	number	No.		
Ethanol	64-17-5	01-2119457610-43	60-80 %	F;R11
Propane	74-98-6	Not available.	10-20 %	F+; R12
Butane (contains <0.1%	106-97-8	Not available.	10-20 %	F+; R12
of 1,3.butadiene)				
Silver(I) chloride	7783-90-6	Biocide, not applicable	<0,1%	N;R50/53

SECTION 4: FIRST AID MEASURES

Inhalation

If aerosol spray is inhaled, seek medical attention if necessary.

Eyes

Flush eye(s) with water.

Skin

Flush with water. If irritation persists, seek medical attention.

Ingestion

If aerosol spray have been ingested, seek medical attention immediately.

SECTI	ON 5: FIREFIGHTING MEASURES
5.1	Extinguishing media
	Alcohol resistant foam.
5.2	Special hazards arising from the substance or mixture
	Water spray.
5.3	Advice for firefighters
	In the event of fire, there is a possibility of explosion. Staff must be evacuated immediately to a

safe distance from fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES 6.1 Personal precautions, protective equipment and emergency procedures Prevent access to unauthorised personnel. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind. 6.2 **Environmental precautions** Prevent entry into drains and sewers, basements or confined areas in large quantities. 6.3 Methods and material for containment and cleaning up None. 6.4 Reference to other sections

Use individual protective equipment (see chapter 8).

Trade name / Substance name: Argen Lab Anti-Mold Spray

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Use only in well-ventilated areas. Avoid heat, flames, sparks and other sources of ignition – no smoking. Do not store near flammable substances. Take precautions against static electricity discharges. Increase ventilation to area to prevent formation of explosive air/gas mixtures. Do not pierce or burn aerosols, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Pressurized container. Do not store near flammable substances. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from children. Protect from freezing.

7.3 Specific end use(s)

None.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limit values

Ethanol 8 h = 1000 ppm; 1900 mg/m^3

15 min = 1300 ppm; 2500 mg/m^3

Butane 8 h = 800 ppm; 1900 mg/m³

15 min = 1000 ppm; 2350 mg/m^3

Propane 8 h = 800 ppm; 1500 mg/m³

15 min = 1100 ppm; 2000 mg/ m^3

Silver(I) chloride (powder) $8 h = 0.1 \text{ mg/m}^3$

Other limit values

Not available.

DNEL

Not available.

PNEC

Not available.

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good hygiene and safety practices.

Eye / face protection

Avoid contact with skin and eyes. Wear safety glasses or goggles if eye contact is possible.

Skin protection

Avoid contact with skin. Wear safety clothes when workig with large quatities.

Hand protection

Wear impervious gloves when working with large quantities.

Respiratory protection

Use with adequate ventilation. Do not breathe aerosol spray. It is not expected that exposure limits are exceeded in normal use.

Thermal hazards

This product is extremely flammable.

Environmental exposure controls

Prevent entry into drains and sewers, basements or confined areas in large quantities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
9.1 Information on physical and chemical prope	erties		
Appearance	Colourless liquid, aerosol.		
Odour	Alcohol.		
Odour threshold	Not available.		

Trade name / Substance name: Argen Lab Anti-Mold Spray

рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Water soluble.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

None.

SECTIO	N 10: STABILITY AND REACTIVITY
10.1	Reactivity
	Not available.
10.2	Chemical stability
	Stable under normal conditions of use and storage.
10.3	Possibility of hazardous reactions
	Not available.
10.4	Conditions to avoid
	Pressure container. Keep away from heat, spark, flames and all other sources of ignition. Protect
	from sunlight and do not expose to temperatures exceeding 50 °C.
10.5	Incompatible materials
	Not available.
10.3	Hazardous decomposition products

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ethanol LD50 = 10 470 mg/kg (skin, rat)
Propane/butane LC > 20 mg/l (inhalation)
Silver(I) chloride (powder) LD50 > 5110 mg/kg (oral, rat)

Skin corrosion/irritation

Product is not corrosive to skin. Skin irritation has not been reported.

Serious eye damage/irritation

Not available.

Trade name / Substance name: Argen Lab Anti-Mold Spray

Irritating to eyes.

Respiratory or skin sensitisation

Large quantities of vapours may cause respiratory irritation. May dry skin.

Germ cell mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

STOT-single exposure

Not available.

STOT-repeated exposure

Not available.

Aspiration hazard

Not available.

Other information

Ingestion may cause gastrointestinal pain, nausea, vomiting and diarrhea, and central nervous system (brain) depression similar to alcohol intoxication.

10.1	ON 12: ECOLOGICAL INFORMA	Wien and the second sec	
<u> 12.1 </u>	Toxicity		
	Ethanol	LC50/96h/fish = 11 200 mg/l	
		EC50/48h/invertebrates, fresh water = 5 012 mg/l	
		EC50/48h/invertebrates, sea water = 857 mg/l	
	Propane/butane	Not available.	
	Silver(I) chloride (powder)	LC50/96h/fish (Pimephales promelas) = 1,93 mg/l	
12.2	Persistence and degradabi	lity	
	Ethanol	Readily biodegradable.	
	Propane	Oxidises rapidly by photo-chemical reactions in air.	
	Butane	Oxidises rapidly by photo-chemical reactions in air.	
	Silver(I) chloride (powder)	Not available.	
12.3	Bioaccumulative potential		
	Ethanol	log Pow = 0,32; no bioaccumulation.	
	Propane	Does not bioaccumulate significantly.	
	Butane	Does not bioaccumulate significantly.	
	Silver(I) chloride (powder)	Not available.	
12.4	Mobility in soil Product is readily water soluble and may move with surface and table water. Product does not		
	readily absorb into sediments or soils. Propellant (propane/butane) evaporates quickly.		
12.5	Results of PBT and vPvB a	ssessment	
·	Not known.		
12.6	Other adverse effects		

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Not known.

Dispose of in accordance with federal, state, and local regulations.

SECTION 14: TRANSPORT INFORMATION

	Land transport	Sea transport	Air transport
14.1 UN number	UN1950	UN1950	UN1950

Trade name / Substance name: Argen Lab Anti-Mold Spray

14.2 UN proper shipping name	Aerosols	Aerosols	Aerosols
14.3 Transport hazard class(es)	2	2	2
14.4 Packing group	-	-	-
14.5 Environmental hazards	Not known.	Marine pollutant: No	Not known.

14.6	Special precautions for user
	Not known.
14.7	Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not known.

SECTION 15: REGULATORY INFORMATION		
15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	
	Not available.	
15.2	Chemical safety assessment	

Not available for this mixture.

SECTION 16: OTHER INFORMATION

Indication of changes

Edition 1.0 of this safety data sheet.

Abbreviations and acronyms

None.

Key literature references and sources for data

Publicly available toxicity information. Safety data sheets of the raw materials of the mixture.

Used method in evaluating classification

Classified and labelled according to directive 1999/45/EC.

List of relevant R-and S-phrases or/and safety and precautionary statements

Relevant R phrases

R12 Extremely flammable

Relevant S phrases

S2 Keep out of the reach of children

Keep away from food, drink and animal foodstuffsKeep away from sources of ignition - No smoking

S23 Do not breathe spray

S51 Use only in well-ventilated areas

Training advice for workers

Information not available.