

Datasheet for Top cloth: 10-10.301

Features

With decades of filtration experience Filtration Group B.V. has developed a cloth range to give a solution to all your filtration challenges.

Our broad range of top cloths is developed in such a way that depending on the demanded temperature range, chemical resistance and selectivity the best solution for your process can be chosen.

Characteristics

- High strength seams - no breaks. This brings stand-down time to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It saves time when installing a cloth.
- Packed in plastic bags to prevent the cloths from becoming dirty.
- A sticker on the plastic bag identifies the cloths. Because the identification sticker does not touch the cloth itself there is no risk of ink or glue going into hygienic applications.

Specifications

Cloth code	10-10.301
Cloth use	Top cloth
Material	PP
Cloth structure	Monofilament
Surface treatment	Heat-set and calendered
Filter fineness [μm]	10
Air permeability [$\text{l}/\text{dm}^2/\text{min}$] at 200 Pa	$15 \pm 50\%$
Maximum temperature [$^{\circ}\text{C}$]	90

Approvals

Approved according to 2004/1935/EG, declaration of conformity available on request.

Recommendations

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth (Cricket filter only).

Filtration Group B.V.
Postbus 35
7240 AA Lochem
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com
www.filtration.group

December, 2017

Order Information

Element type	Length	Ordering Code
Type I	620	-
	750	-
	1000	72415528
	1500	72415530
	2000	-
Type II	1000	-
	1500	72415531
	2000	72415532
	2500	72415534
PTS 70 mm	1500	-
	1750	-
	2000	-
PTS 90 mm	1000	72393268
	1500	-
	1750	-
	2000	-
	2250	-
	2500	-

Filtration Group B.V.
Postbus 35
7240 AA Lochem
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com
www.filtration.group

December, 2017