Fire-Retardant Paint Additive

Flamecheck M-IIIPA is a "Class A" fireretardant paint additive for latex and acrylic paint. (Tested with most major brands.)

Easy To Use

Flamecheck M-IIIPA is easy to use. Simply add 8 ounces of Flamecheck M-IIIPA to 1 gallon of interior or exterior latex paint. Mix thoroughly, do not dilute.


- Gives a "Class A" fire rating on the paint coating.
- Can be used on any paintable surface.
- ✓ Once added Flamecheck M-IIIPA will render the paint unable to support combustion.
- Unlimited shelf life in a sealed container. Do not allow to freeze.

Tested & Proven: ASTM E-84 ZERO Flame Spread & ZERO Smoke

Flamecheck M-111PA passes ASTM E-84 Steiner Tunnel test with a "Class A" rating. ZERO flame spread and ZERO smoke over a non-flammable substrate.

When painting wood or fabric (stage), treat absorbent substrates with Flamecheck M-111 prior to painting for added protection.

"Class A" fire-retardant paint additive







Flamecheck M-111PA Fire Retardant Paint Additive



Gives a "Class A" Fire Rating to your Indoor and Outdoor Painting

Saving Lives & Property Since 1985

www.flamecheck.com

Approved for Residential and Commercial Applications

Color & Sheen

Will Flamecheck M-111PA change the color or sheen of the paint I use? No, Flamecheck M-111PA will not change the color or sheen of the paint it's added to.

Coverage

Mix 8 oz of Flamecheck M-111PA into 1 Gallon of paint, coverage is 300-400 sq. ft. per coat, apply two coats to achieve a "Class A" finish.

Always test your application to insure it meets the expected standard.

Application

High quality paintbrush or professional roller is acceptable. For larger jobs an airless spray gun is recommended.





Non-Toxic

Flamecheck has been manufacturing non-toxic fire retardant products since 1985.

Flamecheck M-111PA is safe to use in areas with daily human contact such as:

- ✓ Bedrooms
- ☑ Kitchens
- ☑ Garage
- ☑ Hallways
- ☑ Stairways
- ☑ Family room
- ☑ Hotels
- ✓ Escape routes
- ☑ Daycare Centers
- ☑ Hospitals
- ✓ Nursing facilities
- ✓ Restaurants
- \blacksquare Schools and Offices
- ☑ Cabins
- ✓ Concrete Surfaces
- ☑ Industrial Oil Storage
- ☑ Movie and Theater Sets
- ✓ Escape Rooms
- ✓ Haunted Houses



Disclaimer: Use only as directed. For more information please read the Safety Data Sheet. Flamecheck International has no control over how anyone applies paint with Flamecheck M-111PA, therefore Flamecheck International cannot make any guarantee as to the fitness or suitability of this product for any particular purpose or use. Application techniques vary, therefore it is the end user's responsibility to test and verify the application techniques and suitability of this product for the intended use. Always test a sample to ensure this product meets any expected standard. Flamecheck International LLC only warrants the quality control of this product. All products are supplied in sealed containers. Do not use if the seal is missing or broken For the complete disclaimer regarding this product, visit www.flamecheck.com. *This is NOT an Intumescent paint additive.

> Passes ASTM E-84 "Class A" with ZERO flame spread and ZERO smoke