

K-2K

K-Maxi-2K

NTM  
www.ntm.fi

# NTM



*Simple and easy for  
dual waste streams!*

K-2K 2-chamber rear loader

www.ntm.fi



## K-2K - Technical Specifications

A small, light and agile 2-chamber loader for collecting two different types of waste. This is the K-2K model in a nutshell. Separated waste in hard-to-access areas is no problem for the K-2K. The bin lift is controlled using levers and the tried and tested hydraulics guarantee high operational reliability and safety. The 2-chamber loader is also available in a heightened version, the K-Maxi-2K, to enable you to best adapt to your specific needs.

	K-2K	K-Maxi-2K
Load volume (net)	8,5 (5,6/2,9) - 11,0 (7,2/3,8)m <sup>3</sup>	10,0 (6,6/3,4) - 13,1 (8,6/4,5)m <sup>3</sup>
Body weight		
including bin lift	3700 - 4400 kg	2700-3500 kg
Height above chassis frame	1815 mm	1615, 1815, 1965 mm
Width	2350 mm	2040-2350 mm
Total length	4500 - 5600 mm	4100 - 5600 mm
Loading height	1150 mm	1150 mm
Compaction force	142 kN (14,25 tonnes)	142 kN (14,25 tonnes)
System pressure	190 bar	190 bar

### Optional:

- Footboards
- Automatic compaction cycle
- Lever for bin lift on the left side
- Semi-automatic bin lift
- Hydraulic oil heater
- Auto lube
- Weighing equipment
- Sack lift
- Bio equipment
- Different box alternatives
- Dust-free emptying of bins
- Variable pump



### Standard equipment:

- Bin lift
- Pneumatic bin catcher bar
- Proportionally controlled hydraulic levers for the bin lift
- Dual circuit manual override controls
- Cleaning of packer plate when emptying
- Rear view camera
- Side access door



The manufacturer reserves the right to make alterations without prior notice.

# K-2K 2-chamber rear loader

www.ntm.fi