

DECORATIVE FINISH FOR ROOFS



ROOFTOP

DESCRIPTION:

Rooftop is a decorative finish for roofs. Suitable for use on Fibro, cement tile and galvanised iron

FEATURES/BENEFITS:

- Excellent Durability
- Solvent Resistant
- Sensitive to aromatic hydrocarbons and alcohol
- Lead free

TYPICAL APPLICATIONS:

- Fibro Roofs
- Concrete Tile Roofs
- Galvanised Iron Roofs

COLOURS:

- A range of popular traditional and modern tile colours available
- Available Gloss and Semi-Gloss



COVERS:

Assumes no losses. Two coats are recommended each with coverage of 10sqm per litre at a recommended 40 micrometres dry film build.

VOLUME SOLIDS: 40%

SURFACE PREPARATION:

Surface to be painted should be dry and free from dust, grease and dirt. Remove flaking, powdery paint and repair surface imperfections with Rooftop filler coat. Roofs should be thoroughly scrubbed with hot water or water blasted. If fungal growth is present the roof should be first treated with Rooftop Mildew remover. Fibro roofs should be diluted with 10 to 20% water. Galvanised roofs should be first primed with Rooftop Galvanised Iron Primer.



APPLICATION:

Application is by brush, roller or spray. Thin up to 100ml per litre with water to aid application.



DRYING TIMES:

Rooftop is touch dry in 30minutes, re-coat after two hours. In damp and humid conditions drying time is lengthened.

CLEAN UP:

Wash all equipment and any minor spills with clean water.

PACKAGING:

15L Pail
20L Pail
200L Drum

DECORATIVE FINISH FOR ROOFS



ROOFTOP

SAFTEY DATA:

Non-flammable and classified as non-hazardous.

UN-NUMBER: N/A

HAZCHEM CODE: N/A

DANGEROUS GOODS CLASS & SUBRISK:

N/A

POISON CODE: N/A

May cause irritation when in contact with sensitive skin and eyes. Wash infected area with copious quantities of water. If ingested contact a doctor or poisons information centre. DO NOT induce vomiting. Give water to drink. The use of eye protection is recommended.

The information presented in this data sheet does not imply any warranty. Further, the maker reserves the right to alter the product, the specification and/or the application techniques as described herein without prior notice, in line with his policy of technological advancement and product improvement. Whilst any information and/or specification contained herein is to the best of our knowledge and experience, all of the above information must in every instance be taken as merely indicative and subject to confirmation after long-term practical applications. For this reason, anyone intending to use the product must ensure beforehand its suitability for the envisaged application. In every instance, the user alone is fully responsible for any consequences deriving from the use of the product. Furthermore, no warranty is given or implied in connection with any recommendations or suggestions made by us or our Representatives, Agents or Distributors as conditions of use and any labour involved beyond our control.



ADCRETE INDUSTRIES PTY LTD
43 Grice Street (PO Box 3030) Clontarf, Qld 4019
Ph: (07) 3883 1888 Fax: (07) 3883 1777
ABN: 42 010 308 791

June 17, 2016