

# Technical Data Verona Lo-Line



# Verona Lo-Line Double Convector Type 22

Height mm	Length mm	Tap Centres	Henrad Code	Heat er Watts	missions Btu/hr	Henrad Price
	800	800	248308	541	1846	£224.76
140	1400	1400	248311	946	3228	£297.49
148	2000	2000	248314	1352	4613	£376.81
	2200	2200	248315	1487	5074	£403.25
	800	800	248316	898	3064	£381.97
296	1400	1400	248319	1571	5360	£477.46
270	2000	2000	248322	2244	7657	£603.62
	2200	2200	248323	2453	8370	£614.80

Btu/hr @ ∆t50°C

Working pressure: Tested to withstand 4.0 bar

For technical and installation information visit our website www.henrad.co.uk/downloads





# Floor mounting bracket information

Length mm	Feet Required			
400 - 1500	2			
1600 - 3500	3			

Optional extra to have no lugs. This needs specifying at the time of ordering for floor standing only.



# Technical Data Verona Lo-Line

### Technical information

#### **Testing and Operating Pressures**

Henrad Verona Range has been independently tested to ensure radiators perform to a maximum working pressure of 4.0 bar.

#### **Connections**

Henrad Verona has 2 x  $^{1}/_{2}$ " BSP connections (BOE) as standard.

#### **Paint Process**

Two coat paint process, each Henrad radiator is subjected to a multi-stage cleaning and paint process.

The final powder coat is Traffic white (RAL 9016) which is stoved and cooled to give a perfect finish.

All radiators are illustrated in Traffic white unless stated.

#### **Water Treatment**

Installation of the system should be properly flushed and fitted in accordance with the British Code of Practice for the Treatment of Water in Domestic Hot Water Central Heating Systems.

#### Warranty

Henrad Verona Range come with a 5 year manufacturer's warranty.

Henrad (UK) Limited, Marriott Road, Mexborough, South Yorkshire S64 8BN. Telephone: 0844 543 6200 Facsimile: 0844 543 6300


### www.henrad.co.uk

# Henrad Verona

#### **Wall Mounting Information**


All dimensions in mm.

#### Verona Lo-line




Horizontal radiator - Plinth				
Height	Width			
148	500 1 0000			
296	500 to 2200			


#### 148





#### 296





#### Optional mounted feet

