

THE NILFISK VL
WET & DRY SERIES





WET & DRY VACUUM CLEANERS FOR ALL APPLICATIONS

The new family of wet & dry vacuum cleaners contains variants from 20 to 75 liter containers so you can feel certain that we have something that fits your needs.

The VL series offers you a wide portfolio of thoroughly tested machines with a number of new innovations to help you do a good cleaning job with maximum help from the machine.

Whether you need to clean huge areas or small spots, wet, dry or a combination - we have the machine for you.

The VL wet & dry series from Nilfisk is designed and developed to the highest standards: Yours!

By partnering with our customers and users we have achieved a wet & dry vacuum cleaner that meets the requirements of the most demanding end users.

Combined with Nilfisk service and support, our wet & dry portfolio provides you with a reliable, high performance cleaning solution that is easy to operate with an attractive cost of ownership.

VL200 and VL500 are ideally suited for hotels, contract cleaners, education, exhibition and conference centers as well as public buildings, manufacturing and industrial applications.



VL200: This handy machine is available with an Inox container for the extra tough environments.



VL200: Compact and ergonomic design for easy transportation

WE ASKED YOU, AND THIS IS YOUR ANSWER

VL200 is the compact and transportable solution

For small wet and dry cleaning applications our VL200 machine is the perfect choice. You can choose between a 20 or 30 liter machine with nice and handy features. Both variants have the built in semi-automatic filter cleaning system

Push & Clean for quick and handy cleaning of the filter helping you maintaining the high suction power on the machine. The handy machine is available with an INOX container for the extra tough environments.



VL500 makes daily operation easy, fast and safe

- · By transferring the weight as you lift the container, the Nilfisk Ergo Tipping system enables you to empty a completely filled container of fluid without excessive effort.
- Emptying the container without having to remove the motor head makes operation fast and easy, without risk of damage to critical components.
- · With the dual filtration system, the VL500 can be used in both wet and dry environments without the need to change filters for different applications.
- The unique design of the VL500 with single latch locking is not only signaling quality and innovation but also high performance and reliability.





Easy and fast emptying of the VL500 container thanks to the unique Ergo Tipping system. Emptying the machine without having to remove the motor head makes daily cleaning easier ans safer.





Big areas to clean? Try the squegee accessory for the VL500. $\label{eq:VL500}$



Dual filtration enables you to clean both wet and dry without changing filters




A flood pump is available as an accessory, and is the ideal solution for moving large volumes of liquid

VL200 MODEL OVERVIEW



VL500 MODEL OVERVIEW





Dual or single motor

Dual filtration for both wet and dry cleaning

Fail safe filter design makes operation easier

Ergo tip makes emptying the container easy and effortless

Features like the motor head,

push handle and container

locking mechanisms are designed

for single handed use

APPLICATION FILTER CONFIGURATION SUGGESTIONS

	Mesh wet filter	Dry cartridge filter	HEPA H13	Cloth wet & dry filter	Fixed floater	Detachable floater
Application						
General light cleaning e.g. kitchen spills				Х	Х	
Floor restoration e.g. foamy substances	X	X				X
Very dry & dusty e.g. wood shops			X	X		X
Very wet e.g. flood situations	X	X				Х
Different/changeable environments	X	X				X
Production	X	X	(X)			X
Hotels	X	X				X

THE RELIABILITY AND PERFORMANCE THAT OUR CUSTOMERS DEMAND

TECHNICAL SPECIFICATIONS

Description	Unit	VL200 20 PC	VL200 30 PC INOX	
IP protection class		IP24	IP24	
Rated power	W	1200	1200	
Max power	W	1500	1500	
Suction power end of tube	W	250	250	
Airflow	l/sec.	48	48	
Vacuum at nozzle	kPa	23.5	23.5	
Sound pressure level BS 5415	dB(A)+/-2	64	64	
Sound power level IEC 704	dB(A)+/-2	72	72	
Container capacity	litre	20	30	
Cable length	m	10	10	
Hose length	m	1.9	1.9	
Main filter area	cm ²	3000	3000	
HEPA filter area	cm ²	-	-	
Length x width x height	cm	38x39x50.5	39x40x63.5	
Weight	kg	7.5	10.5	

Specifications and details are subject to change without prior notice.

TECHNICAL SPECIFICATIONS

Description	Unit	VL500 35 Ergo	VL500 55 Ergo	VL500 75 Ergo	VL500 35 Basic	VL500 55 Basic	VL500 75 Basic
IP protection class		IP24	IP24	IP24	IP24	IP24	IP24
Rated power	W	1250	1250/2400	1250/2400	1250	1250/2400	1250/2400
Max power	W	1350	1350/2500	1350	1350	1350	1350/2500
Suction power end of tube	W	250	200	200	250	200	200
Airflow	l/sec.	48	48/72	48/72	48	48/72	48/72
Vacuum at nozzle	kPa	20	20/21	20/21	20	20/21	20/21
Sound pressure level BS 5415	dB(A)+/-2	62	64/66	64/66	62	64/66	64/66
Sound power level IEC 704	dB(A)+/-2	81	82/84	85/84	81	82/84	82/84
Container capacity	litre	35	55	75	35	55	75
Cable length	m	10	10	10	10	10	10
Hose length	m	1.9	2.5	2.5	1.9	2.5	2.5
Main filter area	cm ²	1051	1840	1840	1051	1840	1840
HEPA filter area	cm ²	2070	4410	4410	-	-	-
Length x width x height	cm	46x42x73	84x62x89	84x62x103	46x42x73	84x62x100	84x62x100
Weight	kg	12.5	26.5/27.5	26.5/28.5	11.5	24.5/25.5	26.5/28.5
Filter type:							
Sack filter		No	No	No	Yes	Yes	Yes
Dual filter		Yes	Yes	Yes	No	No	No
HEPA filter		Yes	Yes	Yes	No	No	No
Ergo filter		Yes	Yes	Yes	No	No	No

Specifications and details are subject to change without prior notice.

