

MILD STEEL KIOSK SPECIFICATION

Dimensions	Height	Width	Depth
MSK 1	1250	750	400
MSK 2	1250	1250	400
MSK 3	1250	1250	400
MSK 4	1250	1500	400
MSK 5	1250	1600	400
MSK 6	1500	1500	500
MSK 7	1500	2000	500
MSK 8	1500	2250	500
MSK 9	1500	2750	500

The kiosks are manufactured from 2mm zintec sheet steel to BS6687-1986 (chromate washed substrate BS1449-2.5 microns).

The kiosks are pressformed and welded construction and are supported by the appropriate certification to IP55 of BS5490 to give excellent weather protection and good earth continuity and finished to the following paint specification: -

1. Degrease and clean to remove surface dirt
2. 1-coat of 2-pack etching primer
3. Air dry for 1-hour
4. 2-coats of pure polyester powder paint to give a minimum dry film thickness of 50 microns
5. Stove at 180 degrees for 45 minutes

The finished colour is dark green shade RAL 6005 textured type finish.

The kiosks are fitted with the following equipment as standard: -

1. 2-kiosk lifting brackets (Not applicable to smaller, non-standard kiosks. Unless requested)
2. 14mm floor fixings
3. Door retaining stay(s) to hold door(s) open at 90 degrees
4. Flush 7mm triangular door locks
5. Full height mounting rails at the rear of each section
6. Internal hinges
7. Earthing points