

Trailers shown may feature optional equipment available at an additional charge.



Your Authorized United Trailers Dealer:

BUILT FAR LONG HAUL

SPECIFICATIONS XLTV - TA35, TA50/52, TA60

MODEL			8.519TA35	8.521TA35	8.523TA35	8.521TA5	8.523TA5	8.525TA5	8.527TA5	8.523TA60	8.525TA60	8.527TA60	8.529TA60
Body:	Length		18' 6"	20' 6"	22'-6"	20' 6"	22' 6"	24' 6"	26' 6"	22' 6"	24' 6"	26' 6"	28' 6"
•	Width		8' 4"	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"
Overall:	Length		21' 3"	23' 3"	25' 3"	23' 3"	25' 3"	27' 3"	29' 3"	25' 3"	27' 3"	29' 3"	31' 3"
	Width		8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"
	Height		8' 6"	8' 6"	8' 6"	8' 7"	8' 7"	8' 7"	8' 7"	8' 9"	8' 9"	8' 9"	8' 9"
Interior:	Length		18' 1-3/4"	20' 1 3/4"	22' 1-3/4"	20' 1-3/4"	22' 1-3/4"	24' 1-3/4"	26' 1-3/4"	22' 1-3/4"	24' 1-3/4"	26' 1-3/4"	28' 1-3/4"
	Width		8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"
	Height		6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 7-3/4"	6' 5-3/4"
Rear Door Opening: Width		92"	92"	92"	92"	92"	92"	92"	92"	92"	92"	92"	
		Helght	77"	77"	77"	77"	77"	77"	77"	77"	77"	77"	77"
Platform Height			17"	17"	17"	18"	18"	18"	18"	20"	20"	20"	20"
Axles			Tandem										
Axle Type		4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	
Suspension			Spring/Torsion										
Tire Size			ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST235/80R16	ST235/80R16	ST235/80R16	ST235/80R16
Load Range			С	С	С	E	E	E	E	Ε	Ε	E	E
Wheel Bolt Pattern			5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	8-Bolt/6.5	8-Bolt/6.5	8-Bolt/6.5	8-Bolt/6.5
Hitch Ball Size			2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch to Top of Ball			17"	17"	17"	18"	18"	18"	18"	20"	20"	20"	20"
Hitch Weight (% of Curb Weight)			10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%	10-15%
Avg Curb Weight (lbs.)			3120	3320	3660	3500	3840	4060	4275	4240	4460	4675	4950
GVWR (lbs.)			7,000	7,000	7,000	9800/9990	9800/9990	9800/9990	9800/9990	12,000	12,000	12,000	12,000
GAWR (lbs.)		7,000	7,000	7,000	10,000	10,000	10,000	10,000	12,000	12,000	12,000	12,000	
Avg. Payload Capacity		3880	3680	3340	6300/6490	5960/6150	5740/5930	5525/5715	7760	7540	7325	7050	

Specifications and features subject to change without notice.

STANDARD FEATURES

- 36" V-Nose
- Approximate 6'-6" Interior Height
- Protective Undercoating
- 7K Drop-Leg Jack
- Dexter Spring or Torsion Axles w/ E-Z Lube Hubs
- Ramp Door w/ Spring Assist and Beavertail*
- 5.2 White Vinyl Interior Sidewall Liner
- 16" On-Center Roof Bows
- 16" On-Center Vertical Hat Posts
- 16" On-Center C-Section Crossmembers
- .030 Smooth Bonded Aluminum Exterior
- .045 ATP Stone Guard 24" Tall
- Smooth Aluminum Fender Flares
- ATP Front Corners
- Colored Front Nose (Standard Front)
- ATP Front Nose (Slant Nose Front)
- 4ea Heavy-Duty D-Rings
- 3/4" Plywood Floor
- 32" Side Door w/ Bar Lock
- 2ea 12-Volt Interior LED Dome Lights w/ Switch
- LED Lights
- Non-Powered Roof Vent
- Flow-Thru Sidewall Vents
- Foam Sidewall Seal Aids in Dust Block
- White Mod Wheels
- Radial Tires
- 3-Year Limited Warranty





