

These rapid drying moisture extraction ovens have variable forced air extraction



Standard Specifications:

Temperature range 40°C to 250°C Dial thermostat (HYD) Stainless steel interior Fan assisted circulation* Output vent for extraction tubing Overheat safety with warning indicator Fan assisted extract unit

The exterior is constructed from sheet steel finished in easy clean stove powder paint. The interior is aluminium coated (CLAD) steel and the shelves are chromed steel grids supported on shelf runners.

The door & chamber are fitted with silicone seals for good insulation from heat and are easy to clean.

The heaters are controlled by either a hydraulic or digital PID controller.

There are 11 models in the range with capacities from 50 to 350 litres, all with the option of a variable fan assisted air extract.

Larger and bespoke models up to 4500 litres are also available.

The forced air extractor is a 'bolt-on' unit and can be easily retro-fitted to our HD heavy duty ovens if required.

Options Include:

Digital control and readout (DIG)
Maximum temperature limiter
Programmable timers and controllers
Adjustable shelf ladders
110v supply

CE

| Model | Litres | Shelf Positions | No of Shelves | External mm H x W x D | Internal mm H x W x D | Max Load Height mm | Power watts |
|---|--------|--------------------|------------------|--------------------------|--------------------------|-----------------------|----------------|
| GPME-OV-50 | 50 | 3 | 2 | 625 x 590 x 422 | 325 x 490 x 315 | 240 | 1000 |
| GPME-OV-52* | 52 | 5 | 5 | 845 x 590 x 300 | 470 x 490 x 193 | 385 | 1000 |
| GPME-OV-75 | 75 | 3 | 2 | 625 x 590 x 567 | 333 x 490 x 460 | 248 | 1250 |
| GPME-OV-100 | 100 | 4 | 3 | 735 x 590 x 567 | 445 x 490 x 460 | 360 | 1250 |
| GPME-OV-120 | 120 | 4 | 3 | 735 x 590 x 659 | 445 x 490 x 552 | 360 | 1500 |
| GPME-OV-150 | 150 | 5 | 3 | 845 x 590 x 659 | 555 x 490 x 552 | 470 | 1500 |
| GPME-OV-180 | 180 | 6 | 4 | 957 x 590 x 659 | 667 x 490 x 552 | 582 | 1750 |
| GPME-OV-210 | 210 | 6 | 4 | 957 x 590 x 749 | 667 x 490 x 642 | 582 | 2000 |
| GPME-OV-240 | 240 | 8 | 4 | 1178 x 590 x 659 | 888 x 490 x 552 | 803 | 2250 |
| GPME-OV-280 | 280 | 6 | 4 | 941 x 750 x 769 | 651 x 650 x 662 | 566 | 2250 |
| GPME-OV-350 | 350 | 7 | 4 | 1104 x 750 x 769 | 814 x 650 x 662 | 729 | 2500 |
| * no internal fan, wall mounted Extractor adds 265mm to external height of all models | | | | | | | |

As part of our policy of continuous product improvement, the specifications are subject to change without notice.

Contact us on: 01744 - 322377 Email: info@jimengineering.com