



Product Bulletin



RV, BOAT & AIRCRAFT WAX™

Product Description:

Easy to use. Quickly removes dull film, oil smudge, oxidation and light scratches on all painted, gel coat, fiberglass, chrome and aluminum surfaces. Leaves a high gloss, carnauba wax shine that lasts for months.


- **RV:** Removes oxidation, road grime and black streak marks near joints.
- **BOAT:** Removes fresh and salt water marine build-up and gives new life to gel coats. Protects against prolonged exposure to sun and salt air.
- **AIRPLANE:** Removes jet fuel build-up and reduces surface tension for maximum air speed, handling and fuel efficiency.
- **PLEXIGLAS®:** Cleans and removes fine scratches that distort vision and clarity.

Product Details:

- VOC Compliant
- NPE Free
- Phosphate Free
- pH: 8.5
- Color: Pink
- Fragrance: Floral

Packaging:

Quart: P-38-Q



Features & Benefits:

One-Step Cleaner & Wax

Removes light scratches, oxidation, black streaks, marine, & jet fuel buildup, water spots, bird droppings and More

Carnauba Wax and Polymer Resins Offer a Long Lasting High Gloss Shine

For Use on All Painted, Gel Coat, Fiberglass, Chrome and Aluminum Surfaces

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hand Use: Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (about 1 min.) and wipe off with a clean microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

Orbital or D/A Polisher: Use a PRO® PB-12 Bonnet/YU-7-C Yellow Polish Pad. Apply product to bonnet/pad. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a RV-85-C Charcoal Foam Polish Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure @ 1500-2300 rpm. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants. For added protection, finish with P-36 Cherry Finishing Wax™, P-63-Q Poly Gard™ or P-82 Carnauba Creme Wax™.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. Polish one section at a time.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

