

Name: _____ Date: _____ Track: _____	Track conditions Size: <input type="checkbox"/> Open <input type="checkbox"/> Med. <input type="checkbox"/> Tight Traction: <input type="checkbox"/> High <input type="checkbox"/> Med. <input type="checkbox"/> Low Surface: <input type="checkbox"/> Smooth <input type="checkbox"/> Med. <input type="checkbox"/> Bumpy	Result Race time / Lap: _____ Best lap (1Lap): _____
-----------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------

Front suspension

Rebound stop: _____

Kingpin ball spacer: _____

<input type="checkbox"/> E0160	<input type="checkbox"/> E2123(Steel)
<input type="checkbox"/> E0159	<input type="checkbox"/> E2124(Steel)
<input type="checkbox"/> E2218	<input type="checkbox"/> E0220(CVD)
<input type="checkbox"/> E2146	<input type="checkbox"/> E2147(1.5)
<input type="checkbox"/> E0239	<input type="checkbox"/> E0240(1mm)
	<input type="checkbox"/> E0241(2mm)
<input type="checkbox"/> E0160	<input type="checkbox"/> E2123(Steel)
<input type="checkbox"/> E0159	<input type="checkbox"/> E2124(Steel)

Kingpin ball spacer: _____

Ride height: _____

Toe angle: _____

Lower arm plate:
E2144A,B
E2154(CFRP 1mm)
E2155(CFRP 1.2mm)

Anti roll bar: _____

Upper arm spacer:

Lower arm spacer:

Upper arm position:

Lower arm position (Kick up):

Front shocks

Piston: _____ Oil: _____

Spring: _____

Shock position:

Pivot ball position: Front Rear

Damper stay: E2562(Aluminum)
E2565(CFRP)

Steering ackerman

▲Front

Front upper plate

E2148D E2158(CFRP)

Servo saver arm

E2301A E2310(Aluminum)

Rear suspension

Rebound stop: _____

Kingpin ball spacer: _____

<input type="checkbox"/> E2131	
<input type="checkbox"/> E2134(Aluminum)	
<input type="checkbox"/> E0239	<input type="checkbox"/> E0240(1mm)
	<input type="checkbox"/> E0241(2mm)
<input type="checkbox"/> E2219	<input type="checkbox"/> E0220(CVD)

Kingpin ball spacer: _____

Ride height: _____

Camber angle: _____

Lower arm plate:
E2145A,B
E2156(CFRP 1mm)
E2157(CFRP 1.2mm)

Anti roll bar: _____

Lower arm spacer:

Upright spacer:

Upper arm position:

Lower arm position (Anti-squat):

Rear shocks

Piston: _____ Oil: _____

Spring: _____

Shock position:

Pivot ball position: Front Rear

Damper stay: E2563(Aluminum)
E2566(CFRP)

Center shaft

E0223,E0259 E2228,E2229

Tension rod

Front: E2107A(Long) E2107B(Short)
 Rear: E2148C E0803(Rubber)

Weight

_____ g _____ g

Engine

Type: _____ Plug: _____ Reducer: _____
 Muffler: _____ Fuel: _____ Gasket: _____
 Engine mount: E0701(Standard) Other _____

Diff. Gear

Oil _____

Front: 44/13T 42/12T
 Rear: 44/13T 42/12T
 Center: 44T 46T
47T 48T

Tires

Front	Rear
Type: _____	_____
Compound: _____	_____
Inserts: _____	_____
Wheel: _____	_____

Clutch

3P 4P
 Clutch bell: 13T 14T
 Clutch shoes C0754 E0704 E0710 E2706
 Clutch spring 0.8 0.9 0.95 1.0 1.05 1.1

Body/Wing

Body: _____
 Wing: _____
 Wing position:

Comments

.....

