


Sidener's Energy Isolation Valve functions as a two position 3-way hydraulic valve with redundant valving elements and redundant monitoring. The purpose of the valve is to, when energized, provide a flow path for a flow of hydraulic fluid from its source to the hydraulic system. When de-energized, the valve blocks flow from the hydraulic energy source and vents the hydraulic system to tank.

- The valve's hydraulic circuitry features a series flow condition from the inlet of the valve through redundant valving elements to the discharge of the valve.
- The hydraulic circuitry also features a parallel flow condition from the discharge of the valve through either or both of the valving elements to the tank port. This configuration assures that if a valving element fails to operate as requested, inlet flow will be blocked and fluid from the outlet side of the valve is directed to tank.
- Safety Rated Monitoring Switches indicate the movement of the redundant valving elements. Operation of the Safety Rated Monitoring Switches is typically monitored by a Safety Relay or a Safety PLC supplied by others.



Contact us for Additional Assistance!




Specifications


Steel: 3000PSI / Aluminum: 3000PSI
85% of Rated Voltage
24VDC-2.35Amps /115VAC-0.52Amps
Continuous at 100% Voltage
.085110 seconds at 2500PSI
-13F to +160F
Mineral Based or Synthetic Fluids
40 to 1850 SSU (2.8 to 400 cST)
ISO Code 18/16/13 or better
Ductile - 78 pounds Aluminum - 44 pounds
Any




www.exoticautomation.com/safety


CREI-05 Specification Sheet







Drawings









Sidener Engineering 17450 Bataan Ct. Noblesville, IN 46062 (317) 773-8119 indysales@erpc.com www.sidenereng.com

A DIVISION

OF



AUTOMATION & SUPPLY

ENGINEER

G

BRAD HARRISON MINI CONNECTOR PIN CONFIGURATION

ON VALVE

303

www.exoticautomation.com/safety

Simplified CREI Circuit