

## Datasheet for Top cloth: 10-10.309

### Features

With decades of filtration experience Filtration Group B.V. has developed a cloth range to give a solution to all your filtration challenges.

Our broad range of top cloths is developed in such a way that depending on the demanded temperature range, chemical resistance and selectivity the best solution for your process can be chosen.

### Characteristics

- High strength seams - no breaks. This brings stand-down time to a minimum.
- Sewed in felt rings (where possible). This prevents mixing of different types of felt. It saves time when installing a cloth.
- Packed in plastic bags to prevent the cloths from becoming dirty.
- A sticker on the plastic bag identifies the cloths. Because the identification sticker does not touch the cloth itself there is no risk of ink or glue going into hygienic applications.

### Specifications

Cloth code	10-10.309
Cloth use	Top cloth
Material	PP
Cloth structure	Monofilament
Surface treatment	Heat-set and calendered
Filter fineness [ $\mu\text{m}$ ]	-
Air permeability [ $\text{l}/\text{dm}^2/\text{min}$ ] at 200 Pa	$80 \pm 15\%$
Maximum temperature [ $^{\circ}\text{C}$ ]	90

### Approvals

Approved according to 2004/1935/EG, declaration of conformity available on request.

### Recommendations

Use in combination with drain cloth 10-00.003 to further improve the filtration flux and the lifetime of the top cloth .

Filtration Group B.V.  
Postbus 35  
7240 AA Lochem  
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com  
www.filtration.group

December, 2017

**Order Information**

<b>Element type</b>	<b>Length</b>	<b>Ordering Code</b>
Type I	620	-
	750	-
	1000	-
	1500	72415538
	2000	-
Type II	1000	-
	1500	-
	2000	72415539
	2500	-

Filtration Group B.V.  
Postbus 35  
7240 AA Lochem  
The Netherlands

+31 (0) 57-329 77 77

info.fgnl@filtrationgroup.com  
www.filtration.group

December, 2017