J. B. Jewitt Co., Inc. Homestead Finishing Products 1935 West 96th Street Unit Q

Cleveland OH 44102-2673 Telephone: (216) 631-5309

Emergency Assistance

For emergency assistance involving this product call – 216-631-5309

Section 1: Product Identification

Product Name: TransTint® 6028A Green MSDS #:6028A Date Issued: August 23rd, 2010 Original Update X Reason For Change: General regulatory update

Section 2: Hazardous Ingredients					
Hazardous Ingredients	CAS Number	OSHA PEL (Permissible exposure limit)	ACGIH TLV (Threshold limit value)	% By Weight	EU Symbol/ Classifications
2-Propoxyethanol	2807-30-9	Not established	Not established	35-45	XN; R21/R36
Proprietary dye compound	NA	Not established	Not established	20-35	Not classified
Diethylene glycol monobutyl ether	112-34-5	Not established	Not established	10-20	XI; R36
2-Propanol, 1-methoxy	107-98-2	100 ppm	369 mg/m ³	10-20	R10
1,2-Propanediol	57-55-6	Not established	Not established	1-5	Not classified

Note: All health hazard components above 1% composition and all carcinogens above 0.1% (1000 ppm) composition are listed.

Section 3: Hazard Identification

EMERGENCY OVERVIEW: DANGER! This product is HAZARDOUS by OSHA Hazard Communication definition. Toxic. May cause central nervous system depression. Causes skin and respiratory tract irritation. Risk of serious damage to eyes. Exposure may cause nausea, headache, drowsiness and dizziness.

Hazard Rating:	NFPA	HMIS 🖂	Hazard Rating Scale:
Health:	*2		0= Minimal
Flammability:	1		1= Slight
Reactivity:	0		2= Moderate
PPE:	Χ		3= Serious
			4= Severe

Note: NFPA and HMIS ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the specific hazard. To deal adequately with the safe handling of this, or any, material, all the information in the MSDS must be considered and interpreted by a trained professional.

Potential Health Effects:

This material has **not been** tested as a whole. The data contained below is based on the properties of the individual components.

This material has been tested as a whole. The data below is based on the properties of the mixture.

Main Routes of Exposure:

	Inhalation	\boxtimes	Ingestion
\boxtimes	Skin Absorption	\boxtimes	Skin or Eye Contact

Effects of Acute (Immediate) Exposure:

s

Effects of Chronic(Long Term) Exposure:

Inhalation	Chronic exposure to organic solvents has been associated with
	various nervous system damage including permanent memory
	loss, loss of intellectual ability and loss of coordination.
Skin Contact	Irritant

Medical Conditions Aggravated by Exposure :

Persons with breathing and lung problems can be affected by breathing in any type of chemical vapor or mist. Persons with asthma, allergies, or other breathing-related problems should stay away from, not handle, and not be exposed to any product vapors or mists as a precautionary measure.

Target Organs Affected:

Blood, lungs, liver, kidneys

The components of this material are considered Carcinogenic by: Not Applicable

National Toxicology Program (NTP)

The International Agency for Research on Cancer (IARC)

The Occupational Health and Safety Administration (OSHA)

Section 4: First Aid Measures		
Eye Contact	In case of contact, immediately flush eyes with plenty of	
	water for at least 15 minutes, holding eyelids open to rinse	
	completely. Get medical aid.	
Ingestion	If swallowed, give 3-4 glasses of water but do not induce	
	vomiting. If vomiting occurs, give water again. Never give	
	anything by mouth to an unconscious person. Potential for	
	aspiration if swallowed. Get medical aid immediately. Have	
	physician determine whether vomiting or stomach evacuation	
	is necessary.	
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.	
Skin Contact	In case of contact, flush skin with plenty of soap and water.	

Remove contaminated clothing and shoes. Get medical aid if irritation, redness, swelling or skin pain develops and persists. Wash clothing before re-use.

** Note to the Physician:..... None.

Section 5: Fire Fighting Measures		
Flash Point Deg. C \square F	>141 degrees	
Auto – Ignition Temperature	Not determined	
Upper Flammable Limit (% Vol)	Not determined	
Lower Flammable Limit (% Vol)	Not determined	
Extinguishing Media	Use water fog, dry chemical, carbon dioxide or foam. Cool containers with water until well after the fire is out.	
Hazardous Combustion Products	No decomposition expected under normal conditions.	

General Information:

Firefighters should wear full protective equipment and positive pressure self-contained breathing apparatus in pressure-demand mode. Vapors may form an explosive mixture with air. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low areas. Use water spray to cool fire-exposed container surfaces.

Section 6: Accidental Release Measures	
Spill / Leak	Use proper personal protective equipment as indicated in Section 8. Stop flow of material. Absorb with inert material (e.g. dry sand, earth or other suitable absorbent), then place into a suitable container. Clean up spills immediately. Provide ventilation. Remove all sources of ignition. Use a spark-proof tool. Prevent from entering floor drains or sewers. Do not release any chemicals, dyes, or dye solutions of any type to sewers or any waterways without proper authorization from government agencies. Make appropriate notifications as required.
Sectio	n 7: Handling and Storage
Handling Procedures	Maintain good personal hygiene. Wash hands and face thoroughly after handling, and before eating, drinking or using tobacco products. Remove contaminated clothing and wash before re-use. Avoid contact with eyes, skin and clothing. Keep containers tightly closed. Do not cut, weld, braze, solder, drill, grind or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor or mist.
Storage Needs	Observe local regulations. Store in a cool (<100°F), dry, well-ventilated area away from incompatible materials (Strong oxidizing agents, strong acids, strong bases). Keep containers closed when not in use. Keep away from heat, sparks or open flames. 2-Propoxy ethanol can form unstable peroxides upon prolonged exposure to air. Keep from freezing. Keep from contact with oxidizing materials.
Section 8: Exposure Controls / Personal Protection	
Eye / Type	Wear splash-proof chemical safety goggles or safety glasses with side shields. Contact lenses should not be worn when working with chemicals.
Respiratory /Type	A half-face or full-face NIOSH-approved respirator with

exceed TLV.

organic vapor cartridge is recommended where exposures

Gloves / Type	Wear chemical resistant gloves such as butyl rubber or neoprene.
Clothing / Type	Wear long sleeved garment such as a lab coat to prevent skin
Other / Type	exposure. Facilities using or storing this product should be equipped with an eyewash facility and safety shower within 100 feet
Ventilation Requirements	from work area. Local exhaust ventilation is required to keep exposures below TLV.

Section 9: Physical and Chemical Properties

Appearance/Odor	Green liquid, solvent odor
Density (Specific Gravity)	8.2 pounds/gallon (0.98 g/ml)
Vapor Pressure/Vapor Density	Not determined
Product VOC	5.95 pounds (713 g/l)
Evaporation Rate	Not determined
Boiling Point	Not determined
Solubility in Water (%W/W)	Miscible
Freezing Point (deg. C F)	Not determined
Melting Point (deg. C F)	Not determined
рН	Not determined
Flash Point	>141°F
Flammability	Not determined
Autoflammability	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined
Partition Coefficient	Not determined

Section 10: Stability and Reactivity		
Hazardous Polymerization	Will not occur	
Stability	Stable	
Incompatibility	Strong oxidizing agents, strong acids, strong bases	
Conditions to Avoid	Ignition sources, excess heat	
Hazardous Products of	No decomposition expected under normal conditions.	
Decomposition		

Section 11: Toxicology Information	
Irritancy of Material	May cause skin, eye and respiratory irritation.
Sensitizing Capability of Material	Not determined
Carcinogenicity of Material	See Section 3
Teratogenicity	Not known
Mutagenicity	Not known
Reproductive Effects	For 2-Propanol, 1-methoxy (CAS# 107-98-2):
	(Rats, Mice and Rabbits): Exposure to 0.04 to 2 mg/kg/day
	during the first 18-21 days of gestation were found to cause
	no effects in mice and rabbits; delayed ossification was seen
	in the rat.
	(Rats): Inhalation of 3000 ppm for 6 hrs/day on day 6-15 of
	pregnancy was found to cause delayed ossification in
	offspring.
	Reproductive Effects (Rats and Rabbits): Inhalation Exposure
	to male rats and rabbits of 300, 1000 or 3000 ppm 6 hrs/day,
	5-days/week for 13 weeks did not show evidence of testicular
	effects.
Synergistic Materials	Not known

	5
Section 12: Ecology Information	
Environmental Biodegradability	Volatile and water-soluble. Not known.
Section 13: Disposal Considerations	
Waste Disposal	Waste generators must consult with federal, state and local hazardous waste regulations to ensure complete and accurate classification.
Section	14: Transport Information
U. N. # D.O.T. Classification IATA	NA 1993 Not regulated if transported by ground (Non-bulk) Combustible liquids, NOS (contains 2-propoxyethanol, 2-propano1-methoxy) 3, PG III (if shipped in containers >119 gallon) Not regulated
Section 15: Regulatory Information	
TSCA TSCA	Components of this product are listed on the TSCA Inventory or are exempt.
⊠ CERCLA	Glycol ether compounds: Listed, no RQ assigned
⊠SARA TITLE III	 This product is considered, under applicable definitions, to meet the following categories: Section 311/312: Immediate/acute health hazard Delayed/chronic health hazard Section 313: This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under Section 313 (40 CFR 372). This information must be included in all MSDSs copied or distributed for this material: 2-Propoxyethanol (CAS# 2807-30-9) Diethylene glycol monobutyl ether (CAS# 112-34-5)
CALIFORNIA PROPOSITION 65	WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
STATE RIGHT-TO-KNOW LISTING	 ✓ <u>Illinois:</u> 2-Propanol, 1-methoxy (CAS# 107-98-2)
	Massachusetts: 2-Propanol, 1-methoxy (CAS# 107-98-2)
	Minnesota: 2-Propanol, 1-methoxy (CAS# 107-98-2) 1,2-Propanediol (CAS# 57-55-1)
	New Jersey: 2-Propanol, 1-methoxy (CAS# 107-98-2)
	Pennsylvania: 2-Propanol, 1-methoxy (CAS# 107-98-2) 1,2-Propanediol (CAS# 57-55-1)

⊠ CANADA	 <u>Rhode Island:</u> 2-Propanol, 1-methoxy (CAS# 107-98-2) 1,2-Propanediol (CAS# 57-55-1) <u>Domestic Substances List:</u> Not determined WHMIS classification:
	Not determined
EUROPEAN INFORMATION	 R10 Flammable R21 Harmful R36 Irritating to eyes S7/S9 Keep container tightly closed and in a well-ventilated area S24/S25 Avoid contact with skin and eyes S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28 Afore contact with skin such immediately with
	S28 After contact with skin wash immediately with plenty of water S36/S37/S39 Wear suitable protective clothing, gloves and eye protection XI

Section 16: Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. This information is based on the material as manufactured, it may not be valid for this material if used in combination with any other materials or in any process. J.B. Jewitt Co., Inc./Homestead Finishing Products shall not be held liable for any damage resulting from handling or from contact with the product(s).

6