


Engine: Yamaha F350XCC Boat: Nautic Star® 265XTS Configuration: Single Test Date: 25-Jul-2017



PERFORMANCE DATA

RPM	МРН	GPH	MPG
1000	5.6	1.7	3.29
1500	7.3	2.9	2.52
2000	8.2	5.2	1.58
2500	13.5	7.3	1.85
3000	23.1	8.9	2.6
3500	28.9	11.2	2.58
4000	37	14.1	2.62
4500	42.1	17.6	2.39
5000	46.7	22	2.12
5500	51.7	29.4	1.76
5950	57.5	33.1	1.74

Time to Plane: 3.93 seconds 0-30 MPH: 7.3 seconds



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



NAUTIC STAR® 265 XTS

Length	26'2"
Beam	9'0"
Dry Weight (Boat Mfr. Pub)	4,200 lbs
Maximum HP	350 hp
Fuel Capacity	74 gal
Weight as Tested	5,870 lbs

F350XCC

Horsepower	350 hp
Induction	EFI
Displacement	5.3 L
Weight (Estimated)	763 lbs
Gear Ratio	1.73

ENGINE MOUNTING HEIGHT

Mounting Hole Position Ventilation Plate Height	#1 2 1/2" Above Boat Bottom	
PROPELLER(S)		
Series	Saltwater Series XL™	
Diameter x Pitch	15 1/2 x 19	
Yamaha Part #	6AW-45974-20-00	
Propeller Material	Polished Stainless Steel	

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	93° F / 80° F
Elevation (in feet above sea level)	235′
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 3/4 tank of fuel, 1 battery, optional Power Pole, optional T&H 6" hydraulic jack plate, safety and test gear.

YPB#: PB_NST_265XTS_F350XCC_2017-07-25_BAY

Boat Manufactured By: NauticStar Boats P.O. Box 26 • Amory, MS 38821 (662) 256-5636 NauticstarBoats.com

