

Miniminder Lockers



Dimensions:

Doors	Height	Width	Depth
12	970mm	600mm	200mm
20	1190mm	800mm	200mm
28	1626mm	800mm	200mm
40	1845mm	1000mm	200mm

Strength and Security with Style

Sturdy Construction: Doorframe constructed from heavy gauge mild steel of press formed channel section.

Style: Attractive and functional locker design.

Colour: Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Construction: Spot-welded and pop riveted.

Material & Finish: Mild steel-stove enamelled (see Finish specification).

Door Frame Assembly: Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section; top and bottom cross members that are designed to create doorstops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.

Doors: Doors are attached to the right hand side of doorframe upright with two 'five knuckle' semi-concealed hinges. Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder. Two rubber buffers are fitted to the top and bottom corners of the door for quiet closure.

Locking: Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Helmsman. We can also supply, as an optional extra, a door-mounted combination lock with master key over-ride facility and user codes that can be reset.

Ventilation: Ventilation is provided by a series of unique ventilation slots in the top cross member.

Paint Finish: Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The paint is applied by high-speed electrostatic rotating bells, which are computer controlled to ensure the correct thickness of paint is applied. The component parts are then stove enamelled at the correct temperature to ensure a hard paint finish is achieved.

Colour Range: Standard locker frame stove enamelled colours is: "Ice". Standard door stove enamelled colours are: "Ice", "Rockpool", "Smoke", "Nimbus", "Forest", "Skye", "Kingfisher", "Royale", "Cherry". The general brochure illustrates these colours. Exact colour samples are available.

OPTIONAL EXTRAS: The following can be supplied at an additional cost and, if included, will be specified in the quotation.

Combination Lock: The standard cam lock or latch lock can be replaced with a door-mounted combination lock with master key over-ride facility and user codes which can be reset.

Locker Numbering:

- a) Number Label – Made of transparent vinyl, with a permanent, self-adhesive back. Numbers are printed in black and can comprise one to four digits.
- b) Number Plate – Made of laminated plastic, white numbers on black, numbers can comprise one to four digits.
- c) Number Discs – Laminated plastic 25 mm diameter, white numbers on black, numbers can comprise one to four digits. The disc is holed and a split key ring is provided.

Installation: Davian offers a full installation service for its products.

For further information please contact us by email or telephone for a free quotation.

After Sales Service: All of our products are supported by the Davian Service Department who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment.

- **Health & Safety:** Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.

In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.