Building Regulations

sgg PLANITHERM TOTAL+ is the ideal low-E solution for compliance with Building Regulations relating to energy efficiency in England, Wales and the Republic of Ireland (Part L), Scotland (Section 6) and Northern Ireland (Part F).

Whole Window U-values

Thanks to its superior thermal insulating performance, SGG PLANITHERM TOTAL+ enables a wider range of frame types and designs to meet mandatory maximum and/or area weighted average whole window U-value requirements, affording greater flexibility to architects, specifiers and fabricators.

Window Energy Ratings

With its optimised balance of very low emissivity and high solar gain sag PLANITHERM TOTAL+ is one of the most energy efficient low-E glazing product available under the BFRC window energy rating scheme.

This performance advantage can help fabricators and installers comfortably meet the Window Energy Rating band C (or better) requirements of Document L of the Building Regulations using standard double glazed units for the majority of windows. Indeed many standard window designs will now achieve a minimum B rating, allowing for application to be endorsed by the Energy Savings Trust (see overleaf), with the added ability to reach the top of the range A+ ratings using double or triple glazing (depending on the complete window system).

Technical Specifications

Performance Data	DGU TGU		U	
Internal Pane	scc PLANITHERM TOTAL+			
External Pane	sgg PLANICLEAR	sgg DIAMANT	sgg PLANICLEAR	sgg DIAMANT
Composition in mm	4(16)4		4(16)4(16)4	
Low-Emissivity Coating Position	Face 3		Face 3/5	
LT	81	%	72%	73%
LRe	12%		16%	
LRi	13%		16%	
т	64%	66%	52%	53%
RE	20%	21%	25%	26%
A1	6%	3%	6%	3%
A2	9%	10%	11%	11%
А3	-	_	6%	7%
g-value	0.73	0.75	0.63	0.64
Shading Coefficient	0.83	0.86	0.72	0.74
U-value in W/m²K**				
Air	1.4		0.8	
90% Argon	1.2		0.6	

sss PLANITHERM TOTAL+ meets the durability requirements of class C of European standards EN 1096 and is CE marked.

Energy Saving Trust

The Energy Saving Recommended logo has been developed by the Energy Saving Trust to distinguish the most energy efficient products on the market.

The Energy Saving Trust is an independent, non-profit making organisation backed by the Government. Its aim is to cut emissions of carbon dioxide (CO₂) - the main greenhouse gas causing climate change - by promoting the sustainable and efficient

Windows with a B rating or higher are eligible to be endorsed by the Energy Saving Trust and (subject to approval) to use the Energy Saving Recommended logo.



High performance low-E glass products such as sgg PLANITHERM TOTAL+ are recognised as being an essential component in improving the energy efficiency of windows and can help windows to qualify for Energy Saving Recommended status.



SSS BIOCLEAN, SSS COOL-LITE, SSS DECORGLASS, SSS MASTERGLASS, SSS PLANICLEAR, SSS PLANITHERM, SSS SATINOVO MATT, SCS STADIP, SGG STADIP PROTECT, SGG STADIP SILENCE add SGG VIEWCLEAR and all other devices and logos are registered trademarks of Saint-Gobain.

Download our range of apps



milim SAINT-GOBAIN

Saint-Gobain Glass UK Ltd Weeland Road, Eggborough East Riding of Yorkshire, DN14 0FD, UK

www.saint-gobain-glass.com/uk www.planitherm-network.com



















^{*} Light and solar performance according to EN 410

^{**} Centre-pane U-values have been rounded in accordance with EN 673
For Window Energy Ratings simulators should calculate whole window U-values from first principals using normal surface emissivity ($\epsilon = 0.05$)

SGG PLANITHERM® TOTAL+

New improved advanced performance low-E glass

Our latest generation of SGG PLANITHERM TOTAL+ represents a further breakthrough in low-emissivity (low-E) performance for the UK & Ireland's leading low-E coating brand.

sgg PLANITHERM TOTAL+ is a high performance low-E glass developed in the UK, specifically for the particular needs of the UK market. It has been optimised for even better Window Energy Ratings (WERs) and as such is one of the most energy efficient window glass products available today.

Using the very latest advancements in magnetron coating technology from Saint-Gobain Glass, this new coating combines much improved processing qualities and performance, whilst maintaining the excellent aesthetics that are expected from the SGG PLANITHERM range.

Marketing campaign to promote energy efficient windows

Since 2011, Saint-Gobain Glass UK has orchestrated a high-impact marketing campaign, utilising direct mail, new campaign-based websites, e-mail, PR and advertising (TV, radio and press).

This exciting and significant promotion has supported the industry by changing the end-consumer's awareness of energy efficient windows and has elevated sgg PLANITHERM TOTAL+ to one of the most recognised low-E coating brands in the market



Created in response to consumer demand, the PLANITHERM Installer Network is a nationwide group of like-minded window installation companies who supply sgg PLANITHERM and are committed to energy efficiency.

Fabricators and Installers can sign-up by visiting our all-new website www.planitherm-network.com

Free to join, all members receive a host of great support initiatives to help generate customer leads and even rewards for installing windows containing sgg PLANITHERM.

✓ Free Member Profile on our consumer

- ✔ Free Installer Toolkit
- ✔ Free Online Training
- ✔ Free Online Marketing Portal
- ✔ Free Glazing Options Literature

site www.planitherm.com

✓ New! PLANITHERM Rewards – earn points on every PLANITHERM installation.





Applications

sgg PLANITHERM TOTAL+ is an extremely versatile low-E solution suitable for a wide range of domestic and commercial applications:

Residential:

- Windows and skylights
- Patio doors, French doors and other external doors

Commercial:

- Façades/windows
- Curtain walling
- Structural glazing
- Overhead glazing

Description

sgg PLANITHERM TOTAL+ is manufactured on the Saint-Gobain Glass UK magnetron coater. A unique combination of multiple metal oxide layers are applied to high quality sgg PLANICLEAR clear float glass using a magnetically enhanced cathodic sputtering process under vacuum conditions. The resultant microscopically thin and transparent metallic coating very effectively reflects long-wave heat radiation back into a room, thereby retaining heat within a building, whilst maximising natural light transmission.

Benefits

sgg PLANITHERM TOTAL+ offers a number of key benefits that clearly differentiate it from other low-E products, helping to give processors and window fabricators an added edge in an increasingly discerning and competitive market:

Benefits for glass processors:

- ssg PLANITHERM TOTAL+ is a 'single stock' product; the same version can be used in either annealed or toughened form. This significantly reduces stockholdings, reducing working capital, freeing up warehouse space, as well as simplifying logistics and production planning.
- the latest sgg PLANITHERM TOTAL+ has been developed to significantly improve its durability and ease of processing helping to ensure that finished units are of the highest quality.
- depending on the type of furnace and settings, SGG PLANITHERM TOTAL+ may offer improved toughening cycle times and/or reduced cycle temperatures, helping to improve throughput and lower energy costs.
- as a durable, single version product, sgg PLANITHERM TOTAL+ can help to improve processing optimisation in terms of cutting, planning, and 'right first time' yields.
- produced at the Saint-Gobain Glass
 UK float plant in Eggborough on the
 magnetron coater, sgg PLANITHERM
 TOTAL+ is available in a full range of
 thicknesses and dimensions.

Benefits for fabricators/consumers:

- Enhanced Thermal Insulation
 Double glazed units incorporating
 sgg PLANITHERM TOTAL+ offer up to
 three times more insulation than
 standard double glazing and significantly
 better thermal insulation compared to
 hard coated low-E products:
- considerable reductions in heating billseliminates cold areas around windows
- maximises the amount of natural light into the home, without haze or tint effects
 helps to reduce condensation on the inner pane
 sag PLANITHERM TOTAL+ offer level of light transmittance, not the entry of natural daylight in building. This type of coating benefits from the lack of 'haz.
- environmentally friendly solution, given the lower CO₂ emissions associated with reduced energy consumption
 ensures compliance with current
- Building Regulations requirements for all frame types or designs
 exceptional Window Energy Rating
- exceptional Window Energy Rating performance thanks to the optimised balance between a very low U-value and even higher solar gain.

• Neutral Appearance

- The sgg PLANITHERM coating is remarkably neutral in both transmission and reflection as opposed to traditional hard coated low-E products which typically suffer from a noticeable tint:
 white curtains remain looking white from outside
- no discolouration of Georgian bars

Exceptional Clarity

sgg PLANITHERM TOTAL+ offers a high level of light transmittance, maximising the entry of natural daylight into the building. This type of coating also benefits from the lack of 'haze effect' commonly associated with hard coated products.

Brand Marketing Support

By offering SGG PLANITHERM TOTAL+ fabricators and installers can sign up to be part of our unique PLANITHERM Installer Network, accessing a wealth of marketing support materials and tools to help them differentiate their offer.

Range

Stock Sizes

Thickness	Standard Sizes		
	6000 x 3210mm		
4, 6, 8, 10mm	2550 x 3210mm		
	2250 x 3210mm		

Toughened Glass:

sag PLANITHERM TOTAL+ is an offline coated low-E glass that can be used as a single version in both annealed and toughened form. Critically, once toughened, the coating retains the same technical characteristics and aesthetic qualities. For applications requiring safety glass sag PLANITHERM TOTAL+ can be readily toughened to meet the requirements of BS EN 12150.

Laminated Glass:

ssg PLANITHERM TOTAL+ is available as ssg STADIP and ssg STADIP PROTECT laminated glass in most common configurations. Laminated glass offers safety and security performance as well as UV filtration.

Processing

sage PLANITHERM TOTAL+ must always be assembled into a double or triple glazed unit. The coating is generally placed on face 3 for DGU (or face 3 / 5 for TGU), though it is possible to place the coating on face 2 without affecting the U-value. Appearance may vary slightly, so it is important to maintain consistent coating positioning throughout a particular façade.

Full guidance on handling and processing sgg PLANITHERM products are detailed in a separate document available from Saint-Gobain Glass UK.

Triple Glazing

Thanks to its optimised balance of solar gain (g-value) and thermal insulation (U-value), sgg PLANITHERM TOTAL+ is ideally suited to triple glazing applications. Typically the coating is positioned on face 3 and 5 of the IGU to provide the best Window Energy Rating performance. Triple-glazing also provides even more advanced thermal insulation properties with U-values as low as 0.6 W/m2K.

It is recommended that the centre pane is always toughened for thermal safety reasons.

Product Combinations

By combining sgg PLANITHERM TOTAL+ with other specialist glass products available from the Saint-Gobain Glass range, a multitude of high performance, multi-functional glazing solutions can be achieved.

Solar Control Glazing

The sgg COOL-LITE family presents an extensive range of solar control solutions, designed to reduce solar heat gain, thereby reducing reliance on ventilation and air conditioning systems.

Low-maintenance Glazing

sgg BIOCLEAN can be combined with sgg PLANITHERM TOTAL+ to add effective self-cleaning properties to a double glazed unit. This product combination offers a significantly more neutral and less reflective solution compared to equivalent products currently available on the market.

Acoustic Glazing

sGG STADIP SILENCE is an acoustic PVB laminated glass, which noticeably reduces noise whilst also offering the same safety and security characteristics as laminated glass.

Vision Control

sgg DECORGLASS is a range of traditional patterned glass with varying obscuration levels which can be combined with sgg PLANITHERM TOTAL+ to offer privacy in various applications.

sag MASTERGLASS (a range of contemporary geometric textured glass) and sag SATINOVO MATT (acid-etched glass) offer further design possibilities for commercial or domestic applications.


Combining sgg PLANITHERM TOTAL+ with sgg DIAMANT low-iron glass in the outer pane can improve the energy index of a given window by further increasing solar gain.

Anti-Condensation


seg VIEWCLEAR II is a neutral anticondensation coating designed to significantly reduce the number of days where external condensation may occur on an insulating glazing unit.

Outside Inside LT: 81% g: 0.73

Double-glazed unit with sgg PLANITHERM TOTAL+



Insulating glass unit with $_{\text{SGG}}$ PLANITHERM (coating on face 3)



Insulating glass unit with $_{\mbox{\scriptsize SGG}}$ PLANITHERM (coating on faces 3 and 5)



(coating on face 3)

sgg PLANITHERM TOTAL+

 $1.2\,\,\mathrm{W/m^2K}$ 4 unit with 90% argon gas filling

Light Transmittan

Light Reflectance 12%

73%



2 ● SAINT-GOBAIN GLASS CLIMATE 3 ● SAINT-GOBAIN GLASS CLIMATE