Whiteriver

wood for living


LAMINATE FLOORING

Sirver and

09/2018

What is Laminate?

The look and feel of high-quality laminate floors make them virtually indistinguishable from real wood. Unlike real wood floors, however, they are not made from solid wood. Instead, they consist of a HDF wood core layer covered with a decorative layer. Laminate flooring comes in various widths and lengths. Large formats with surrounding V-joint and nature-identical embossing are now especially popular, as they replicate genuine country house-style plank floors more convincingly than ever before. Laminate flooring that is embossed in register (EIR) in other words, the surface of the floor follows the same grain as natural wood with real indentations and graining across the plank as opposed to a totally smooth finish for an authentic look. Good laminate flooring is also robust, lightfast, easy to clean, and characterised by low emissions. A big advantage over real wood flooring, apart from being kinder on your wallet, is that you can easily install laminate yourself. A tongue-and-groove click-together system makes it incredibly simple to install attractive floors in your rooms. Laminate flooring is at home everywhere: in living rooms, kitchens and bedrooms as well as in offices and hotels. Its innovative surface structures approximate the look & feel of wood and stone more closely than has ever before achieved. There is a huge array of different decors to choose from for impressively implementing your personal decorating style. Whether you prefer classic oak or a contemporary tile look, nature-identical wood styles or trendy adaptations, imaginative patterns or unicolours, high-gloss or matt: there are virtually no limits to your creativity with laminate flooring.



These floor coverings are simple to install, hard-wearing and easy to clean. You'll enjoy them for a long time with relatively little effort. Laminate consists of approximately 90 per cent wood, a natural material. That is why it has such an eco-friendly profile and delivers both health and environmental benefits. The décor side is mostly made of high-quality paper impregnated with melamine resin. Laminate flooring thus predominantly comprises wood, a renewable raw material. Laminate flooring meets all expectations with regard to modern, personalised living. This is partly because of the huge amount of available designs and partly due to its functionality. We naturally also offer all of the required accessories, from skirting boards across impact sound insulation to cleaning aids. And so that you will continue to enjoy our floors for a very long time, they are robust, compressionproof, and strong. Laminate floors are abrasion-resistant, lightfast and stain-resistant. They are easy to clean by vacuuming or wiping with a slightly damp mop. The smooth, unbroken surfaces prevent allergy-provoking microorganisms from accumulating. What you get is a clean, hygienically flawless floor - thus making laminate especially suited for people with allergies.

HARO MOISTURE RESISTANT

9.3MM DISANO AQUA CLASSIC 4V 07

LONG PLANK

- **10MM MAMMUT PLUS LONG PLANK 4V** 13
 - 12MM MAMMUT LONG PLANK 4V 17
 - 8MM TRITTY 100 GRAN VIA 4V 23

STANDARD PLANK

- 12MM ROBUSTO 4V 33
- 12MM LIFESTYLE 4V 41
- 12MM EVEREST 4V 45
- **10MM EVEREST 4V** 49
- **10MM METRO CHESTNUTS & METRO PLUS 4V** 53
 - **10MM METRO HANDSCRAPED 4V** 59
 - **10MM METRO HIGH SHINE 4V** 61
 - **10MM METRO NARROW 4V** 65
 - **8MM HERRINGBONE 4V** 69
 - 73 8MM EXQUISIT PLUS WIDE 244MM 4V
 - 77 8MM DYNAMIC PLUS 4V
 - 8MM DYNAMIC 4V 83
 - 87 8MM EXCEL 4V

 - 7MM SMART & SMART 4V 91

ACCESSORIES

- UNDERLAYS 97 99
- WHITE PRIMED SKIRTING & ARCHITRAVE PREFINISHED SKIRTING
 - 100
 - SCOTIA 101
 - **FLOORING PROFILES** 103
 - MEASUREMENT GUIDE 104

INSTALLATION & AFTERCARE

LAMINATE CARE & MAINTENANCE 105 INSTALLATION INSTRUCTIONS 107










New Generation Flooring Suitable for Kitchens & Bathrooms. No underlay is required, manufactured with integrated Cork Underlay which reduces room and footfall sound as well as optimised walking comfort.

HARO Disano Classic Aqua I Field Oak Textured - See Page 9



9.3MM **DISANO AQUA CLASSIC**



The moisture resistant design floor for healthy living.

Disano Floors are right on trend and combine the positive features of engineered and laminate floors. They are soft, warm underfoot, hard-wearing, easy-care, quiet - and in addition, they promote healthy living. They are free of PVC, plasticizers, and phthalates and have received the Blue Angel label and Eco seal. Thanks to the additional ElastoTec layer, DISANO Classic provides a pleasantly soft walking feeling. The AquaReject core board based on natural materials is particularly resistant against swelling, making it a great alternative to tiles in bathrooms or kitchens. **The only requirement is glue-down installation in kitchens and bathrooms for water resistant rating.** DISANO Classic Aqua is available in lively, vibrant styles as well as classic, elegant colour variants.


 THICKNESS:
 9.3MM

 BOARD SIZE:
 2035 X 235 X 9.3MM

 BOX QUANTITY:
 5 PANELS / 2.39M2

 USE CLASS:
 33 / AC5





A moisture resistant high density fibreboard (HDF) with built in cork underlay and durable decorative surface.

DISANO Classic Aqua in trendy Plank 1-Strip format can also be installed in wet rooms (A0) if glued down. With its AquaReject coreboard based on natural materials it is especially resistant to moisture.

Soft and durable decorative surface layer

Authentic wood appearance. The surface layer is resilient, soft and pleasantly warm, protects the floor and ensures excellent durability and ease of maintenance. Resistant to fading under UV light – no colour change.

Pressure Distribution Layer

Semi-flexible, water-resistant and free from PVC and plasticisers. The ElastoTec layer provides additional elasticity and walking comfort. It protects the floor from dents and penetrating moisture while ensuring

Coreboard with moisture protection (5 mm)

The AquaReject core board based on natural materials is particularly resistant against swelling. This is why DISANO Classic Aqua is also suitable for glue-down installation in damp rooms (A0). improved stability.

Integrated cork insulation underlay

High-density cork insulation underlay for room and footfall sound reduction as well as for optimum walking comfort (1.2mm). No additional insulation underlay needed. Suitable for use with underfloor heating:Thermal resistance 0.063 m2 K/W.




OAK VINTAGE GREIGE RUSTIQUE TEXTURED 4V C1418035 (HARO ID 536249)



COUNTRY OAK GREY RUSTIQUE TEXTURED 4V C1418042 (HARO ID 536251)




WILD OAK TEXTURED 4V C1418041 (HARO ID 535700)



SAND OAK TEXTURED 4V C1418038 (HARO ID 535703)



FIELD OAK TEXTURED 4V C1418040 (HARO ID 536247)



TOBACCO OAK TEXTURED 4V C1418044 (HARO ID 536248)



CRYSTAL OAK TEXTURED 4V C1418043 (HARO ID 536242)



C1418039 (HARO ID 535699)




THICKNESS: 9.3MM **BOARD SIZE:** 2035 x 235 x 9.3MM **BOX QUANTITY:** 5 panels / 2.39M2 **USE CLASS:** 33 / AC5









10MM MAMMUT PLUS LONG PLANK

The best and more. This is the promise of the new decors of the MAMMUT PLUS collection from Kronotex. While exhibiting the same technical mastery as all MAMMUT flooring, this offers you even more authenticity, an even larger choice of styles and even greater perfection. Apart from its incredible robustness and versatility, MAMMUT PLUS also raises the bar in other ways. Its extra-wide panels complement the existing extra-long and extra sturdy versions of the MAMMUT family. And the decors seduce you with their elegantly authentic natural wood look, which can't help but add posh country style comfort to your home.

 THICKNESS:
 10MM

 BOARD SIZE:
 1845 X 244 X 10MM

 BOX QUANTITY:
 4 PANELS / 1.80M2

 USE CLASS:
 33 / AC5








MACRO OAK LIGHT GREY 4V C2212028



MACRO OAK BEIGE 4V C2212029




Ρ8

eir

MACRO OAK WHITE 4V C2212027

ALSO AVAILABLE IN 12MM

COMPATIBLE PROFILE COLOUR SEE PAGE 102





HIGHLAND OAK BLACK 4V C2212044



HIGHLAND OAK SILVER 4V C2212026



P12



NORTHLAND OAK 4V C2212045



MACRO OAK NATURE 4V C2212020

10MM MAMMUT PLUS 4V LONG, WIDE PLANK

THICKNESS: 10MM **BOARD SIZE:** 1845 x 244 x 10MM **BOX QUANTITY:** 4 panels / 1.80M2 **USE CLASS:** 33 / AC5



188MM 1845MM 12MM

12MM MAMMUT LONG PLANK

For many, the best is just about good enough. And if you are always striving towards perfection as well, then there is only one floor for you: MAMMUT from Kronotex. It combines the best features of ROBUSTO, DYNAMIC and EXQUISIT, and is thus the absolute Nonplus-Ultra of laminate floors. Whether used universally, for extremely heavy loads or to create a sophisticated and natural look, MAMMUT is a floor which can meet all requirements. The panels are extra hard, extra long and, what's more, extra practical. An outstanding feature of the patterns and hues is their country cottage character and the fascinating, authentic natural wood look.

 THICKNESS:
 12MM

 BOARD SIZE:
 1845 X 188 X 12MM

 BOX QUANTITY:
 4 PANELS / 1.387M2

 USE CLASS:
 33 / AC5





EVEREST OAK WHITE 4V C2212014



MACRO OAK BROWN 4V C2212040



MOUNTAIN OAK NATURE 4V C2212041



HIGHLAND OAK SILVER 4V C2212031



EVEREST OAK 4V C2212010



MOUNTAIN OAK GREY 4V C2212042



MACRO OAK NATURE 4V C2212023



MOUNTAIN OAK BEIGE 4V C2212043



EVEREST OAK BRONZE 4V C2212006



EVEREST OAK NATURE 4V C2212009



MACRO OAK GREY 4V C2212039



EVEREST OAK GREY 4V C2212013



EVEREST OAK BEIGE 4V C2212008




THICKNESS: 12MM **BOARD SIZE:** 1845 x 188 x 12MM **BOX QUANTITY:** 4 panels / 1.387M2 **USE CLASS:** 33 / AC5













Extra long, extra wide, particularly authentic: a genuine trendy product with a length of 2200 mm and a width of 243 mm. Our boards in Gran Via format create an amazing, spacious appearance. The characteristic look of Gran Via planks is emphasised by bevelled edges: the edges of the planks are chamfered on all four sides. This way, the plank character is emphasised in an impressively vivid way – just like real engineered flooring.

The Gran Via 4V design makes rooms remarkably more spacious and gives them a POWERFUL RADIANCE, regardless of the style. This makes the floor a key element for an ambience of openness.

HARO Laminate Floors have double moisture protection thanks to their well balanced multilayer Construction and unique aquaTec system.

THICKNESS:	8MM
BOARD SIZE:	2200 X 243 X 8MM
BOX QUANTITY:	5 PANELS / 2.68M2
USE CLASS:	32 / AC4



Tritty 100 Gran Via: Authentic Surfaces

Wood has a wonderful feature: its feel. During many decades of wood processing we have gained the experience and feeling for authentic wood surfaces. This is why we offer our HARO Laminate Floors in four surface variants. This way, you can experience laminate floors that are abound with naturalness. In our product range you will find any surface texture to emphasise the chosen style and selected format in a natural way.

Simple Installation

Life is complicated enough as it is. Luckily, our HARO Laminate Floors are easy to install. With our Top Connect installation system, we offer a technology that makes the installation of floors child's play. And you benefit from it, whether you let a craftsman install your floor or you do it yourself.

Quietness

A floor for relaxed living should radiate a warm atmosphere, and be durable and easy to maintain. When it is also as guiet as a whisper, it is perfectly suitable for all areas of your home where there is a lot of hustle and bustle. For this we have developed the unique *ComforTec technology - it has proven to be the world's quietest laminate floor with a sound reduction of up to 60 percent. This makes HARO Laminate Floors with Silent CT the perfect floors for children's rooms, dining rooms and all other areas where life is pulsating. An intriguingly elegant and quiet floor.



The Gigantic One. Extraordinary appearance and distinctive plank character by bevelled edges on four sides. **Dimensions:**

8 x 243 x 2200 mm



*ComforTec is available on all floors at an additional cost - please allow an additional 4-5 weeks for delivery.



Tritty 100 Gran Via: Authentic Finishes



EIR Authentic

Almost indistinguishable from real wood. Texture and style match perfectly. The gloss level emphasises the character and the natural look of the wood reproduction.



Textured Matt Similar to real wood grain. The matt appearance underlines the natural look.



EIR Authentic Matt Almost indistinguishable from real wood. Texture and style match perfectly. The surface has a natural oil character. The Plank 1-Strip designs also have a slight shine effect in the pores.




Soft Matt Distinctive velvety soft surface. Natural and matt with a slight gloss effect in the texture.



4V Bevel on all sides The edges are bevelled on both sides and ends – for an even more vivid impression. The expert calls this "long and short side bevelling".

Stair Nosing



HARO Tritty 100 Gran Via Stair Nosing

- 60 x 60 x 2180mm Click engages both sides
- Re-enforced aluminium corner
- 4-5 week lead time
- Precision solution for a seamless appearance
- Available to special order alternatively with overlap joint on riser. Must be specified at time of ordering




Wooden stairs are in line with the latest interior design trends. Puristic furniture and large glass areas correspond with floors, walls and stairs that radiate warmth and provide texture. Therefore, laminate flooring on stairs is attracting more and more fans. HARO offer the perfect solution for contemporary interior stair design with its current and cutting-edge laminate flooring.

We believe it is important that stairs, corners and edges also look good in rooms with HARO floors. We therefore offer the matching stair nosings for your HARO flooring.

For more information please visit: www.haro.com/en/interior/haro-stairs-stair-trim







VINTAGE OAK 4V C1418011 FINISH: TEXTURED MATT (HARO ID 526712)



OAK PORTLAND NATURE 4V C1418037 FINISH: AUTHENTIC EIR (HARO ID 533141)



OAK PORTLAND AMBER 4V C1418030 FINISH: AUTHENTIC EIR (HARO ID 533142)



ALPINE OAK GREY 4V C1418018 FINISH: AUTHENTIC MATT EIR (HARO ID 526711)




OAK CONTURA NATURE 4V C1418032 FINISH: AUTHENTIC EIR (HARO ID 535273)



OAK DUNA LIMED 4V C1418023 FINISH: AUTHENTIC EIR (HARO ID 530340)



ZEBRA OAK 4V C1418031 FINISH: SOFT MATT (HARO ID 535270)



CHESTNUT BIANCO 4V C1418026 FINISH: TEXTURED MATT (HARO ID 530303)




FINISH: AUTHENTIC EIR (HARO ID 530340)






OAK VENETO SAND 4V C1418028 FINISH: AUTHENTIC MATT EIR (HARO ID 535271)



OAK CONTURA BLACK 4V C1423024 FINISH: AUTHENTIC EIR (HARO ID 533144)



OAK PORTLAND GREY 4V C1418027 FINISH: AUTHENTIC EIR (HARO ID 533139)



ALPINE OAK NATURE 4V C1418005 FINISH: AUTHENTIC MATT EIR (HARO ID 526709)



OAK VENETO CREME 4V C1418029 FINISH: AUTHENTIC MATT EIR (HARO ID 535269)



P13

SMOKED OAK ITALICA 4V C1418020 FINISH: AUTHENTIC EIR (HARO ID 530333)




THICKNESS: 8MM BOARD SIZE: 2200 x 243 x 8MM BOX QUANTITY: 5 panels / 2.68M2 USE CLASS: 32 / AC4









12MM ROBUSTO 4V

There are situations in life where one needs a thick skin. Where one has to be very resilient and tough. Which is why ROBUSTO is also the perfect floor for extreme levels of use. With its high-density, 12mm thick fibreboard and an especially wear-resistant surface, it can cope with pretty much anything to which it is exposed. Even if used for commercial purposes. Its CLIC tongue-and-groove connection system will never disappoint in any situation as it was specially developed to hold up under the highest pressure.

 THICKNESS:
 12MM

 BOARD SIZE:
 1375 X 188 X 12MM


 BOX QUANTITY:
 5 PANELS / 1.293M2

 USE CLASS:
 33 / AC5









AMERICAN WALNUT 4V* C2210008




RIP OAK WHITE 4V C2210007





RUSTIC OAK 4V C2210027



CAROLINA WALNUT 4V C2210032



RIP OAK NATURE 4V C2210009

HIGHLAND OAK 4V C2210002



OAK MIST 4V C2210029



HARBOUR OAK 4V C2210004



RIP OAK 4V C2210001





FANTASY WOOD 4V C2210014



PETTERSSON OAK DARK 4V C2210015



TIMELESS OAK GREY 4V C2210010




THICKNESS: 12MM BOARD SIZE: 1375 x 188 x 12MM BOX QUANTITY: 5 panels / 1.293m2 USE CLASS: 33 / AC5

* American Walnut is 1380 x 193 x 12mm (1.332m2 pack) Note: This floor is produced in a sister factory of Kronotex.









12MM LIFESTYLE 4V

If you love life you will love lifestyle. Luxurious, luscious and longevity are just some of the aspects of this stylish Lifestyle range. Contrasting styles, colours and textures, combined with a strong AC4 abrasion class and 5G Click System makes this range the perfect choice for any location.

THICKNESS:	12MM
USE CLASS:	32 / AC4
CARLINGFORD OAK	1380 X 193 X 12MM (1.332M2 PACK)
KINSALE WALNUT	1380 X 193 X 12MM (1.332M2 PACK)
SUMMER OAK GREY	1375 X 188 X 12MM (1.293M2 PACK)







SUMMER OAK GREY 4V C2210028



CARLINGFORD OAK 4V C2220005






THICKNESS: USE CLASS: CARLINGFORD OAK KINSALE WALNUT SUMMER OAK GREY

12MM 32 / AC4 AK 1380 X 193 X 12MM (1.332M2 PACK) 1380 X 193 X 12MM (1.332M2 PACK) I375 X 188 X 12MM (1.293M2 PACK)





12MM EVEREST 4V

The peak of good taste and authenticity. With EVEREST 12MM 4V you are assured of a floor that will enhance the look of any room. Warm toned decors create a comforting ambience and make a classic foundation on which to base your room interior. EVEREST 12MM 4V features a 4V four way bevel on all edges.

 THICKNESS:
 12MM

 BOARD SIZE:
 1215 X 166 X 12MM

 BOX QUANTITY:
 5 PANELS / 1M2

 USE CLASS:
 31 / AC3








RECLAIMED PINE 4V C2213002





THICKNESS: 12MM BOARD SIZE: 1215 x 166 x 12MM BOX QUANTITY: 5 panels / 1M2 USE CLASS: 31 / AC3





10MM EVEREST 4V

The peak of good taste and authenticity. With EVEREST 10MM 4V you are assured of a floor that will enhance the look of any room. Warm toned decors create a comforting ambience and make a classic foundation on which to base your room interior. EVEREST 10MM 4V features a 4V four way bevel on all edges.

THICKNESS:	10MM
USE CLASS:	31 / AC3
HARBOUR	1216 X 197 X 10MM (1.44M2 PACK)
TUDOR OAK	1215 X 193 X 10MM (1.41M2 PACK)
WINDSOR OAK	1215 X 125 X 10MM (1.82M2 PACK)









HARBOUR OAK 4V C1817001



WINDSOR OAK 4V C1816001 (NARROW BOARD)





THICKNESS:	10MM
USE CLASS:	31 / AC3
HARBOUR	1216 X 197 X 10MM (1.44M2 PACK)
WINDSOR OAK	1215 X 125 X 10MM (1.82M2 PACK)
TUDOR OAK	1215 X 193 X 10MM (1.41M2 PACK)



193MM 1380MM 10MM

10MM METRO CHESTNUTS & METRO PLUS 4V

The METRO CHESTNUT 4V collection is a unique collection of 3 specially selected chestnut decors in varying tones, all featuring the realistic embossed in register surface. A 10mm board with a hard wearing AC5 coreboard means these floors will stand up to the toughest demands. METRO CHESTNUT 4V features a 4V four way bevel on all edges. The METRO PLUS 4V collection continues to grow. It sets new trends. It defines the avant-garde and creates classics. The authentic wood decors, the variety of surface structures, easy installation and 4 way bevels are governed by the same guiding concept: to enable new ideas. METRO PLUS 4V features a 4V four way bevel on all edges.

THICKNESS: 10MM BOARD SIZE: 1380 x 193 x 10MM BOX QUANTITY: 6 panels / 1.60M2 USE CLASS: 33 / AC5







CHESTNUT 4V C1810003



CHESTNUT NATURE 4V C1810002





THICKNESS: 10MM BOARD SIZE: 1380 x 193 x 10MM BOX QUANTITY: 6 panels / 1.60M2 USE CLASS: 33 / AC5





OAK RUSTIKAL 4V AC5 C1810004



MONACO OAK 4V AC5 C1810007








THICKNESS: 10MM BOARD SIZE: 1380 x 193 x 10MM BOX QUANTITY: 6 panels / 1.60M2 USE CLASS: AC4 / AC5



10MM METRO HANDSCRAPED

A beautiful floor is the basis for a beautiful home. Embodying the precious traces of time, the floors in the METRO HANDSCRAPED 4V range reveal their beauty with a traditional hand-scraped finish. Warm, inviting colours and a unique surface result in an every day elegance with timeless charm. METRO HANDSCRAPED 4V floors features a 4V four way bevel on all edges.



 THICKNESS:
 10MM

 BOARD SIZE:
 1285 X 192 X 10MM

 BOX QUANTITY:
 7 PANELS / 1.73M2

 USE CLASS:
 32 / AC4






AGED ASH 4V C1814001







10MM METRO HIGH SHINE 4V

From the country house to the penthouse, METRO HIGH SHINE 4V never fails to impress in any situation. A hard wearing, high shine surface finish reflects good taste and quality. The 159mm width boards give a spacious timelessness. Let your interiors shine with a floor from the METRO HIGH SHINE 4V range. METRO HIGH SHINE 4V features a 4V four way bevel on all edges.

 THICKNESS:
 10MM

 BOARD SIZE:
 1380 X 159 X 10MM

 BOX QUANTITY:
 8 PANELS / 1.76M2

 USE CLASS:
 32 / AC4



N.B. While laminate floors are hard wearing and have a high degree of scratch resistance, they are not completely scratch proof and care should be taken to protect your floor surface. It is always beneficial to use protective felt pads under moveable furniture, chairs, table legs, doormats in entrances etc. (to protect your laminate floor against moisture, dirt and sand). Please note that wear and tear on darker coloured laminates or high shine surfaces may be more visible.





DROP LOCK SYSTEM For products that use Drop Lock System, we do not recommend underlays thicker than 3mm.



VIENNA WALNUT 4V C1813006

Ľ-


SORRENTO OAK 4V C1813005

TIRANA HICKORY 4V C1813003



THICKNESS: 10MM BOARD SIZE: 1380 x 193 x 10MM BOX QUANTITY: 8 panels / 1.76M2 USE CLASS: 32 / AC4





10MM METRO NARROW 4V

The METRO NARROW 4V range combines conventional beauty with contemporary style and thus lends that special something to every setting. METRO NARROW 4V floors are narrow and long, which creates a particularly graceful look. Metro NARROW 4V features a 4V four way bevel on all edges.

THICKNESS:	10MM
BOARD SIZE:	
Amsterdam / Valetta Walnut	1383 X 116 X 10MM
Atlantic Walnut	1380 X 159 X 10MM
BOX QUANTITY:	
Amsterdam / Valetta Walnut	8 PANELS / 1.28M2
Atlantic Walnut	7 PANELS / 1.54M2
USE CLASS:	32 / AC4







AMSTERDAM OAK 4V C1813006 Drop Lock Installation

D6 VAL


VALETTA WALNUT 4V C1811003 Drop Lock Installation **ATLANTIC WALNUT 4V** C1811005 *5G Installation*



THICKNESS:	10MM
BOARD SIZE:	
Amsterdam / Valetta Walnut	1383 X 116 X 10MM
Atlantic Walnut	1380 X 159 X 10MM
BOX QUANTITY:	
Amsterdam / Valetta Walnut	8 PANELS / 1.28M2
Atlantic Walnut	7 PANELS / 1.54M2
USE CLASS:	32 / AC4



ARRIVING 2019




8MM HERRINGBONE LAMINATE

The classic Herringbone design can be traced back to the Romans who used the design in the construction of roads to add strength. The pattern became know as "Herring - Bone" as it resembles the out line of a fish skeleton. The Renaissance periods between the 14th and 17th centuries saw the design being used in many aspects of architectural design including flooring.

Traditional real wood Herringbone has long been a desirable choice to add a touch of class to any room or entrance hallway. Laminate manufacturing expertise has now been developed to bring you a high quality affordable alternative.






ARRIVING 2019



LINDOW OAK 4V C1610003





ASCOT OAK 4V C1610001


CHESTER OAK 4V C1610002



THICKNESS: 8MM BOARD SIZE: 665 x 133 x 8MM BOX QUANTITY: 14 panels / 1.24M2 USE CLASS: 32 / AC4

Note: Floors must be perfectly level before installing laminate Herringbone. Any variation in floor levels must be corrected prior to installation.





8MM EXQUISIT PLUS WIDE 244MM

Exquisit Plus Wide 4v - 244mm wide boards give an expansive feel to any room. Spaciousness and elegance go hand in hand to create an exquisit ambience. exquisit plus wide 4v floors feature embossed in register surfaces for that realistic wood look from a laminate floor. Exquisit plus wide features a 4V four way bevel on all edges.







RECLAIMED OAK / HARBOUR OAK 4V C1413001

PETTERSSON OAK NATURE 4V C1413005



BARN OAK / HARBOUR OAK GREY 4V C1413002



VILLAGE OAK 4V C1413016



eir

THICKNESS: 8MM **BOARD SIZE:** 1380 x 244 x 8MM BOX QUANTITY: 8 panels / 2.694M2 USE CLASS: 32 / AC4



193MM 1380MM 8MM

8MM **DYNAMIC PLUS 4V**

DYNAMIC PLUS 4V - All the features of a DYNAMIC floor with the added benefit of an embossed in register for that realistic wood look from a laminate floor. It can be used anywhere, is extremely resilient and, above all else, offers a unique variety of patterns and hues. All this makes DYNAMIC PLUS 4V the perfect floor for your ideas. DYNAMIC PLUS 4V features a 4V four way bevel on all edges.








VICTORIAN OAK 4V C1411007



BRACKEN OAK 4V C1411008





NORDIC OAK 4V C1411011



OAK CHATEL 4V C1410011









193MM 1380MM 8MM


8MM **DYNAMIC** 4V

A floor with which you can express your entire individuality. DYNAMIC 4V can be used anywhere, is extremely resilient and, above all else, offers a unique variety of patterns and hues. Whether you choose the rich, dark hues of Augusta Walnut or the traditional tones of Irish Oak, you will be assured of stunning floor whose performance matches its good looks. DYNAMIC 4V features a 4V four way bevel on all edges.

THICKNESS:	8MM
BOARD SIZE:	1380 X 193 X 8MM
BOX QUANTITY:	8 PANELS / 2.131M2
USE CLASS:	32 / AC4







IRISH OAK 4V C1411005

AUGUSTA WALNUT 4V C1411006





193MM 1380MM 8MM



The EXCEL 4V range will win you over with its unique range of three brand new decors. 8mm boards with AC4 abrasion class rating can be used throughout the home, bringing a natural and durable wood look to your home's spaces. Floors that are made to be enjoyed for a long time. EXCEL 4V features a 4V four way bevel on all edges.







BREWERY OAK 4V C1410001



PORTER OAK 4V C1410002

KINSALE OAK 4V C1410009



P8

SKELLIG OAK 4V C1410012

8MM Excel 4V

P4



193MM 1383MM 7MM

7MM SMART & SMART 4V

Enjoy decorating your home to your own individual tastes. A SMART laminate floor features an outstanding price/performance ratio. The warmth and look of a real wood floor with the reliability and convenience of a laminate floor. The SMART range features a plank, a two strip and one 3-strip decors. All floors in the SMART range are square edge. Excellent value combined with warm, inviting wood decors make SMART a wise choice for any home. A price conscious and classic choice for your room that does not compromise on style or elegance. The SMART 4V range features three attractive oak plank decors. SMART 4V features a 4V four way bevel on all edges.







SUMMER OAK NATURE 4V C1211007



BURREN OAK 4V C1211008









TICINO WALNUT 3-STRIP C1210002

SUTTER OAK C1210003




THICKNESS: 7MM **BOARD SIZE:** 1383 X 193 X 7MM BOX QUANTITY: 9 PANELS / 2.40M2 **USE CLASS:** 31 / AC3

Underlays

Underlay is the foundation to all professional floor installations therefore it is essential that the correct product is specified to suit conditions and customer expectations of performance. We recommend using a good quality underlay for all hard subfloors, whether they are made of cement, wood substrate, ceramic or synthetic. You consequently increase the resilience of the floor, absorb indoor and footfall sound and level minor irregularities in the subfloor. We recommend that you use polythene over concrete subfloors in addition to underlay.







3MM PE FOAM

Code: F1010002/ F1010001 Coverage Per Roll/Pack: 15/25m2 Roll Size: 3mm x 1m x 15/25m TOG Rating: 0.81 Impact Sound Reduction: 16db Underfloor Heating: Not Suitable Compressive Strength: Poor Heat Transfer Resistance: 0.081 k/w m²

2MM CORK

Code: F1010004 Coverage Per Roll/Pack: 20m2 Roll Size: 2mm x 1m x 20m TOG Rating: 0.41 Impact Sound Reduction: 17db Underfloor Heating: Yes Compressive Strength: Good Heat Transfer Resistance: 0.041 k/w m2

2MM HEAT MASTER PERFORATION


Code: F1010014 Coverage Per Roll/Pack: 10m2 Roll Size: 2mm x 1m x 10m TOG Rating: 0.35 Impact Sound Reduction: 20db Underfloor Heating: Yes Compressive Strength: Very Good Heat Transfer Resistance: 0.035 k/w m2


3MM ACOUSTIC BLUE

Code: F1010007 Coverage Per Roll/Pack: 10m2 Roll Size: 3mm x 1m x 10m TOG Rating: 0.88 Impact Sound Reduction: 22dB Underfloor Heating: Yes (< 8mm Laminate) Compressive Strength: Very Good Heat Transfer Resistance: 0.088 k/w m2



DROP LOCK SYSTEM For products that use Drop Lock System, we do not recommend underlays thicker than 3mm.









3MM ULTRASTRONG

Code: F1010015 Coverage Per Roll/Pack: 10m2 Roll Size: 3mm x 1m x 10m TOG Rating: 0.60 Impact Sound Reduction: 22db Underfloor Heating: Yes (≤ 8mm Laminate) Compressive Strength: Excellent Heat Transfer Resistance: 0.060 k/w m2

3MM SOUNDMASTER


Code: F1010012 Coverage Per Roll/Pack: 10m2 Roll Size: 3mm x 1m x 10m TOG Rating: 0.67 Impact Sound Reduction: 20db Underfloor Heating: Yes (≤8mm Laminate) Compressive Strength: Good Heat Transfer Resistance: 0.067 k/w m2

3MM SILENT PLUS

Code: F1010011 Coverage Per Roll/Pack: 10m2 Roll Size: 3mm x 1m x 10m TOG Rating: 1.20 Impact Sound Reduction: 23db Underfloor Heating: Not Suitable Compressive Strength: Very Good Heat Transfer Resistance: 0.120 k/w m2

4MM GOLD PLUS EXTRA

Code: F1010013 Coverage Per Roll/Pack: 15m2 Roll Size: 4mm x 1m x 15m TOG Rating: 0.90 Impact Sound Reduction: 20db Underfloor Heating: Not Suitable Compressive Strength: Good Heat Transfer Resistance: 0.090 k/w m2




RE VITA LIZE

YOUR HOME -

Timber floors need a minimum 10mm expansion gap around all edges where the floor is meeting skirting or fixed structures such as kitchen islands. This is essential for natural movement of the floor as room temperatures change throughout the year. The quick fix DIY solution is to leave gap at existing skirting and cover with a small angled piece of timber known as "scotia". The professional installer and discerning home owner will take the opportunity to add another dimension to their project by replacing the skirting and cutting the base of the door frame. This effectively allows the floor to float under the skirting and door frame for a flawless finish and makes installation easier.

White Primed Skirting & Architrave Options

White primed skirting and architrave continue to grow in popularity. Each length is pre-primed ready for you to add your own finish. Choose crisp white for clean lines or contemporary shades to match surrounding decors. Our profiles are made from moisture-resistant MDF.



PRE FINISHED SKIRTING OPTIONS

Our pre-finished foil wrapped skirtings come in handy 2.4m lengths and are perfect for replacing old skirting while the 16mm scotias are the ideal size for covering expansion gaps should you wish to leave existing skirting in place. Full range of matching scotia are also available for this range.




SCOTIA


FOIL WRAPPED SCOTIA DIMENSIONS: 16MM X 16MM X 2400MM






FINISHING TOUCHES Flooring Profiles


















WRG1 FLAT SELF ADHESIVE 900mm & 1800mm *All Colours*



WRG2 REDUCER SELF ADHESIVE 900mm & 1800mm *All Colours*



WRG3 EDGE SELF ADHESIVE 1800mm All Colours



WRG4 SCREW DOWN REDUCER / FLAT 900mm & 1800mm Silver & Gold Only It is important to complete your floor with quality finishing touches. Whiteriver flooring profiles come in a variety of different styles and colours to help create a seamless and streamline look for your installation. AC4 rating ensures a lasting finish.





FINISHING TOUCHES Commercial Profiles

BY WHITERIVER

Precision German manufacturing ensures a professional finish for all applications. The base section is secured to the substrate with screws while the top section can be adjusted and removed at any time. Suitable for installation in high use commercial areas.



Euro Step Stair Nosing 320 Silver 2700mm 7mm - 16mm F1625043



Transition 588 2-Part Screw Down Silver 2700mm 10mm - 16mm F1627005



End 587 2-Part Screw Down Silver 2700mm 10mm - 16mm F1627006



Reducer 586 2-Part Screw Down Silver 2700mm 10mm - 16mm F1627007

Measurement Guide

	Feet&Inches	3'3"	4'11"	6'6"	8'2"	9'10"	11'5"	13'1"	14'9"	16 [°] 5"	18'0"
Feet&Inches	Metres	1.0M	1.5M	2.0M	2.5m	3.om	3.5M	4.om	4.5m	5.om	5.5M
			-		_	-				-	
	1.000	1.0002	a =	a a m ²	0 F m ²	a a m2	o = m ²	• • • • • • •	4 = 1002	= 0 m2	- - m ²
3'3"	1.0M	1.0M ²	1.5m ²	2.0 m ²	2.5 m ²	3.0 M ²	3.5 m²	4.0 m ²	4.5m ²	5.0 m²	5.5 m²
4'11''	1.5M	1.5 m²	2.3 m ²	3.0m²	3.8m²	4.5m²	5.3m²	6.0 m²	6.8m²	7.5 m²	8.3m²
6'6"	2.0M	2.0 m ²	3.0 m²	4.0m ²	5.0 m ²	6.0 m²	7.0m ²	8.0 m ²	9.0 m²	10.0 m ²	11.0 m ²
00	2.011	2.0111	3.0111	4.011	5.011	0.0111	7.0111	8.0111	9.011	10.0111	11.0111
8'2"	2.5M	2.5 m²	3.8m²	5.0 m²	6.3M ²	7.5M ²	8.8 m²	10.0 M ²	11.3 M ²	12.5M ²	13.8m²
9'10"	3.om	3.0 m²	4.5m ²	6.0 m ²	7.5M ²	9.0 m²	10.5m ²	12.0 M ²	13.5 m ²	15.0 m ²	16.5 m ²
	0.011	0.5.11	40		,	J					
		2	2	2			2		- 2		
11'5"	3.5M	3.5m²	5.3m²	7.0M ²	8.8m²	10.5 m ²	12.3 M ²	14.0M ²	15.8m ²	17.5 m ²	19.3M ²
13'1"	4.om	4.0 m²	6.0 m²	8.0 m²	10.0 m ²	12.0 m ²	14.0m²	16.0 m ²	18.0 m²	20.0 m ²	22.0 m ²
14'9"	4.500	4.5m ²	6.8m²	9.0m ²	11.3 M ²	12 F m ²	15.8m²	18.0 m ²	20.3 m ²	22.5m ²	24.8m ²
14 9	4.5M	4.5111	0.0111	9.011		13.5 M ²	13:0111	10:0111	20.311	22,5111	24.0111
16 [°] 5"	5.0M	5.0m²	7.5M ²	10.0 m²	12.5M ²	15.0 m²	17.5M²	20.0 M ²	22.5M ²	25.0 m²	27.5M ²

Example - Room measuring 3m x 4.5m = 13.5m2

Laminate Care & Maintenance



Modern, responsible households build on environmentally safe products that are easy to use. Decades of know how influenced the revolutionary development clean & green. The result is a perfect product which makes cleaning and care of high quality floors easier than ever before. Designed for the special requirements of modern, responsible households, the clean & green products are not only easy to use and very eco friendly, but also highly efficient: Each bottle is good for 40 applications. All clean & green products are kind to the environment. You can tell this by checking the list of precious ingredients – and by the EU Eco Flower label. The Flower is an international ecolabel that is awarded to products and services meeting high environmental and performance standards.

Laminate floors are antistatic and dirt-repellent. That's why those with allergies also increasingly choose this floor because where there's no dust, house dust mites have no chance. It is hygienic and very easy to look after.

Dry Cleaning

Laminate floors are very easy to maintain. Dry cleaning with a mop, broom or vacuum cleaner is generally all you need to do. Marks and dirt can be wiped off with a slightly damp cloth, following the grain of the plank.

Damp Cleaning

Damp Cleaning. We recommend that laminate floors be cleaned with clean & green active where damp cleaning is required. Add dosage cap of clean and green active to 5 litres of water. Cleaning should then take place with well rung out mop or slightly damp cloth. This point is critical to the correct maintenance of your floor. Don't clean the floor with excessive amounts of water and always avoid letting water stand on the surface.

Other Tips

In order to maintain the quality and beauty of the floor, but also for your own personal well being, an indoor climate of approx. 50% - 60% relative air humidity is ideal with a room temperature of approx. 20° C. N.B. While laminate floors are hard wearing and have a high degree of scratch resistance, they are not completely scratch proof and care should be taken to protect your floor surface. It is always beneficial to use protective felt pads under moveable furniture, chairs, table legs and doormats in entrances etc. (to protect your laminate floor against moisture, dirt and sand). Please note that wear and tear on darker coloured laminates or high shine surfaces may be more visible.



For regular dry cleaning of the Laminate floor coverings, we recommend using a vacuum cleaner. For regular damp cleaning of the Laminate floor coverings, we recommend flat microfibre mops.



1 Lt. Aqua Shield500ml Intensive Active CleanerF2012022F2012018

Steam cleaning machines are not suitable for use on laminate floors.

General Guidelines

- Leave boxes unopened in room for 48 hours prior to installation.
- Inspect all boards in daylight for any visible faults or defects before installation.
- · Check the sub-floor is level and even before installation.
- Install 0.2mm/500 gauge polythene on all concrete surfaces to provide a vapour barrier.
 All polythene joints should be overlapped and taped.
- Consult instructions and website for full details on site conditions and moisture content of subfloor.


The moisture content of cement screeds should be 2.0% CM (3% on red scale Tramex Concrete Encounter). For anhydrite/pump screeds with underfloor heating, the moisture content should be 0.3% CM (1.6% on red scale Tramex Concrete Encounter).


- Use a good quality flooring underlay for your floor.
- Select board direction e.g. towards light or longest room dimension.
 This floor requires no glue and has a simple click system.
- Never install kitchen units / islands on top of floor as this will restrict natural movement and may cause the floor to lift.
- Install as a floating floor with room for expansion around perimeter.
 Follow installation instructions for first and second row.
- Where the same floor is being installed through adjoining rooms it is important to leave a 10mm expansion gap under each door and install suitable profile.
- Stagger joints by 30 40 cm thereafter.
- Select finishing profiles, skirting, pipe covers, doorway slips.
- Use felt pads and protective castors underneath furniture legs. Please use suitable cleaning products for aftercare.
- Installation instructions may vary. See pack for details.


Floors must be perfectly level before installing laminate Herringbone. Any variation in floor levels must be corrected prior to installation.


Disano Aqua Classic must be glued down to achieve water resistant rating.














Installing your floor

