



## AXPOLY® PP51 1033

**Product information sheet:** Black copolymer polypropylene resin, filled grade

**Description:** A filled polypropylene grade that delivers greater stiffness in moulded components, plus a higher flexural modulus where stability under load is important.

Export tariff code: 3902100010

### Product physical properties

Product grade: Axpoly® PP51 1033

Test parameter	Method	Unit	Value
Physical properties			
Density	ISO 1183	g/cm <sup>3</sup>	1.01
Rheological properties			
Melt Flow (2.16 kg @ 230°C)	ISO 1133	g/10mins	7
Mechanical properties			
Tensile strength (@ 23°C)	ISO 527	MPa	20
Flexural Modulus (@ 23°C)	ISO 178	MPa	1500
Notched Izod Impact strength (@ 23°C)	ISO 180	kJ/m <sup>2</sup>	4

**Please note** this polymer is not approved for use in food, medical or toy applications. All grades are tested to ISO standards, and certified as ROHS and REACH compliant.



The data is provided as a guide only and does not create any liability, warranty or guarantee of performance. The values may vary from the above information and do not indicate specific limits. This document does not create any liability, warranty or guarantee of product performance. It is the buyer's responsibility to determine the suitability of the material for the end application.

[www.axiongroup.co.uk/AxpolyPolypropylene](http://www.axiongroup.co.uk/AxpolyPolypropylene)

Indigo Street, Off Langley Road South, Salford. M6 6RX  
 Tel. +44 161 737 6124  
 E. [info@axionpolymers.com](mailto:info@axionpolymers.com)