

Damar Highway Instacure

Description

UV radiation curable paint specially formulated for spray applied line marking on new or old sealed roads. It offers rapid cure and hardening by LED light with excellent adhesion and abrasion resistance to both hot-mix and chip-seal with good glass bead retention-reflectivity.

Features

- UV radiation cure road paint that will dry instantly after spray application and eliminate traffic hold up during conventional paint application.
- There is no minimum coning off time for this product as it is instant cure.
- Can be applied to new seal after 4 weeks.
- Application over waterborne coatings.
- Excellent resistance to abrasion and weathering.
- High elasticity.
- Good adhesion, water and thawing salt resistance.
- High whiteness and long-time retro-reflective life.

Limitations

- Do NOT use on Paving Stones
- Do NOT apply when ambient temperature is below 5°C or above 40°C
- Do NOT apply to WET roads

Only use Damar approved coated beads with this product.

- Application to concrete is problematic due to large variations in drying agents and surface finishes available, plus surface contaminations.
- For application to concrete surfaces please refer to concrete application sheet

Properties

Resin System	Radiation Curable Acrylate
SG	White 1.50 Yellow 1.37
Finish	Matt
Colour	White and yellow
Dilution Rate	Use as Supplied
Volume Solids	100%
Theoretical Coverage	4.0 – 5.0 m ² /litre @ 200 – 250µ DFT

Number of Coats	Generally 1
Thinning Solvent	Maximum 250ml of UV Thinning solvent per 20L pail
Clean Up	UV Wash

Surface Preparation

Direct application to hotmix asphalt and chip seal. New surfaces should be left for 4 weeks and be free from oil film. This can be removed by water jet blasting. Direct application to concrete is NOT recommended.

Approvals

New Zealand NZTA M/7 2017
White CEO, ALO
Yellow Interim approval pending

Storage Stability

- 6 months in original sealed package.
- Product must be stored under cover in a cool dry place.
- Protect from Frost.

Damar Highway Instacure

Standard Packaging

20L White Pail ARK0170
200L White Drum ARN0170
20L Yellow Pail ARK1970
200L Yellow Drum ARN1970

Accessory materials

- UV Wash to rinse and clean only.

Safety Regulations

Flash Point	>100°C
D.G.Classes	6.5B (contact), 6.4A, 6.3A, 9.1D
UN No.	3082
Packaging Group	III

Disposal

Dispose with care according to local regulations.

Note: The use of personal protective equipment such as safety glasses, gloves, overalls etc. is mandatory when handling these products.

Refer to Material Safety Data Sheet for this product.

NEW ZEALAND: Eastgate Business Park, 800 Te Ngae Road, Rotorua
PO Box 7084, Te Ngae, Rotorua 3042, New Zealand
P: 0800 33 44 75 **F:** 0800 33 44 76 **E:** orders@damarindustries.co.nz
www.damarindustries.co.nz

AUSTRALIA: 25 Hargraves Place, Wetherill Park, NSW, 2164
PO Box 6599, Wetherill Park 2164, Australia
P: +61 2 9756 4511 | **F:** +61 2 9756 0985
www.damarindustries.com.au

DISCLAIMER: This information is not a specification and is given in good faith. Since conditions of use are beyond the manufacturers control, all information given is without warranty, implied or otherwise, and is not intended to be exhaustive. Final determination for sustainability of the product for the use contemplated is the sole responsibility of the user. It is also the users responsibility to ensure that all information is current prior to using the product.