




ATN

PIAF 1100R

Mast boom lift PIAF 1100R





PIAF 1100R

ADVANTAGES OF PIAF 1100R

- Large outreach.
- Designed and manufactured for heavy-duty use.
- Compact size.
- Easy to maintain.
- Large autonomy (oversized battery).

STANDARD FEATURES

- Non-marking rubber tyres.
- Progressive hydraulic joystick transmission.
- Driving operated by a hydraulic joystick.
- 575 Ah 24 V centralized battery filling system.
- 85 A battery charger.
- 3 drive speeds.
- Lifting facilities.
- Emergency hand-pump.
- Battery indicator with 80% discharge cut-off.
- Tilt indicator with buzzer.
- Overload sensor.
- Hour meter.
- Strong large size platform.

OPTIONS

- Air line to platform.
- 220V AC power to platform.
- Automatic power cut-off if tilt value >2°.
- Flashing light.
- Motion alarm.
- Special paint colour(s).

	PIAF 1100R
Working height	11 M (36 ft. 2,54 in.)
Platform height	9 M (29 ft. 46,34 in.)
Horizontal reach	3,74 M (12 ft. 27 in.)
Lift capacity (indoor, 2 persons, no wind)	200 Kg (441 lbs.)
Lift capacity (outdoor, 1 person, wind <28 mph)	120 Kg (264,6 lbs.)
Turntable rotation	2x110 °
A Platform width	0,90 M (2 ft. 9,5 in.)
B Platform length	0,80 M (2 ft. 6,2 in.)
C Length	3,05 M (10 ft.)
E Width	1,03 M (3 ft. 3,4 in.)
F Height - stowed	2,14 M (7 ft. 0,21 in.)
D Wheelbase	1,20 M (3 ft. 11,24 in.)
Drive speed - stowed	4,8 Km/h (2,98 Mph)
Drive speed - raised	1,0 Km/h (0,62 Mph)
Gradeability - stowed	20 %
Maximum tilt value	2 °
Weight	3200 Kg (7055 lbs.)
Max.ground bearing pressure	10,4 Kg/cm2

CE This product complies with European regulations in force (EN 280). Due to our constant improvement policy, ATN reserves the right to make any modifications without any prior notice.



Rue André Thevet,
Z.I.Guillaume Mon Amy Fauillet 47400 FRANCE
+33 (0) 553 798 320 +33 (0) 553 880 107
<http://www.atnplatforms.com>

