

ROTOMAX 1,5

Flexible, space-saving, strong as an ox



ROTOMAX 1,5 F

Order Nr. 110 205 (230 V, 50 Hz, 1 Ph) 27,4 kg

- Continuously variable speed regulation via keypad.
- Speed gauge in LED display.
- Speeds: 500 to 15,000 rpm.
- Soft start/integrated brake.
- Available with foot (F), with trolley (STM) or as suspended version (HM)

WB 4
Order Nr. 110 220

FH 4 (6 mm)
Order Nr. 57 570 01

WI 4 (3 mm)
Order Nr. 57 661 01

WIG 7
(M14) 2,7 : 1
max. 25 000 rpm
Order Nr. 49 608 04

WB 7 (6 mm)
Order Nr. 110 221

FH 7 (6 mm)
Order Nr. 49 530 01

WI 7 (6 mm)
Order Nr. 57 645 01

WI 7-45° (6 mm)
Order Nr. 57 662 01

FH 10 (6 mm)
Order Nr. 57 170 01

WI 10 (6 mm)
Order Nr. 57 645 03

WI 10-45° (6 mm)
Order Nr. 57 662 03

WB 10
Best.-Nr. 110 222

DIN 10

NA 4 x 1250 DIN10/G16 Order Nr. 30 002 02

NA 7 x 1500 DIN10/G22 Order Nr. 30 007 02

NA 10 x 2000 DIN10/G28 Order Nr. 30 026 03

NA 12 x 2000 DIN10/G28 Order Nr. 30 029 02

G16

G22

G28

G28

FSM 1:1
Order Nr. 57 891 01

FH 12 (12 mm)
Order Nr. 48 265 01

BSG 10/50
Bestell.-Nr. 52 630 01