

ChannelPlus H37XL Series 2

Electronic Programm



A three channel programmer giving independent timing of each channel on a 7 day programme.

Ideal for the control of two heating zones as well as hot water via separate thermostats and zone valves.

- Back-lit LCD display
- Preset clock
- Automatic Winter / Summer time changes
- Simplified menu driven programming
- Advance and boost on each channel
- Full 7 day operation
- Volt free version
- 5 year warranty



ChannelPlus H37XL Series 2

Programmer with 7 day setting over 3 independent channels (e.g. Zones 1, 2 and 3 or hot water, heating 1 and 2)

Designed for use with fully pumped central heating systems using three separate 2 port zone valves.

Part L1 of the Building Regulations requires properties above 150 sq m floor space to have two separate heating zones.

This is an ideal application for the H37XL.

Also available:

ChannelPlus H37VXL

The same as the H37XL but with volt free contacts

Specification

CONTACT RATING	3 (1) Amps 230V AC
CONTACT TYPE	Micro-disconnection Voltage free (not H37XL)
SUPPLY	230V 50 Hz
POLLUTION DEGREE	Degree 2
ENCLOSURE PROTECTION	IP30
DOUBLE INSULATED	Yes
OPERATING TEMPERATURE RANGE	0° C to 40 °c
BATTERY LIFE	Lithium
CASE MATERIAL	Thermoplastic flame retardant
DIMENSIONS	101 x 163 x 37 mm
DISPLAY	Back lit liquid crystal
CLOCK	24 hour or 12 hour AM/PM
DISPLAYED TIME	
ADJUSTMENTS	1 minute steps
SWITCHED TIME	
ADJUSTMENTS	10 minute steps
PROGRAMME OPTIONS	ON, OFF, All Day, Auto & Holiday
OPERATING PERIODS	
PER DAY	3 for each channel
OVERRIDE (EACH CHANNEL)	1 or 2 hour boost 1 or 2 hour extension to ON period Instant advance
MOUNTING	9 pin wall fixing plate
RATED IMPULSE VOLTAGE	Cat 2 – 2500V
POLLUTION DEGREE	Degree 2
ENCLOSURE PROTECTION	Flame retardant thermoplastic