

Description: The NGSG for Hygienic Applications uses a transparent FEP tube and stainless steel ends. The ends are swaged to provide a crevice free bore throughout with the FEP tube providing a rugged, shatterproof enclosure. The unit can be supplied with a variety of hygienic end fittings to suit customer requirements.



Approvals: FDA 21CFR177.1550

Features:

- 316 stainless steel or FEP contact with product, using hygienic fittings
- Shatterproof sight tube for maximum safety
- Uses the series 7000 swaging system for crevice free fitting connection
- Length to suit customer requirements
- Available with or without guard
- Materials of construction suitable for hygienic use

	Dimensions			
	NB inches	DN mm	Id mm	Wall Thickness
	½	15	12.7	2.5
	¾	20	19.1	3.2
	1	25	21.7	3.2
	1½	40	34.4	3.2
	2	50	47.1	3.2
	2½	65	58.8	3.7
	3	80	72.5	4.5
	4	100	97.9	5.5

- Options:**
- 1) End fittings - Hygienic end connections RJT, IDF/ISS, DIN, SMS, Tri-clamp etc.,
 - 2) Elbows - fixed.
 - 2) Fittings Materials - Hastelloy C22, C276.
 - 3) Guarding - None, mesh or slotted stainless steel.
 - 4) Application - Can be engineered into flexible hose assemblies.

Please consult Flexrite for Working Pressures and Temperatures.

Website : www.flexrite.co.uk

E-mail: enquiry@flexrite.co.uk

Tel : +44 (0)1933 673699

Fax : +44 (0)1933 675819

19 The Trinity Centre
Park Farm Industrial Estate,
Wellingborough, NN8 6ZB