



# BANCE



## SMITHLIGHT MODEL INI20LR

NR CAT No: 0054/039168

LU CAT No: Plant/9238



Also available as Intrinsically Safe (Model EX90L) for explosive environments. IECEx, Zone 0 Group I, Group IIA T2 IP65. Please contact us for details.

- Robust solid construction manufactured from ABS747IP65
- Shock absorbing rubber fitted to base, rubber seal on lid
- UV and saltwater resistant
- 2 directional independent light heads or dual direction
- 60° angle directional light positioning
- Adjustable height light head
- Generates no (or very little) heat
- Low battery warning
- Mains charger and vehicle charger
- Battery, chargers and light unit all contained within easy to carry robust case

R BANCE AND CO LTD

Cockcrow Hill House, St. Marys Road, Surbiton, Surrey KT6 5HE, UK

Tel: +44 (0)20 8398 7141 Fax: +44 (0)20 8398 4765 e-mail: [admin@bance.com](mailto:admin@bance.com) URL: [www.bance.com](http://www.bance.com)

# BANCE

## Specification

Weight: 7.7 Kg  
Open Height: 1120 mm  
Closed Height: 600 mm  
Width: 334 mm  
Depth: 220 mm  
Lumen: 2160

## Charging

240v AC Mains Charger (options available)  
12/24v DC Vehicle Charger  
Recharge in 7 - 8 Hours

## Operation

10 - 12 hours continuous use with one light head  
5 - 6 hours continuous use with two light heads  
2 adjustable height levels  
2 directional light options or dual direction option  
Tilting head

## Features

1 hour remaining warning light and sounder  
10,000 hours (approx) battery life  
Remote control



R BANCE AND CO LTD

Cockcrow Hill House, St. Marys Road, Surbiton, Surrey KT6 5HE, UK

Tel: +44 (0)20 8398 7141 Fax: +44 (0)20 8398 4765 e-mail: admin@bance.com URL: www.bance.com