00 44 (0) 1702 542554 00 44 (0) 1702 542558 sales@wnealservices.com www.wnealservices.com

## WNS Flat 'S' Cleat Rollformer (FSC20)

Manufactured by W. NEAL SERVICES LTD.


W. NEAL SERVICES LTD
29 Purdeys Way
Purdeys Industrial Estate
Rochford
Essex
SS4 1ND
ENGLAND













**WNS** 20swg (1.0mm) 'S' CLEAT ROLLFORMERS are 9 station machines. They are principally used in the HVAC industry for joining two ducts together in conjunction with drive cleat and plain seam rolls. Flat 'S' cleat rolls are fitted inboard with external double extended shafts, onto which many auxiliary rolls can be fitted. WNS Rollformers are manufactured with all steel side plates. The shafts, forming rolls, gears and guide fences are all hardened, and needle bearings are fitted throughout.

SPECIFICATIONS											
Model:	Speed: Motor Power:		Supply Voltage:	pply Voltage: Length:		Height:	Weight:				
FSC20	8.0m/min	2HP, 1.5kW	415v, 3 Phase	1650mm	615mm	1000mm	300Kg				

Revised: Jan 2018


CE





## WNS Flat 'S' Cleat Rollformer (FSC20)

Manufactured by W. NEAL SERVICES LTD.

W. NEAL SERVICES LTD 29 Purdeys Way Purdeys Industrial Estate Rochford Essex SS4 1ND ENGLAND







\*Optional Rolls which can be fitted to auxiliary shafts.

CE

SPECIFICATIONS												
Auxiliary Rolls:	'S' Cleat Rolls Fitted Inboard:	Small Pittsburgh Lock *:	Drive Cleat *:	Double Seam*:	Plain Seam*:	Right Angle Flange*:	Standing Seam*:	3 in 1*:	Safe Edge*:	Closed Double Seam*:		
Sections:	(Standard)	ļ						 				
Maximum Thickness:	0.8mm	0.8mm	1.0mm	1.2mm	1.0mm	1.6mm	0.8mm	0.8mm	0.8mm	1.2mm		
Material Used:	92mm	25mm	54mm	32mm	11mm	11mm	54mm	-	-	32mm		
Seam Width:	27mm	10mm	29mm	13mm	10mm	-	-	-	8.0mm - 10mm	13mm		
Flange Height:	-	-	-	-	-	Max. 11mm	-	-	ī	-		
Seam Height:	-	-	-	-	-	-	19mm	15mm	-	-		

## Other Products in our Range....







