

CO₂ Dry Ice Cleaning Systems

The PHX-150 Dry Ice Cleaning System delivers powerful dry ice blasting capabilities in an economical, highly mobile unit. The most aggressive pneumatic pellet cleaning system on the market today!





The cleaning system uses .114" (2.9 mm) pellets that are produced with TOMCO₂ Sytems' High Pressure Pelletizers. We offer high pressure pelletizers from 100 lbs. (90.72 kg) to 1000 lbs. (453.60 kg). You can produce as many pellets as you need in each particular situation, or use TOMCO₂ Sytems' Storage Boxes to maintain an insurance supply at all times. The pellets last up to two weeks when stored in TOMCO₂ Sytems' boxes.



TOMCO₂ Systems 3340 Rosebud Road Loganville, Georgia 30052 USA 1-800-832-4262 рн 770-979-8000 **Fx** 770-985-9179 E-mail: info@TOMCOsystems.com www.TOMCOsystems.com

Advantages

- Convenient front hook-up for quick air hose connection
- Safety interlocks and guards prevent accidental contact with moving parts
- 14" wide body navigates easily through doorways and into tight spaces
- Reinforced stainless steel construction and durable molded castors
- Quick release airlock for fast cleaning or inspection
- Customer Support available 24 hours, 7 days a week

Nozzles and Extension

Various nozzle sizes available for specific cleaning requirements.

Specifications

- Dimensions: 14" x 18.5" x 45.75" (W x L x H) (36cm x 43cm x 116cm)
- Dry Weight: 140 lbs. (63kg)
- Hopper Capacity: Over 100 lbs. (45.5kg) of pellets
- Ice Consumption Rate: .05 lbs. 7 lbs. (.023kg 3.2kg)/min
- Supply Air Pressure Range: 70 psi 125 psi (4.8 - 8.6 bar)
- Air Consumption Range: 100 CFM 250 CFM
- Blast Pressure Range: 50 psi 125 psi (2.8 - 8.6 bar)
- Inlet Air Temperature: 140° F (60° C) maximum
- Inlet Air Connection: 1" FNPT