











The UK's & Ireland's Leading Refrigeration Rental Company

# REFRIGERATION RENTALS



With over 40 years experience in the commercial refrigeration business we understand the demands owning commercial refrigeration can put on your business. That's why we offer flexible refrigeration rental solutions to suit any requirement.

We have a complete range available for hire including Multi Decks, Serve Overs, Spot Merchandisers, Glass Door Cabinets, Chest freezers, Wall & Well Freezers, Island Displays, Patisserie Fridges and much more. Our clients include many of Ireland's & The UK's largest retail groups, food producers, market researchers, media companies and events & exhibitions organisers. We have the equipment, knowledge and experience to deliver first class fridge rental solutions on time and on budget.

In the events & exhibitions sector we have expanded our fridge rental service to the worlds largest Food & Drink trade shows, providing the highest quality refrigeration equipment to a wide range of International clients.







Multi Deck Chillers	
Ouverture	3
Opera	4
Opera SV	5
Venere	6
Cardboard Chiller	7



Serve Over Counters	
Kristina	8



Spot Merchandisers	
Galileo Spider	9
Alpha	10



Patisserie Displays	
Glass Sided Freezer	11
Rotating Chiller	12
Georgia III	13
Georgia Cube	14



Glass Door Display Chillers & Freezers	
Single Upright Chiller	15
Double Upright Chiller	16
Single Upright Freezer	17
Double Upright Freezer	18





## 100% Fridge Rental Flexibility: Short, Medium or Long Term Hire

Whether for a few days, a couple of weeks, to meet seasonal promotions, for trade fairs and exhibitions, new product launches or for long term rental, Refrigeration Rentals offers you the refrigerated display unit that perfectly matches your needs.

- \* Complete flexibility on rental term.
- \* Manageable payment structures.
- \* Match your cash outlay to your income.
- \* No maintenance or service costs.
- \* The highest quality and most modern equipment supplied.
- \* Full delivery, installation and collection service.

IRL Telephone: +353 1 4271010 UK Telephone: +44(0)1925 658315

**Email:** 

info@hire-innovation.com



Food and beverage symbols used throughout this brochure







Retail Freezers	
Symphony Wall & Well Freezer	19
Rondo Dual Temperature Island	20



Chest Freezers & Ice Cream Freezers	
Aran	21
Burren	22
Line	23
Soft Scoop Freezer	24



Chilled & Frozen Storage	
Upright Catering Chillers	25
Upright Catering Freezers	26
Gastronorm Prep Counters	27



Undercounter Chillers & Freezers	
Single Door Under Counters	28
Back Bar Chillers	29



Dome Salad Counters	
Showmaster Dome	30









The 'Ouverture' Chilled Multi Decks are perfect for merchandising large quantities of chilled produce such as packed meats, dairy products, bottled drinks and packed sandwiches. The Multi Deck fridges are ideal in grab-and-go environments such as supermarkets, and for events & exhibitions.

#### Key Features of Ouverture

- \* Stylish, modern design
- \* Fully automatic operation
- Switchable interior light
- LAE Digital Temperature display
- Adjustable temperature
- \* 4 adjustable shelves + base shelf
- Suitable up to 25°C at 65% RH
- \* Temperature range: +1°C/+5°C
- Comes with heavy duty castors
- \* Multi-plexable for increase in flexibility

#### Additional Options

- \* Mirrored/glass end walls
- Available with doors on special request
- \* Night-blinds
- \* Additional shelving
- \* Branding
- \* Ticket strips
- \* Perspex risers

# Technical specifications for Ouverture

Product Code	MD100	MD130	MD190	MD250
Total Length With End Walls	997 mm	1310 mm	1935 mm	2560 mm
Total Length w/out End Walls	937 mm	1250 mm	1870 mm	2500 mm
Total Depth	845 mm	845 mm	845 mm	845 mm
Total Height (Inc Castors)	2000 mm	2000 mm	2000 mm	2000 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp	<b>16</b> amp
Nominal Power Consumption	1199 Watts	1419 Watts	1883 Watts	2824 Watts
Temperature Range	+1°C/+5°C	+1°C/+5°C	+1°C/+5°C	+1°C/+5°C
Interior/Exterior finish	Grey/White	Grey/White	Grey/White	Grey/White
Number of shelves	4 adjustable + base			
Refrigerant Type	R404A	R404A	R404A	R404A







The 'Opera' Chilled Multi Decks are perfect for merchandising large quantities of chilled produce such as packed meats, dairy products, bottled drinks and packed sandwiches. The Multi Deck fridges are ideal in grab-and-go environments such as supermarkets, and for events & exhibitions.

#### Key Features of Opera

- Stylish, slim-line design
- \* Fully automatic operation
- Switchable interior light
- \* LAE Digital Temperature display
- \* Adjustable temperature
- \* 4 adjustable shelves + base shelf
- Suitable up to 25°C at 65% RH
- \* Temperature range: +1°C/+5°C
- Comes with heavy duty castors
- \* Multi-plexable for increase in flexibility

#### Additional Options

- Mirrored/glass end walls
- \* Available with doors on special request
- Night-blinds
- Additional shelving
- \* Branding
- Ticket strips
- \* Perspex risers

#### Technical specifications for Opera

Product Code	MDS100	MDS130	MDS190
Total Length With End Walls	997 mm	1310 mm	1935 mm
Total Length Without End Walls	937 mm	1250 mm	1870 mm
Total Depth	705 mm	705 mm	705 mm
Total Height (Inc Castors)	2000 mm	2000 mm	2000 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	1199 Watts	1419 Watts	1883 Watts
Temperature Range	+1°C/+5°C	+1°C/+5°C	+1°C/+5°C
Interior/Exterior finish	Grey/White	Grey/White	Grey/White
Number of shelves	4 adjustable + base	4 adjustable + base	4 adjustable + base
Refrigerant Type	R404A	R404A	R404A









Semi-Vertical Multi Deck for the attractive display of fast-moving convenience foods products.

#### Key Features of Opera SV

- Low energy lighting and fans
- \* Sophisticated control unit for temperature control and shorter running cycles
- \* Multi-plexable for increase in flexibility
- Adjustable shelving
- \* No. of shelves: 4 + base
- \* Temperature range: +1°C/+5°C
- \* Refrigerant: R404A
- \* Power required: 13 amp supply

#### Additional Options

- \* Branding
- \* Ticket strips
- \* Perspex risers

# Technical specifications for Opera SV

Product Code	HHMD70	HHMD100	HHMD130
Total Length With End Walls	760 mm	997 mm	1310 mm
Total Length Without End Walls	700 mm	937 mm	1250 mm
Total Depth	705 mm	705 mm	705 mm
Total Height (Including Castors)	1460 mm	1460 mm	1460 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	1129 Watts	<b>1199 Watts</b>	1419 Watts
Temperature Range	+1°C/+5°C	+1°C/+5°C	+1°C/+5°C
Interior/Exterior finish	Grey/White	Grey/White	Grey/White
Number of shelves	4 adjustable + base	4 adjustable + base	4 adjustable + base
Refrigerant Type	R404A	R404A	R404A







Slim-line Multi Deck suitable for areas where space is a premium.

#### Key Features of Venere

- The perfect refrigerated display case for in-store promotions and events
- \* Fascia's can be fully branded on special request
- \* Fully automatic operation
- \* Digital temperature display
- \* Adjustable shelving
- \* No. of shelves: 4 + base
- \* Adjustable temperature
- Refrigerant: R404A
- Temperature range: +1°C/+4°C
- Switchable interior light
- Comes with castors as standard
- \* Comes with fabric night-blind
- \* Power required: 13 amp supply

#### Additional Options

- \* Branding
- \* Ticket strips
- \* Perspex risers

# Technical specifications for Venere

Product Code	SMD70	SMD130
Total Length	702 mm	1330 mm
Total Depth	700 mm	700 mm
Total Height (Including Castors)	1850 mm	1850 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	600 Watts	1096 Watts
Temperature Range	+1°C/+5°C	+1°C/+5°C
Interior/Exterior finish	Grey	Grey
Number of shelves	4 adjustable + base	4 adjustable + base
Refrigerant Type	R404A	R404A









The perfect refrigerated display case for short-term product launches, store promotions and events & exhibitions.

#### Key Features of Cardboard Chiller

- Easy to assemble design Only takes 2 minutes.
- Completely customisable to suit any product range.
- \* No need for vinyl The cardboard graphics can easily be replaced to suit your current marketing project.
- \* Long Life The Cardboard chiller box unit can be reused for 5+ years approx.
- \* Lightweight and easy to transport.
- \* These units are designed for short-term (up to 3 months) product launches and promotions.
- \* The Cardboard Chiller is ideal for beverages and dairy products.
- \* LED lighting on each shelf level for enhanced presentation.
- Please note that this product is available for sale only. Contact our sales team for more information.





#### Technical specifications for Cardboard Chiller

Product Code	CARDBC
Total Width	480 mm
Total Depth	440 - 540 mm
Total Height (With Header)	2000 mm
Total Height (Without Header)	1690 mm
Power Supply Required	<b>13</b> amp
Nominal Power Consumption	0.4 KW per hour
Temperature Range	+4°C to +7°C
Interior/Exterior finish	Cardboard
Number of shelves	3 + base
Refrigerant Type	R290A











Curved glass serve over for the attractive display of fresh produce.

#### Key Features of Kristina

- Narrow refrigerated display cabinet ideally suited for use where space is limited
- \* Designed with an integral condensing unit
- \* Kristina display area is made of stainless steel
- \* Frontal curved glass is manufactured from tempered safety glass
- \* Toughened safety glass tilts forward
- \* Internal lighting for brighter display
- \* Under counter refrigerated storage
- \* Working prep area to rear of cabinet
- Heavy duty castors
- Stainless steel fish trays available on request
- \* Rear doors available on request
- \* Lightweight and easy to move

#### Additional Options

- Stainless steel ice trays for fish
- Dividers
- \* Perspex sliders
- \* Step deck
- \* Artificial grass

#### Technical specifications for Kristina

Product Code	KS0130	KS0160	KS0190	KS0260
Total Length	1285mm	1585 mm	1885 mm	2585 mm
Total Depth	960 mm	960 mm	960 mm	960 mm
Total Height (Inc Castors)	1260 mm	1260 mm	1260 mm	1260 mm
Power Supply Required	<b>1</b> 3 amp	<b>13</b> amp	<b>1</b> 3 amp	<b>13</b> amp
Nominal Power Consumption	447 Watts	447 Watts	557 Watts	667 Watts
Temperature Range	+1°C/+5°C	+1°C/+5°C	+1°C/+5°C	+1°C/+5°C
Interior/Exterior finish	Grey	Grey	Grey	Grey
Refrigerant Type	R404A	R404A	R404A	R404A











Spot Merchandiser for the display and sale of chilled products.

#### Key Features of Galileo Spider

- Steel bumper bar
- \* The front is glazed and the sides are plexi glass
- \* Unlimited multiplexing available
- \* Can be tilted for maximum product exposure
- \* Temperature Range: +1°C/+4°C
- Available with adjustable feet or castors.
- \* Power required: 13 amp supply

## Technical specifications for Galileo Spider

Product Code	SM100	SM125
Total Length	1000 mm	1250 mm
Total Depth	1200 mm	1200 mm
Total Height (with feet)	880 mm	880 mm
Total Height (with castors)	885 mm	885 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	850 Watts	850 Watts
Temperature Range	+1°C/+4°C	+1°C/+4°C
Interior/Exterior finish	Grey	Grey
Refrigerant Type	R404A	R404A







Alpha is the new plug-in refrigerated spot merchandiser with ventilated refrigeration (RV) that's ideal for displaying and promoting cold cuts, cheeses and dairy products, as well as pre-packaged and fresh food products.

This entirely transparent unit offers maximum product visibility, and can be strategically placed in order to encourage purchases on behalf of the customers.

#### Key Features Alpha

\* No. of shelves: 2 + base.

\* Temperature range: +1°C/+5°C

\* Refrigerant: R404A

Power required: 13 amp supply

## Technical specifications for Alpha

Product Code	SMSV130
Total Length	1280 mm
Total Depth	1200 mm
Total Height (Including feet)	1305 mm
Power Supply Required	13 amp
Nominal Power Consumption	1200 Watts
Temperature Range	+1°C/+5°C
Interior/Exterior finish	Grey
Number of shelves	2 + base
Refrigerant Type	R404A



# **GLASS SIDED FREEZER**

**Upright Glass Display Freezer** 







Upright glass sided freezer display cabinet for the display and preservation of frozen products.

#### Key Features of Glass Sided Freezer

- \* Fully automatic operation
- \* Fixed shelving double glazed door
- \* 100% CFC free
- \* Static cooling
- Castors fitted as standard
- Manual defrost
- \* 6 Shelves as standard
- Excellent internal illumination for better display
- \* Easy clean interior
- \* Temperature display
- Easily replaceable door gaskets
- \* Anti-mist glass
- \* Static shelves
- \* Not suitable for chocolates

# Technical specifications for Glass Sided Freezer

Product Code	SSDF
Total Length	595 mm
Total Depth	615 mm
Total Height (Inc Castors)	1810 mm
Power Supply Required	13 amp
Nominal Power Consumption	700 Watts
Temperature Range	-5°C/-20°C
Interior/Exterior finish	Glass/ Aluminium
Number of shelves	6 static shelves
Refrigerant Type	R134A

# **ROTATING CHILLER**

Upright Glass Display Chiller











Upright glass sided display cabinet for the display and preservation of chilled products.

#### Key Features of Rotating Chiller

- Comes with castors as standard
- \* Automatic defrost
- \* Fan assisted cooling
- \* No. shelves chilled: 5 glass
- \* Fully automatic operation
- \* Switchable interior lights
- \* Digital temperature display
- Replaceable door gaskets
- \* Anti-mist glass
- Refrigerant: R134A
- Exterior finish: Anodised aluminium
- \* Interior finish: Glass/aluminium
- \* Power required: 13 amp supply

# Technical specifications for Rotating Chiller

Product Code	RCDC
Total Length	595 mm
Total Depth	615 mm
Total Height (Inc Castors)	1810 mm
Power Supply Required	13 amp
Nominal Power Consumption	650 Watts
Temperature Range	+3°C/+10°C
Interior/Exterior finish	Glass/ Aluminium
Number of shelves	5 rotating glass shelves
Refrigerant Type	R134A









Georgia III is ranked among luxury types of cabinets by its style and design.

The Georgia III cabinet is intended mainly for the presentation and sale of pastry goods.

#### Key Features of Georgia III

- \* Available with open front or glass front
- Fluorescent lights under shelves
- \* Automatic defrost
- \* Adjustable feet
- Electronic controls
- Refrigerated shelves
- Easy and quick maintenance
- \* Temperature range: +4°C /+8°C

# Technical specifications for Georgia III

Product Code	PAS100	PAS150	PSS100	PSS150
Open fronted/ Glass fronted	Glass front	Glass front	Open front	Open front
Total Length	1000 mm	1500 mm	1000 mm	1500 mm
Total Depth	750 mm	750 mm	750 mm	750 mm
Total Height	1340 mm	1340 mm	1340 mm	1340 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	520 Watts	765 Watts	690 Watts	920 Watts
Temperature Range	+4°C/+8°C	+4°C/+8°C	+4°C/+8°C	+4°C/+8°C
Interior/Exterior finish	Grey	Grey	Grey	Grey
Number of shelves	3 x glass	3 x glass	3 x glass	3 x glass
Refrigerant Type	R404A	R404A	R404A	R404A







Contemporary style square glass serve over for the display of patisserie style products.

#### Key Features of Georgia Cube

- \* Double tempered front, side and back glasses
- Maximal product visibility
- \* LED lightening of display area
- Forced air circulation with electronic controller
- \* Automatic defrosting and evaporation
- Hinged front glass for easy cleaning
- \* Back sliding doors
- Easy and quick maintenance
- \* Temperature range: +4°C /+8°C

# Technical specifications for Georgia Cube

Product Code	PAS100-C	PAS150-C	PSS100-C	PSS150-C
Open fronted/ Glass fronted	Glass front	Glass front	Open front	Open front
Total Length	985 mm	1485 mm	985 mm	1485 mm
Total Depth	725 mm	725 mm	725 mm	725 mm
Total Height (Inc Castors)	1324 mm	1324 mm	1324 mm	1324 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	569 Watts	711 Watts	569 Watts	711 Watts
Temperature Range	+4°C/+8°C	+4°C/+8°C	+4°C/+8°C	+4°C/+8°C
Interior/Exterior finish	Grey	Grey	Grey	Grey
Number of shelves	3 x glass	3 x glass	3 x glass	3 x glass
Refrigerant Type	R404A	R404A	R404A	R404A



# SINGLE UPRIGHT CHILLER

Glass Door Upright Chiller - Single Door













High quality, reliable single glass door chiller ideal for soft drinks, alcohol, chilled snacks and dairy products.

# Key Features of Single Upright Chiller

- Fully automatic operation
- Fully adjustable shelving
- 100% CFC free
- Lock fitted as standard
- Easy clean interior
- Temp range: +1°C/+10°C
- Internal illumination for brighter display
- Digital temperature display
- Single Door Hinged
- Power required: 13 amp supply
- Grey colour as standard
- Refrigerant: R404A

#### Additional Options

- Wine shelves
- Branding
- Lighting canopy

# Technical specifications for Single Upright Chiller

Product Code	GUC1
Total Length	595 mm
Total Depth	640 mm
Total Height	1840 mm
Power Supply Required	<b>13</b> amp
Nominal Power Consumption	350 Watts
Capacity	373 ltr
Temperature Range	+1°C/+10°C
Interior/Exterior finish	Grey
Number of shelves	7 shelves
Refrigerant Type	R404A

## **DOUBLE UPRIGHT CHILLER**

Glass Door Upright Chiller - Double Door







High quality, reliable double glass door chiller ideal for soft drinks, alcohol, chilled snacks and dairy products.

# Key Features of Double Upright Chiller

- \* Fan assisted cooling
- \* Illuminated canopy
- \* Internal light
- \* Double glazed glass door
- Digital control
- \* Lock as standard
- \* Adjustable shelves
- Available with sliding or hinged doors
- \* Cabinet finish: White\* Power supply: 13 amp
- \* Wire Shelves: 8 + Base
- \* Capacity: 800 ltrs
- \* Temp range: +1/+10°C
- \* Refrigerant: R134A

#### Additional Options

Branding

# Technical specifications Double Upright Chiller

Product Code	GUC2
Total Length	1000 mm
Total Depth	720 mm
Total Height	2020 mm
Power Supply Required	13 amp
Nominal Power Consumption	750 Watts
Capacity	800 Itrs
Temperature Range	+1°C/+10°C
Interior/Exterior finish	White
Number of shelves	8 adjustable shelves
Refrigerant Type	R134A



# SINGLE UPRIGHT FREEZER

Glass Door Upright Freezer - Single Door







Single Glass Door Freezer for the display of frozen products.

#### Key Features of Single Upright Freezer

- \* Fan assisted
- \* Switchable interior light
- Static shelves
- Digital temperature display
- \* Adjustable temperature
- \* Temp range: -18°C/-22°C
- Drain hole for defrosting
- Power required: 13 amp supply
- Grey colour as standard

# Technical specifications for Single Upright Freezer

Product Code	GUF1
Total Length	595 mm
Total Depth	640 mm
Total Height	1840 mm
Power Supply Required	<b>13</b> amp
Nominal Power Consumption	570 Watts
Capacity	300 ltr
Temperature Range	-18° C/-22°C
Interior/Exterior finish	White
Number of shelves	6 Static
Refrigerant Type	R404A

# **DOUBLE UPRIGHT FREEZER**

Glass Door Upright Freezer - Double Door







Double Glass Door Freezer for the display of frozen products.

#### Key Features of Double Upright Freezer

- \* Fully automatic
- \* Fan assisted cooling
- \* Auto defrost
- \* Lock
- \* Adjustable shelves
- Castors with locking feet
- LED interior light with switch (2 LED strips per door)
- \* Digital controller and temperature display
- \* Self closing door with stay open feature for ease of loading
- Light canopy with switch
- Replaceable door gasket
- Anti mist glass
- Internal stainless steel base

# Technical specifications for Double Upright Freezer

Product Code	GUF2
Total Length	1382 mm
Total Depth	800 mm
Total Height	2055 mm
Power Supply Required	<b>13</b> amp
Nominal Power Consumption	1200 Watts
Capacity	1108 ltr
Temperature Range	-14/-25°C
Interior/Exterior finish	White/White
Number of shelves	4 per door
Refrigerant Type	R404A














#### Key Features of Symphony

- Available lengths: 1380 mm (2 door) and 2000 mm (3 door)
- \* Temperature range: -18/-25°C
- Canopy lighting
- On castors for easy movement
- \* 2 shelves on door section
- Profile gables
- \* Energy efficient condensing unit
- Power required: 13 amp supply

# Technical specifications for Symphony

Product Code	WWF2	WWF3
Total Depth	1020 mm	1020 mm
Total Height	1995 mm	1995 mm
Storage Volume	321 ltr	476 ltr
Power Supply Required	13 amp	13 amp
Nominal Power Consumption	1520 Watts	2000 Watts
Defrost Power Consumption	1760 Watts	2280 Watts
Temperature Range	-18°C/-25°C	-18°C/-25°C
Interior/Exterior finish	Grey/White	Grey/White
Number of shelves	2 per door	2 per door
Refrigerant Type	R404A	R404A













Dual Temperature Island Unit for the display of frozen and chilled product.

#### Key Features of Rondo

- Dual temperature: Each display can simply switched between chilled & frozen
- \* Energy efficient
- \* Temperature range chilled: +1°C/+4°C
- \* Temperature range frozen: -18°C/-23°C
- Power required: 13 amp supply

#### Additional Options

- \* Base risers
- \* Available in red, grey, white and yellow fascia's (subject to availability)
- Night covers
- \* Branding

# Technical specifications for Rondo

Product Code	DTIC150	DTIC200	DTIF150	DTIF200
Temperature Range	+1°C/+4°C	+1°C/+4°C	-18°C/-23°C	-18°C/-23°C
Total Length	1500 mm	2000 mm	1500 mm	2000 mm
Total Depth	1000 mm	1000 mm	1000 mm	1000 mm
Total Height	910 mm	910 mm	910 mm	910 mm
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	880 Watts	1740 Watts	880 Watts	1740 Watts
Defrost Power Consumption	1250 Watts	2600 Watts	1250 Watts	2600 Watts
Interior/Exterior finish options	White/grey/red/yellow	White/grey/red/yellow	White/grey/red/yellow	White/grey/red/yellow
Refrigerant Type	R404A	R404A	R404A	R404A



## **ARAN CHEST FREEZER**

Glass Lid Commercial Chest Freezer











The Novum Aran is a premium range plugin, self service refrigerated case operating to 3L1. The Aran is a versatile, reliable, high visibility, glass fronted chest freezer powered by an integral hermetically sealed high efficiency condenser unit.

#### Key Features of Aran Chest Freezer

- \* High product visibility
- \* Higher impulse sales
- Lower running costs

#### Additional Options

- Available with lift up glass lid on special request (subject to availability)
- Shelf dividers

## Technical specifications for Aran Chest Freezer

Product Code	ACF150	ACF220
Total Length	1505 mm	2205 mm
Total Depth	900 mm	900 mm
Total Height	955 mm	955 mm
Net Storage Capacity	480 Ltr	742 Ltr
Power Supply Required	<b>13</b> amp	13 amp
Nominal Power Consumption	410 Watts	790 Watts
Defrost Power Consumption	476 Watts	856 Watts
Temperature Range	-18° C/-23°C	-18° C/-23°C
Interior/Exterior finish	Grey	Grey
Refrigerant Type	R404A	R404A

## **BURREN CHEST FREEZER**

Glass Lid Commercial Chest Freezer











The Novum Burren chest freezer has been designed to meet the exacting needs of the modern retailer in terms of energy efficiency, reliability and making efficient and effective use of the available floor space.

#### Key Features of Burren Chest Freezer

- High product visibility
- Higher impulse sales
- \* Lower running costs

#### Additional Options

- Available with lift up glass lid on special request (subject to availability)
- Shelf dividers

#### Technical specifications for Burren Chest Freezer

Product Code	BCF220	BCF250
Total Length	2205 mm	2505 mm
Total Depth	860 mm	860 mm
Total Height	875 mm	875 mm
Net Storage Capacity	698 Ltr	817 Ltr
Power Supply Required	13 amp	<b>13</b> amp
Nominal Power Consumption	410 Watts	490 Watts
Defrost Power Consumption	476 Watts	556 Watts
Temperature Range	-18°C/-23°C	-18°C/-23°C
Interior/Exterior finish	Grey	Grey
Refrigerant Type	R404A	R404A



## **LINE CHEST FREEZER**

Glass Lid Commercial Chest Freezer







The Novum Line is a modern, robust, durable and energy efficient chest freezer. This flexible and versatile cabinet is available with electronic control, modern refrigerants, cyclopentane insulation and long life low energy compressors and fans.

#### Key Features of Line Chest Freezer

- \* High product visibility
- Higher impulse sales
- Lower running costs
- Comes with lift-up curved glass lid
- Temperature range: -18/-23°C
- \* Power required: 13 amp supply

#### Additional Options

\* Shelf dividers

# Technical specifications for Line Chest Freezer

Product Code	LCF150	LCF170
Total Length	1500 mm	1700 mm
Total Depth	740 mm	740 mm
Total Height	892 mm	892 mm
Net Storage Capacity	412 Ltr	484 Ltr
Power Supply Required	13 amp	<b>13</b> amp
Nominal Power Consumption	200 Watts	200 Watts
Defrost Power Consumption	266 Watts	266 Watts
Temperature Range	-18°C/-23°C	-18° C/-23°C
Interior/Exterior finish	White	White
Refrigerant Type	R404A	R404A

## **SCOOP FREEZER**

7 Pan Soft Scoop Freezer







7-pan curved glass scoop ice cream serve over with under storage.

#### Key Features of Scoop Freezer

- \* Fully automatic operation
- \* Electronically controlled
- \* Excellent internal illumination for brighter display
- \* Display Capacity 7 x 5 ltr pans (supplied)
- Under storage can accept 12 x 5 ltr pans (not supplied)
- White plastisised sheet steel
- Curved glass superstructure
- \* Temperature range: -15/-20°C
- Type of defrost: electric
- \* Exterior finish: white
- \* Interior finish: coated steel
- \* Power required: 13 amp supply

#### Additional Options

\* Additional 5 ltr pans for under storage

#### Technical specifications for Scoop Freezer

Product Code	SSF7
Total Length	1341 mm
Total Depth	723 mm
Total Height	1224 mm
Power Supply Required	<b>13</b> amp
Display Capacity	7 x 5 ltr napoli pans (supplied)
Under Storage Capacity	12 x 5 ltr napoli pans (not supplied)
Nominal Power Consumption	740 Watts
Temperature Range	-15°C/-20°C
Interior/Exterior finish	Coated steel/white
Refrigerant Type	R507



#### **UPRIGHT CATERING CHILLERS**

Upright Solid Door Catering Chillers















High capacity single and double door catering chillers.

#### Key Features of Catering Chillers

- Available as a single door (SDCC1) or double door (SDCC2) chiller
- \* Temperature range: -2/+10°C
- \* Fully automatic operation
- \* Digital temperature display
- Fan assisted cooling
- Fully adjustable shelving
- Interior light
- Suitable for fresh meat
- \* Refrigerant: R134A
- \* 2/1 gastronorm size
- \* Type of defrost: Electric
- Number of shelves: 3 per door
- \* Operating range: Up to 40°C ambient
- \* Exterior Finish: Attractive stainless Steel interior/exterior
- Power required: 13 amp supply
- Lock fitted as standard

# Technical specifications for Catering Chillers

Product Code	SUC1 (Single Door)	SUC2 (Double Door)
Total Width	740 mm	1480 mm
Total Depth	850 mm	850 mm
Total Height (Inc Castors)	2010 mm	2010 mm
Storage Capacity	650 ltr	1410 Ltr
Power Supply Required	13 amp	13 amp
Nominal Power Consumption	350 Watts	650 Watts
Temperature Range	-2°C/+10°C	-2°C/+10°C
Interior/Exterior finish	Stainless Steel	Stainless Steel
Number of shelves	3 shelves per door	3 shelves per door
Refrigerant Type	R134A	R134A

# **UPRIGHT CATERING FREEZERS**

**Upright Solid Door Catering Freezers** 













High capacity single and double door catering freezers.

# Key Features of Catering Freezers

- Available as a single door (SDCF1) or double door (SDCF2) freezer
- \* Temperature range: -18/-24°C
- \* Fully automatic operation
- Digital temperature display
- Fan assisted cooling
- Fully adjustable shelving
- \* Interior light
- Suitable for fresh meat
- \* 2/1 gastronorm size
- \* Type of defrost: Electric
- \* Number of Shelves: 3 per door
- Operating Range: Up to 40°C ambientExterior Finish: Attractive stainless steel
- interior/exterior
- \* Power Required: 13 amp supply
- Lock fitted as standard

# Technical specifications for Catering Freezers

Product Code	SUF1 (Single Door)	SUF2 (Double Door)
Total Width	740 mm	1480 mm
Total Depth	850 mm	850 mm
Total Height (Inc Castors)	2010 mm	2010 mm
Storage Capacity	650 ltr	1410 Ltr
Power Supply Required	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	1000 Watts	1200 Watts
Temperature Range	-18°C/-24°C	-18°C/-24°C
Interior/Exterior finish	Stainless Steel	Stainless Steel
Number of shelves	3 shelves per door	3 shelves per door
Refrigerant Type	R134A	R134A



## **GASTRO PREP COUNTERS**

Gastronorm Under counter Chillers & Freezers









High capacity double and triple door catering counters.

#### Key Features of Gastro Prep Counters

- \* Stainless steel exterior 304 grade
- \* Injected polyurethane insulation
- Fitted castors
- Digital temperature display
- \* Compressor on indicator
- 1/1 gastronorm size
- \* Fitted splash-back
- \* Adjustable temperature
- \* Type of defrost: electric
- \* No. of shelves: 1 per door
- \* Exterior finish: Attractive stainless steel interior/exterior

# Technical specifications for Gastro Prep Counters

Product Code	PCC2 (Chiller)	PCC3 (Chiller)	PCF2 (Freezer)	PCF3 (Freezer)
Total Width	1360 mm	1795 mm	1360 mm	1795 mm
Total Depth	700 mm	700 mm	700 mm	700 mm
Total Height without splashback	850 mm	850 mm	850 mm	850 mm
Total Height with splashback	950 mm	950 mm	950 mm	950 mm
Storage Capacity	282 Ltr	417 Ltr	282 Ltr	417 Ltr
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp	<b>1</b> 3 amp
Nominal Power Consumption	450 Watts	450 Watts	700 Watts	700 Watts
Temperature Range	-2°C/+10°C	-2°C/+10°C	-18° C/-24°C	-18°C/-24°C
Number of Doors	2 doors	3 doors	2 doors	3 doors
Refrigerant Type	R134A	R134A	R134A	R134A

## SINGLE UNDERCOUNTERS

Single Door Undercounter Chillers & Freezers









Single door under counter cabinets for the storage of chilled and frozen product.

# Key Features of Single Undercounters

- Heated glass door (freezer)
- Adjustable temperature
- Lock fitted as standard
- Digital temperature display
- Adjustable feet with rollers to rear
- \* Refrigerant: R404A
- \* No. of shelves: 3 fixed
- \* Capacity: 153 ltr
- Temp Range Chiller: +1°C/+10°C
- \* Temp Range Freezer: -18°C/-24°C
- \* Interior finish: White plastic
- \* Power required: 13 amp supply

#### Additional Options

- Solid door and glass door options
- \* Exterior finish in white or stainless steel

# Technical specifications for Single Undercounters

Product Code	UGC-S (Chiller)	UGF-S (Freezer)	USC-S (Chiller)	USF-S (Freezer)
Door Type	Glass Door	Glass Door	Solid Door	Solid Door
Total Width	595 mm	595 mm	595 mm	595 mm
Total Depth	640 mm	640 mm	640 mm	640 mm
Total Height	850 mm	850 mm	850 mm	850 mm
Storage Capacity	153 ltr	153 ltr	153 ltr	153 ltr
Power Supply Required	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	220 Watts	220 Watts	220 Watts	220 Watts
Temperature Range	+1°C/+10°C	-18°C/-24°C	+1°C/+10°C	-18°C/-24°C
Interior/Exterior finish	White/Stainless Steel	White/Stainless Steel	White/Stainless Steel	White/Stainless Steel
Refrigerant Type	R404A	R404A	R404A	R404A



# **BACK BAR CHILLERS**

**Undercounter Bottle Coolers** 









Glass Door Back Bar Chillers for the display of cold beverages.

#### Key Features of Back Bar Chillers

- Available in single, double or triple door options
- \* Interior light for enhanced presentation
- \* Adjustable legs
- \* Climate class: M2
- Refrigerant: R134A
- \* Temperature range: +2°C/+12°C
- Digital temperature display
- Defrost: electric
- Exterior finish: Black as standard (Silver on request)
- Lock fitted as standard
- \* Power required: 13 amp supply

# Technical specifications for Back Bar Chillers

Product Code	BBC1	BBC2	BBC3
Number of Doors	1 Door	2 Doors	3 Doors
Total Width	600 mm	900 mm	1350 mm
Total Depth	640 mm	640 mm	640 mm
Total Height	900 mm	900 mm	900 mm
Storage Volume	142 Ltr	210 Ltr	340 Ltr
Power Supply Required	13 amp	<b>13</b> amp	<b>13</b> amp
Nominal Power Consumption	200 Watts	230 Watts	290 Watts
Temperature Range	+2°C/+12°C	+2°C/+12°C	+2°C/+12°C
Interior/Exterior finish	Black	Black	Black
Refrigerant Type	R134A	R134A	R134A

# **SHOWMASTER DOME**

Dome Island Display Chiller









The ShowMaster is a mobile refrigerated display case in a sleek design with smooth edges. ShowMaster is used in hotels, restaurants, and exhibitions for exceptionally attractive food presentations. When closed, the ShowMaster provides refrigerator temperature. When opened, the acrylic hood serves as an effective hygienic barrier. Salad bar, breakfast buffet, dessert buffet or the presentation of food at fairs and exhibitions.

The ShowMaster is suitable for all food products and guarantees a long lasting delicious freshness.

#### Key Features of Showmaster Dome

- Accessible from all sides, ShowMaster is always an attractive centerpoint
- \* Finish: various colours, wood veneer, laminate, metal surfaces
- Contact cooling, air circulation cooling
- \* Extensive accessories for food presentation
- \* Durable and maintenance-free, easy to clean
- \* Energy-efficient, LED-lighting
- \* Acrylic dome functions as a cover and a hygienic barrier, movable by electric lifting device
- Plug and Play, integrated cooling machine, mounted on castors
- \* Integral drain allows the use of ice
- Compliant to international hygiene and safety regulations (TÜV, CE, HACCP)

#### Technical specifications for Showmaster Dome

Product Code	DIC110	
Diameter	1110 mm	
Total Height (opened)	1670 mm	
Total Height (closed)	1350 mm	
Power Supply Required	<b>13</b> amp	
Nominal Power Consumption	905 Watts	
Temperature Range	+3°C/+10°C	
Interior/Exterior finish	Black	
Number of food containers	12 x 2.5 ltr	
Capacity	90 ltrs	
Refrigerant Type	R404A	



# 100% Fridge Rental Flexibility: Short, Medium Or Long Term Hire

Whether for a few days or weeks, to meet seasonal promotions, trade fairs and exhibitions, new product launches or for long term retail hire, Refrigeration Rentals offer you the perfect refrigerated displays that match your requirements.













Refrigeration Rentals (Part of the Hire Innovation Group)

Ireland office: 11 Broomhill Road, Tallaght, Dublin 24, D24 PF20, Ireland UK office: Unit 3 Bishops Court, Winwick Quay, Warrington, Cheshire, WA2 8QY, UK

 $\textit{IRL Tel:} + 353\ 1\ 4271010\ \mid\ \textit{UK Tel:}\ 0800\ 148\ 8075\ \mid\ \textit{IRL Email:}\ info@hire-innovation.com\ \mid\ \textit{Web:}\ www.refrigerationrentals.com$ 





