









## The SynDeck® Commercial Line - IMO Certified Products

Description	Description	Key Benefits
SynDeck® Ultra Lightweight Underlayment SS1290FC	Ultra-light underlayment with tremendous strength and water resistance	<ul> <li>US NAVY Certified to go over steel without primer</li> <li>Easily troweled on floors. Can create cove base and positive slope to drain.</li> <li>Very low odor</li> <li>Waterproof and is ideal for wet spaces</li> </ul>
SynDeck® Ultra Lightweight Terrazzo SS1290FC Terrazzo	Ultra-light decorative underlayment with tremendous strength and waterproof	<ul> <li>Troweled finish resembles unique marble/granite look without needing a decorative topcoat</li> <li>US NAVY Certified to go over steel without primer</li> <li>Easily troweled on floors. Can create cove base and positive slope to drain.</li> <li>Very low odor</li> <li>Waterproof and is ideal for wet spaces</li> </ul>
SynDeck® Flex	Flexible, durable underlayment with excellent chemical resistance	<ul> <li>Very Flexible top coat that is suitable as "direct to substrate" or on top of SynDeck underlayments</li> <li>Long pot life makes trowel application easy</li> <li>Very flexible top coat that is suitable as "direct to substrate" or on top of Syndeck underlayments</li> <li>Stocked in gray, but special colors available*</li> <li>*Subject to restrictions, contact your representative for more information.</li> </ul>
SynDeck® 1.5 Underlayment	Light underlayment with very good strength and waterproof	<ul> <li>Cost effective</li> <li>Easily troweled on floors. Can create cove base and positive slope to drain.</li> <li>Very low odor</li> <li>Waterproof and is ideal for wet spaces</li> </ul>
SynDeck® IMO Clear Top Coat/ Color Coat	Marine grade epoxy - available in water clear and colors	<ul> <li>Excellent adhesion</li> <li>Highly durable, scratch resistant film</li> <li>Non blushing in low temperature applications</li> <li>Easy to use with SynDeck® anti-skid additive</li> </ul>
SynDeck® IMO UVR	Water clear UV resistant epoxy clear	<ul> <li>Extended pot life</li> <li>Formulated for easy application</li> <li>Easy to use with aggregate for anti-skid effect</li> <li>Very durable</li> <li>No blushing</li> </ul>
SynDeck® Bond Coat	Low viscosity, long open time bonding agent	<ul> <li>Long open time makes it easy to work with</li> <li>Low odor</li> <li>Low viscosity allows for easy application</li> </ul>

EPMAR Corporation 13210 E. Barton Circle Whittier, CA 90605-3254 US: 1.877.99.EPMAR UK: +44 (0)1453 820800 www.syndeckmarine.com



