

XT-SVM-M1410

Manual Measurement System

The Scienscope XT-SVM-M1410 Manual XYZ measurement system provides the largest cost effective platform for a variety of applications. The M1410 has a 14x10x8" (350x250x200mm) stage travel. The stage, column and base are granite for thermal stability and strength. Virtually maintenance free, the price to value is unbeatable. Ask for a demonstration today; or send us some samples for measurement.

Applications

Medical

Optics

Defense

Life Sciences

Automotive

Sheet Metal

Circuit Boards

Electronics

Solar

Consumer


System Details



FEATURING


- Precision Granite Base, Stage and Column
- 1/2 (0.5) Micron Resolution Tape Scales
- 1/2" Color 1.3 Megapixel Camera
- 23" LCD Widescreen Monitor
- · Zoom Lens with magnification detent sensor
- Quick Lock/Release X/Y Stage
- Software controlled Quad LED top Light
- Software controlled collimated LED Back Light
- M3 MetLogix Software
- True position, GDT and tolerancing, reporting
- CAD layout window, DXF capability
- · Live image screen
- Annotation and video capture for archiving and part documentation
- All geometric functions (circle, arc, angle, distance, etc.)
- Workstation Table Optional
- 1 Year Full Warranty







NOW FEATURING THE NEW METLOGIX M3 SOFTWARE!



MACHINE VISION



QUADRANT 72-BULB LED TOPLIGHT

















4X LARGER LENS WITH COLLIMATED BACKLIGHT



Enlarged Lens



Legacy Lens



STANDARD LIGHT COLLIMATED LIGHT



Produces high contrast silhouettes & increased illumination

STAGE DETAILS

- 1. Glass Stage Level Adjustments
- **2.** Y-Axis Stage Lock / Quick Release
- 3. Built-in 1/2 micron resolution tape encoder scale (X/Y)
- 4. Precision Granite base
- 5. Y-axis stage knob
- 6. X-axis stage knob
- 7. X-Axis Stage Lock / Quick Release

General Specifications

Model Number	XT-SVM-M1410	
Measuring Range	14" X 10" X 8"	
Magnification Calibration	Image Magnification Calibration	NEW
Measurement Software Options	MetLogix M3 Software	
Standard Magnification	25X to 158X / Capable of up to 316X	
Illumination	Quad LED top & Collimated back light	
Power Supply	110V - 220V ± 5% 50/60HZ	
System Resolution	1 μm	
Accuracy (X/Y) at 20°C	(3+L/200) μm, L in mm	
Repeatability	± 1 µm	
Camera	1/2" Color USB 1.3 Mega Pixel Digital Camer	a
Support Stand	Table top or workstation Optional	

THIS SYSTEM INCLUDES A 1 YEAR WARRANTY ON PARTS AND LABOR

