

24 Hour Emergency Service Rentals • Sales • Service (800) 627-2653

500 HP 9ppm Low NOx, 150 psig Skid-Mounted Boiler

Cole Industrial has two (2) 500 hp (17,250 #/hr) skid-mounted Cleaver-Brooks firetube boilers designed at 150 psig pressure, firing natural gas, manufactured in 2008. Equipped as follows:

- CBLE Low NOx Burner
- Allan Bradley Compact Logix PLC Rack
- Hawk ICS, 10" Screen, VSD, O2 Trim
- Pilot System w/ Electric Ignition
- Forced-draft Fan, 30 hp Motor & Starter
- Steam Pressure Gauge
- Levelmaster, Auxiliary LWCO
- Water Column & Site Glass
- Three (3) Safety Valves Set at 150 psig
- Pre-piped FW Stop and Check Valves
- Pre-piped & Wired Gas Train
- Continuous Blowdown Metering Valve
- High/low Water and Flame Failure Alarm
- Steam Header Spool Piece 10"x 6" x 48"
- Bottom & Control Blowdown Valves
- Meets FM / IRI / NFPA 85
- Operating Manuals



Fuel Consumption:

Natural Gas:

20,000 SCFH @ 10-25 psig

Connection Sizes:

| Main Steam: | 10"-300# FLG |
|--------------------|--------------|
| Gas: | 2.5" |
| Feedwater: | 2.5" NPT |
| Bottom Blowdown: | 2" NPT |
| Continuous Blowdow | /n: 1" NPT |
| Flue Outlet: | 24" OD FLG |
| | |

Electrical Power Requirements:

480 VAC, 3 ph, 60 Hz., 125 amps

Dimensions & Weights:

| Length: | 19' |
|-------------------|------------|
| Width: | 10' 3" |
| Height: | 10' 4" |
| Shipping Weight: | 40,800 lbs |
| Operating Weight: | 56,750 lbs |

Emissions Data (natural gas):

NOx (corr. to 3% O2): 9 ppm CO (corr. to 3% O2): 50 ppm

HEADQUARTERS: 5924 203rd St. S.W. Lynnwood, WA 98036 Ph: 425/774-6602 Fax: 425/775-2272 N. OREGON OFFICE: 19860 SW 129th Ave Tualatin, OR 97062 Ph: 503/972-0595 Fax: 503/972-0596 YAKIMA OFFICE: 1502 S. 36th Ave. Yakima, WA 98902 Ph: 509/457-5015 Fax: 509/457-5160 S. OREGON OFFICE: 750 Industrial Circle White City, OR 97503 Ph: 541/826-2421 Fax: 541/826-2971 IDAHO OFFICE: 2000 Century Way Boise, ID 83709 Ph: 208/465-8005 ALASKA OFFICE: Anchorage, AK Ph: 907/203-0133