




H

Hobnail

Fibre Bonded




Green




Flint



Blue



Charcoal




Purple



Willow



Fuchsia



Azure



Heckmondwike Hobnail

Fibre Bonded

Hobnail offers a striking cobbled surface structure in a variety of colour options that complements a wide range of building types, locations and décor schemes. With low installation and maintenance costs, Hobnail is designed to withstand the most demanding environments.



Violet

Specification	Hobnail	
Fibre Construction (Sheet)	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester	
Fibre Construction (Tile)	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester	
Colour Fastness	Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:B01) 5 Dry Rubbing (BS EN ISO 105:X12) 5	
Flammability	BS5287 Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char	
	BS EN 13501:2002 Euroclass C _{ff} -s1 (Sheet) Euroclass B _{ff} -s1 (Tile)	
Antistatic	Suitable for use in computer rooms	
Formats	Sheet 	Tiles 
Backing	-	Bitumen
Size	2 metre	50cm x 50cm
Weight	1020gm metre ²	4020gm metre ²
Thickness	7.20mm	8mm