Material Safety Data Sheet

May be used to comply with OSHA Hazard Communication Standard, 29CFR 1910.1200. Standard must be consulted for specific requirements. U S Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

NOTE: Blank spaces are not permitted. If any item is not applicable, or no Information is available, the space must be marked to indicate that

800-255-3924 (USA) - 813-248-0585 (INT'L)

Identity (As used on Label and List)

CITRI-CUT-GEL

SECTION I

Manufacturer's Name

NUVITE CHEMICAL COMPOUNDS CORP.

Emergency Telephone Number

Address (Number, Street, City, State and ZIP Code) 213 Freeman Street Brooklyn, New York 11222 Telephone Number for Information:

718-383-8351

Date Prepared: December 8, 2004

SECTION II - Hazardous ingredients/identity information

			Other Limits	
Hazardous Components (Specific Chemical Identity: Common Name(s)	OSHA PEL	ACGIH TLV	Recommended	% (Optional)

No restricted ingredients as listed by OSHA 29CFR 1910.1000 - 1500 ACGIH, OR EPA 40CFR Part 261.3, 302.4, 355, 370, 372

This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313: NONE

SECTION III - Physical/Chemical Characteristics

Boiling Point: NF	212	Specific Gravity (H20 = 1): $@25 \text{ NC}$	1.02			
Vapor Pressure (mm Hg.): @ 20 NC	18	Melting Point:	Not Applicable			
Vapor Density (AIR = 1): Greater than	1	Evaporation Rate (Butyl Acetate = 1): Less than	1			
Solubility in Water: Infinite						
Appearance and Odor: Orange. Gel/Liquid - Citrus odor						
Section IV - Fire and Explosion Hazard Data						
Flash Point (Method Used): None	C.O.C.	Flammable Limits: Not Applicable LEL	UEL			
Extinguishing Media: Water spray, foam, dry chemical, CO2						
Special Fire Fighting Procedures: Wear full protective safety equipment as standard practice						
Unusual Fire and Explosion Hazards: None						

Section V - Reacti	vity Data									
Stability	Unstable		Conditio	ons to Av	oid					
St	able	Х	None							
Incompatibility (M	aterials to A	Avoid):	Strong acids,	bases, or	xidiziı	ng ager	ıts.			
Hazardous Polyme	rization:		Occur	V		itions t	o Avoi	id		
Section VI - Healt	h Hazard		Not Occur	Х	NON	1E				
Routes of Entry:			Inhalation:	Seconda	ary	Skir	1: Prir	nary	Ingestion: Tertiary	
Health hazards (Acut	e and Chroni	c):								
									cause moderate irritation ous gastric disturbances.	upon direct contact.
CHRONIC: None										
Carcinogenicity:			NTP?	(AR	C Mon	ographs	;?)		OSHA Regulated?	
		No		Nc)				No	
Signs and Symptoms	of Exposure	: May ca	use redness and	irritation to	o expo	sed skin	areas d	luring	prolonged exposure	
Medical Conditions C	Generally Ag	gravated	by Exposure: W	orkers wi	th skin	disorde	rs or se	nsitiv	ity should avoid contact wit	th this product.
									ter for15 minutes and imme nediately contact physician	
Section VII - Prec	autions fo	r Safe H	andling and l	Use						
Steps to Be Taken in container. Do not int	Case Materi roduce mate	al is Rele rial direct	ased or Spilled: ly into rivers, la	Contain a kes, strean	all spil ns, etc.	ls. Use	inert at	osorbe	nt material and dispose in p	proper chemical waste
Waste Disposal Meth	od: Flush &	t dilute i	n accordance wi	th Federal,	, State	and Loo	al regu	lations	5.	
Precautions to Be Tal	ken in Handl	ing and S	toring: When no	ot in use, k	eep co	ntainer o	closed.	Store	indoors	
Other Precautions: I	Dispose of er	npty drur	ns to re-conditio	ner.						
Section VIII - Cor	ntrol Meas	ures								
Respiratory Protectio	n (Specify T	ype): No	t applicable.							
Ventilation	Local Exhau	st: F	Recommended			Spe	cial:	NC	OT APPLICA BLE	
	Mechanica	l (Genera	al): Insure suffic	ient air vel	locity	(Other:	(Open door/window	
Protective Gloves:	Recommend	ed if expo	osure is prolonge	ed - Neopr	rene					
Eye Protection : F	Recommende	d when s	praying or work	ing on ove	erhead	structur	es or if	direct	contact is evident.	
Other Protective Clot	hing or Equi	pment: W	Vork clothes.							

Work/Hygienic Practices: Wash thoroughly after use and wash work clothes. Water source in work area recommended.