



DIMENSIONS												
Version	L (Length)	P (Width)		A	B	C	D	E	E1	F std	F min	H
Optional	750	600		see drawing D10G31001	see drawing D10G31001	615	520	530 min	845	180	150	1640
Optional	750	650				665	570	530 min	845	180	150	1690
Standard	750	700				715	570	530 min	845	180	150	1690
Standard	850	700				715	570	570 min	945	180	150	1690
Optional	1000	800				815	645	650 min	1095	180	150	1770
TECHNICAL DATA												
Load (Kg)	Unit weight (Kg)	Rail weight (Kg/M)		Power (kW)	Mains voltage (V)		Control circuits voltage (DC V)		Speed (m/sec)			
225 max.	80	10		1.10 max.	240		24		~0.1			
MINIMUM STAIR DIMENSIONS												
Version	750x600		750x650		750x700		850x700		1000x800			
(F min+special rail without foot)	F min	F std	F min	F std	F min	F std	F min	F std	F min	F std	F min	F std
LR Total width	2790	2950	2790	2950	2790	2950	3390	3550	4090	4250		
LS Stair width	1035	>1045	1070	>1080	1105	>1115	1195	>1205	1365	>1375		
R Turning radius	1300	>1300	1300	>1300	1300	>1300	1600	>1600	1950	>1950		
G Min. height	1650		1650		1650		1730		1800			
Data with: STD rail + wall feet support ; Self supporting feet: LS + 80 min. ; Special rail to wall LS - 20 ; Side access LS and C + 40 ; Add skirting dim. to LS ; Dimension G for gradient 30° ; In case of change of gradient in the "outside bend", different LS and rail longer than 20m, apply technical dept.												

Inclined platform lift with outside bend

SLIM Technical data and dimensions

Simply Access Ltd

D10G31003 SA