

# DAYTONA

## STAGE HIRE

## DS60 ROOF & WALL PANEL SPECIFICATION

### GENERAL INFORMATION

- The Daytona DS60 Mobile Stage has several panels that form the roof and side walls when the stage is set up.
- These are made up of one central panel that forms the roof of the trailer when in transport mode, and one side panel that folds out from the off-side so that it is level with the central roof panel to form one large flat 10m x 6m square roof.
- The panels are manufactured by Carlier Plastiques who state that the material meets International Fire Standards.

### SPECIFICATION

- Panel Type : C.P.R.S. panels constructed from a plywood core and G.R.P. coating with gelcoat on both sides.
- Thickness : 11mm
- Weight : 9.6kg/m<sup>2</sup>
- Dimensions:
  - Front roof panel/Offside trailer side panel : 10.2m x 2.746m.
  - Centre roof panel/trailer roof panel : 10.2m x 2.072m
- Cross section of the panel specification from the outside to the inside:

Gelcoat: White

Glass tissue: 30g/m<sup>2</sup>

Glass fibre: 450g/m<sup>2</sup>

Polyester resin

Plywood: WBP

Polyester resin

Glass fibre: 450g/m<sup>2</sup>

Glass tissue: 30g/m<sup>2</sup>

Gelcoat: White



P.O. BOX 43 HUDDERSFIELD HD8 9YU J 01484 605555 FAX: 01484 602806

WWW.DAYTONASTAGEHIRE.COM EMAIL: DAYTONASTAGEHIRE@MAC.COM PROPRIETOR PAUL HAIGH