

# **TRAILER ENGINEERING**

**MANUFACTURERS OF INDUSTRIAL TRAILERS & TANKERS**

## IMPORTANT

**WHEN FREEZING WEATHER CONDITIONS ARE LIKELY, IT IS IMPORTANT TO PROTECT THE HIGH PRESSURE PUMP FROM FROST DAMAGE.**

### **EITHER:**

**STORE THE UNIT INDOORS WHERE THE TEMPERATURE REMAINS ABOVE FREEZING.**

**RUN A MILD ANTI-FREEZE SOLUTION THROUGH THE PUMP VIA THE WATER SUPPLY HOSE (OR SEPARATE HOSE IF BOWSER MOUNTED).**

**IF USING THIS METHOD ENSURE ALL ANTI-FREEZE SOLUTION IS WASHED THROUGH PUMP ON COMMENCEMENT OF WORK TO AVOID DAMAGING PAINTWORK OR SENSITIVE AREAS.**

### **OR:**

**AFTER USE, DISCONNECT THE WATER SUPPLY AND RUN THE MACHINE FOR APPROXIMATELY 15 SECONDS UNTIL WATER STOPS COMING FROM PUMP.**

**IF IN ANY DOUBT, DO NOT START THE MACHINE AS DAMAGE MAY OCCUR.**