

# Marine Generators



Suitable for both pleasure and commercial applications, the Nanni Diesel marine gensets benefit from state of the art technology combining reliability, smooth performance and fuel efficiency. Designed for both occasional or more intense use, they are equipped with an automatic stop system in case of oil pressure failure or an abnormal increase in the temperature within the cooling system.

The engines used for the gensets (except the QMF 3.5M) are all equipped with the Nanni Compact Cooling® system, allowing for maximum life span and perfect running.

## Gensets with Sound Shield

In order to minimise noise as much as possible the QMF and QMS gensets are available with a sound shield enclosure, which allows them to reach a threshold of 54dB at 7 metres - that's the equivalent to the noise of a dishwasher. The shield neatly encompasses all connections whilst remaining easily accessible due to the light and removable panels.

All QMS gensets have a rotation speed of 1500rpm. This means that not only are noise and vibration levels low, the friction and wear is greatly reduced.



**Meccalte alternator - Mono-phased - 230 volts** \*Optional: Three-phased

Model	kVA Max	kVA Cont.	kW Max	kW Cont.	Volts	Hz	No. of Cylinders	Disp cm <sup>3</sup>	Intake	RPM	Cooling	Weight (kg)	Dimensions (incl Sound Shield) mm (in) L x W x H
QMF 3.5M	3.5	3.2	3.5	3.2	230	50	1	290	Natural	3000	Direct	105	590 (23.22) x 405 (15.94) x 515 (20.27)
QMF 6.0M	6	5.5	6	5.5	230	50	2	479	Natural	3000	Exchanger	128	650 (25.59) x 480 (18.89) x 530 (20.86)
QMS 7.5M*	7.5	6.6	7.5	6.6	230	50	2	1123	Natural	1500	Exchanger	271	950 (37.4) x 540 (21.26) x 710 (27.95)
QMS 10M*	10	8.8	10	8.8	230	50	4	1498	Natural	1500	Exchanger	300	1050 (41.34) x 540 (21.26) x 710 (27.95)
QMS 16M*	16	13.9	16	13.9	230	50	4	2197	Natural	1500	Exchanger	328	1014 (39.91) x 548 (21.57) x 691 (27.18)