

SPECIFICATION SHEET

UN 1 OPEN TOP STEEL DRUM

210 LITRES (for Solids)



A steel open top drum manufactured in accordance with the UN packaging specification, and B,S,I.: BS EN 210:2000..

Tested for Packaging Groups I, II, III.

Closure

External Lever Closing ring with round rubber gasket

Additional Specification

- Side Seam - Welded
- End Seams - Base Triple Seamed & solution
- Rolling Hoops - Two
- Handle - None
- Internal Finish - Plain/ Epoxy Phenolic Lacquer
- External Finish - Stoving Enamel
- Embossing on Base - 1A2/Y269/S/**/1.0



Volume	Steel Plate Thickness (mm)			Weight	UN Approval
	Top End	Body	Bottom		
210 Litre Nominal	1.0mm	1.0mm	1.0mm	18.6 kg	1A2/Y269/S/**/Manufacturer

To test levels of	The packaging is approved as provided in the relevant transport rule, to contain liquids of		
	1.8	packaging group	density (d)
Drop Height (m)		I	1.14
Leakproofness (kPa)	-	II	1.14
Stacked at 3m with RD(d)	1.2	III	1.14
Internal Pressure (kPa)	300		

Qty Per Pallet	Pallet Size	Shrink Wrap	Strap	Pallet Hood	Layer Pad	Foam Wrap
8	1100mm x 1100mm	Yes	Optional	Optional	N/A	N/A

N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained. Additional UN information can be found on www.vca.org.gov Information on terms & conditions can be found on www.jamesgcarrick.com

This document is uncontrolled when printed.

James G Carrick & Co Ltd
450 Petershill Road
Springburn
Glasgow
G21 4PB

Tel +44 141 558 6008
Fax +44 141 557 0318
e mail sales@jamesgcarrick.com