







### The development of floors and flooring materials within the broad range of commercial developments has been very pronounced over the past decade.

Not only have floors become more exotic in both design and material selection but, equally, we all expect to see the floor maintained to an exceptionally high standard, literally sparkling cleaning, in high profile locations; super clean in the workplace and public space... just as we would expect in our own living space.

Numatic

limate

Contents

Hurricane Nuspeed TwinTec Mains / Cable TwinTec Battery

Walk Behind it Thermoplastic

The Right Equipment For The Right Job Will Provide The Right Results.

4-7	TwinTec Vario	22-25
8-9	Ride-on	26-31
10-14	Brushes and Pads	32-33
15-21	Accessories	34-35



# Hurricane The 1000W Size

### The single disc floor machine is the heart of all hard floor cleaning and maintenance.

The Hurricane motor concept is designed to keep its "Cool" under continuous and arduous operation whilst its seamless power transmission to the floor is via our long-life, oil filled, low load planetary gearbox. THE HFM1015 150rpm machine is equipped with the 1000W Hurricane motor providing a lighter weight and economical solution.

- Planetary Gearbox Long life, oil filled, low load planetary gearbox.
- Hi-Cool Motor Heavy duty, long life motor.
- **ATC** (Automatic Torque Control) Monitoring and balancing power input throughout the cleaning cycle.
- Fully Adjustable Handle For the perfect working position.


NuLoc 2 Pad Drive System option


Large solution tank optio

All Hurricane models incorporate our ATC, Automatic Torque Control, monitoring and balancing operational power input throughout the cleaning cycle.



Optional Hi-Dust Motor Filter





4 (See page 32 for full accessories) Images may include optional access



HFM1015

# Hurricane The 1500W Size

### The HFM 1500 series is available in a choice of 4 different speeds, 150rpm, 230rpm, 300rpm and extra Hi-speed 450rpm.

All models are fitted as standard with our generous oversize Hurricane 1500W drive motor allowing for higher speeds and the use of added weight as required.

The long life, low load, oil filled planetary gearbox ensures seamless power transmission to the floor ensuring excellent results.

With the range of speeds available machines can be selected to cover the whole range of floor care maintenance be it scrubbing, polishing, buffing, burnishing or spray cleaning.

- Planetary Gearbox Long life, oil filled, low load planetary gearbox.
- NuLoc 2 Systems Optional pad interchange systems, quick, simple and secure.
- Hi-Cool Motor 1500W motor allowing for higher speeds and the use of added weight as required. Available in a choice of 4 speeds 150rpm, 230rpm, 300rpm, 450rpm.
- ATC (Automatic Torque Control) Monitoring and balancing power input throughout the cleaning cycle.
- Fully Adjustable Handle Adjustable for the perfect position.

 Accessories A range of accessories available to cover wet applications, carpet shampooing, vacuum polishing and floor sanding.

Tha



Model Motor Deck HFM1515 HFM1523 1500W 450mm HFM1530 HFM1545





HFM1515



Optional spray clean system

Brush	Pad	Power	Speed	Vacuum	Range	Weight	Dimensions (WxLxH)
			150rpm				
450	400	230V AC 50Hz	230rpm		~~	0.01	
450mm	400mm	50Hz	300rpm	Optional	32m	32kg	460x560x1250mm
			450rpm				

# Hurricane The Two Speed

### There are more and more applications where the floor machine must fulfil two functions literally at the "Flick of a Switch".

The HFT model is fitted with the Hurricane dual performance motor rated at 1000W/1250W providing optimised power options at the two different operating speeds.

For scrubbing you want 150rpm but for polishing 300rpm giving guicker and better results. This is very much the case in hospitals, care homes, hotels, schools, etc. where the needs vary quite substantially each day and two separate machines are not always practical or available.



HFT Twin speed selection

 Planetary Gearbox Long life, oil filled, low load planetary gearbox.

#### • Dual Speed

Dual speed motor giving speeds of 150rpm for scrubbing and 300rpm for polishing.

 ATC (Automatic Torque Control) Monitoring and balancing power input throughout the cleaning cycle.

Accessories A range of accessories available to cover wet applications, carpet shampooing, vacuum polishing and floor sanding.

Easy


storag



Adjustable handle

tional 10Kg Additional weight (150rp)

HFT1530





# Humicane NUShine The High Speed Burnisher

Great styling, easy control and powerful. Designed to allow for effortless performance at higher burnishing speeds. When size and weight are a factor the HNS offers the ideal balance.


A compact yet powerful machine with supreme manoeuvrability. If you want stunning results combined with effortless performance then this is the machine for you. The NuShine has complete directional control which means a consistently high standard of finish.

- Powerful Hi-Cool 1500W Motor Heavy duty, long life motor.
- Automatic Torque Control Monitoring power and balance.
- Fully Adjustable Operator Handle Easy to use and fully adjustable operator handle.
- Effortless Effortless all direction control, superb manoeuvrability.
- Brush Pressure Monitor Allowing you to be in control of the surface finish achieving optimum results



500mm HNS1550





1500W

Pad Pressure Cleaning Range Weight 32m 25ka

# **NuSpeed** The Super Compact Size

### The LoLine will put truly usable power, convenience and efficiency in the hands of the operator, giving superb results.

The LoLine rotary has been designed specifically to meet the demand and raise the handling and performance levels to an exceptional user friendly standard.

Our LoLine NLL332 can claim performance characteristics equal to that of bigger, more industrial machines, yet with an ease and speed of operation that will immediately endear it to any user.


A full range of 33cm (13") brushes and pad drives allows the machine to be used for all of the primary floorcare functions





• Pads and Brushes Full range of 33cm (13") brushes and pad drives for all primary floor care

- Easy Storage Only 18kg in weight, compact size and folding design means easy and convenient to move and store.
- 200rpm 200rpm means versatility but equals performance of bigger more industrial machines.





Model Motor Deck Brush Pad Power Speed Vacuum Range Weight Dimensions (WxLxH) NLL332 400W 330mm 330mm 330mm 230V AC 50/60Hz 200rpm -32m 18kg 450x580x1185mm

# **NuSpeed** The Full Size

### The NuSpeed range of professional Floorcare machines has been specifically designed to provide optimum results whatever the application.

All NuSpeed NR models within the range are equipped with our performance enhancing ATC (Automatic Torque Control) feature. This is a unique system that monitors operation and boosts torque as required to provide consistent performance under varying load conditions.

#### ATC

ATC (automatic torque control) monitoring and balancing power input throughout the cleaning cycle.

Xtra Weight

Unique Nuspeed design means an increase in operating weight of 40kg can be achieved within the standard specification.

 Easy Storage Compact size and folding handle means easy and convenient to move and store.



Deck

NR1500 folded for storage



Infin

and an and the second of the surf way of

# TwinTec The Cylinder Machine

### Designed to be compact, easy to operate and exceptionally manoeuvrable when in use, whilst the oversized transit wheels allow easy movement to and from any specific locations.

The cylinder power brush ensures deep cleaning performance, whilst the twin water pickup nozzles allow multi-directional operation which is vitally important when cleaning narrow walkways often found in shops and food stores. You can walk in forwards and reverse out without turning and without loss of scrubbing and drying performance.




Model	Brush Motor	Vac Motor	Power	Brush Speed	Range	Brush Width	Capacity	Weight	Dimensions (WxLxH)
TT1535S	400W	1000W	220-240V	1000rpm	42m	450mm	15L	38kg	480x750x740mm



Overfill cut off system

- **Compact** Yet exceptionally manoeuvrable.
- **Multidirectional** Twin water pickup nozzles for all round cleaning.
- Cylinder Power Brush Ensures deep cleaning.
- Swing Steering Provides easy directional control.
- Transit Wheels
   Oversized transit wheels allow easy
   movement to and from any location.
- Simple Control Easy to use operator controls.







Operator controls

## **TwinTec** The Compact Single Disc

The TwinTec 1840 cable machine has been designed to address the question of size being exceptionally compact, yet with performance equal to bigger machines.

The compact design really does allow this machine to clean in areas normally cleaned by hand, yet 30% to 40% faster and better.

Although designed for small and congested areas the TT1840 is equally at home in larger areas and can be used in conjunction with our cable roll, "the cable reel that rolls", extending the cable length from 20m to 40m without any loss of performance.

The style and proportion of the polyform water tanks allow for the machine to adopt a convenient tilt position with only approximately 5 litres in the clean water tank to facilitate single handed brush or pad changing.

20m Cable i



• **Convenient** Fold flat design for easy transport from site to site.

- **Rugged Construction** Tough all steel chassis design.
- Fully Adjustable Handle For the perfect working position.
- Low Noise Quieter, unobtrusive design means true versatility.
- Easy Change Easy one handed brush or pad changing.



Visible operation

Model	Brush Motor	Vac Motor	Power	Brush Speed	Range	Pad/Brush Width	Capacity	Weight	Dimensions (WxLxH)
FT1840	400W	300W	220-240V 50Hz	150rpm	42m	360/400mm	18L	40kg	520x880x1132mm





Simple controls



Easy and generous fill cap

## **Ecolec** Value Engineered

The EcoTec Economy 4045 is designed to provide an exceptional "value for money" professional machine and to clean to a professional standard.

The very big advantage of the cable electric machines is the exceptional power and performance available to clean floors that are both rough and excessively dirty.

Two cost saving specification changes have been made compared with the TT premium model, being a nutex epoxy powder coated chassis in place of stainless steel and a Structofoam floor tool in place of aluminium.



Mod	el Brush Motor	Vac Motor	Power	Brush Speed	Range	Pad/Brush width	Capacity	Weight	Dimensions WxLxH
ET40	45 1500W	1000W	220-240V 50Hz	150rpm	42m	400/450mm	40L	57kg	470x890x1180mm

Structofoan floor too



Non-marking wheels

- Nutex Chassis Nutex epoxy powder coated chassis.
- Planetary Gearbox Numatic high efficiency long life gearbox.
- Structofoam Tilting Brush Deck Making brush changes quick and simple.
- Polyform Tanks Heavy duty clean and dirty water tanks.
- Twinflo Vacuum Motor Provides exceptional wet pick up.
- Fully Adjustable Handle For the perfect working position.
- Simple Control System Soft touch Nutronic controls.



Flexifill 1m easy fill hose

### TwinTec A Range of Two

The TwinTec mains cable range has masterful performance moving under its own brush power with amazing speed and purpose. Available with 45 or 55cm scrub width.

When selecting a scrubber dryer machine, the area that needs to be cleaned and the time available to clean it will determine the preferred size of the brush system.







Tilting deck for easy brush change and storage

Model	Brush Motor	Vac Motor	Power	Brush Speed	Range	Pad/Brush Width	Capacity	Weigh
TT4045		100014	220-240V	150	40	400/450mm	401	67kç
TT4055	1500W	1200W	50Hz	150rpm	42m	500/550mm	40L	68kç

12 (See page 32 for full accessories)

Care must be taken, however, to ensure that bigger is better but not too big, taking into account the obstructions that must be navigated during the daily cleaning cycle.

- Twinflo Vacuum Motor Provides exceptional wet pick up.
- Structofoam Tilting Brush Deck Making brush changes quick and simple.
- Planetary Gearbox. Long life, oil filled, low load gearbox.
- Simple Control Simple on / off trigger control.
- Polyform Tanks Heavy duty clean and dirty water tanks.
- Stainless Chassis Strong full stainless steel chassis.
- Flexifill System Easy filling and emptying system.



Full stainless steel chassis and non marking wheels imensions (WxLxH 470x890x1100mm 560x935x1100mm



Flexifill 1m easy fill hose



# TwinTec Big & Bold

### The TT6650 cable machine is a genuine workhorse providing a truly cost effective answer to big area low cost floor maintenance.

First and foremost the user will find the TT6650 as easy to use as our smaller machines with the control and operation systems to exactly the same specification, it handles like a dream.

Big capacity polyform tanks provide a full 60 litre capacity to match the exceptionally stable 65cm single brush scrubbing head, complemented by an oversized, floating aluminium floor tool.



- Structofoam Tilting Brush Deck Making brush changes quick and simple.
- Fully Adjustable Handle For the perfect working position.
- Twinflo Vacuum Motor Provides exceptional wet pick up.
- Stainless Chassis Strong stainless steel chassis.



#### Easy tank filling access Easy and generous fill cap

# TwinTec Battery Compact

# The TwinTec 1840 cable machine has been designed to address the question of size being exceptionally compact, yet with performance equal to bigger machines.

The compact design really does allow this machine to clean in areas normally cleaned by hand, yet 30% to 40% faster and better.

- Cable Free
- Total freedom of 24V battery operation. • Battery Pack
- Quick change 24V gel battery pack.
- Water Feed System 360° water feed system for uniform liquid delivery to floor.
- Fully Adjustable Handle Flat to upright for perfect position.
- **Parabolic Squeegee** 270° rotating parabolic squeegee system.
- Quick Change
   Fast, single handed brush or pad
   changing.
- Hi / Lo Mode For quieter cleaning when needed.

Simple soft touch controls



Model	Brush Motor	Vac Motor	
TTB1840	400W	300W	į

14 (See page 32 for full accessories)







Quick change gel battery pack

Power	Run Time	Recharge Time	Pad/Brush Width	Capacity	Weight	Brush Speed	Dimensions WxLxH
2x12V 4V 18Ah)	45min	6hrs	360/400mm	18L	52kg	150rpm	520x850x1132mm

# Ecotec Battery Value & Performance

### The EcoTec Economy 4045 is designed to provide an exceptional "value for money" professional machine.

The ETB4045 has a number of cost saving variations introduced into the specification without loss of performance or operating life. The LoLine chassis is manufactured in nutex epoxy powder coated steel in place of stainless steel; the wet pick up floor tool is Structofoam rather than aluminium and the machine is fitted with fully sealed 60Ahr gel batteries.



# TwinTec Battery Setting the Standard

With these machines every part is designed to combine the best in functionality and reliability.



- Provides exceptional wet pick up.
- Structofoam Tilting Brush Deck Making brush and pad changing quick and easy.
- Easy Operation Simple on / off trigger control.
- Stainless Steel Chassis Strong, long life, low maintenance.
- On Board Charging Convenient and easy, just plug and go.
- **Hi / Lo Mode** For quieter cleaning when required.

			-	·		Soft touch	Nutronic	control	S		
Model	Brush Motor	Vac Motor	Power	Run Time	Recharge Time	Pad/Brush Width	Capacity	Weight	Traction Drive	Brush Speed	Dimensions WxLxH
TTB4045				0.0511mg	1	400/450mm		128kg			470x1075x 1160mm
TTB4055	400W	400W	2x12V (24V 100Ah)	2.25Hrs		500/550mm	40L	134kg	-	100rpm	560x1115
TTB4055T				2.3Hrs		500/550mm		140kg	250W		x1160mm
T= Traction	drive										

16 (See page 32 for full accessories)

The TTB4045 is the classic Numatic TwinTec 24V battery model. It started its life with 30 litre capacity, now raised to 40 litre, and is today the most popular model worldwide.The premium specification starts with a full stainless steel chassis, Structofoam tilting brush deck, polyform tanks, fully sealed gel batteries, built in battery charger, heavy duty TwinFlo wet pick up vacuum system and heavy duty geared brush drive.

The 4055 is one size up from the 4045 containing all the advanced TwinTec 24V features but with a 20% increased cleaning path.

The 4055T (traction) offers effortless cleaning due to the powerful traction unit. A traction model is essential where inclines such as wheelchair ramps are present.



On-board charger





Additional fill and filter point



Battery isolator key

# **TwinTec** Battery Twin Brush Power and Performance

### All the specification of other TwinTec models with the addition of a twin brush deep power cleaning system.

For more demanding high resistance floor surfaces the Twin Brush is often the preferred choice giving optimal performance in any situation.

There are two variations within this model, one with and one without the powered traction drive. The traction drive model must be selected for applications where inclines or wheelchair access ramps are part of the cleaning programme.



... Twin Brush Power and Performance



Unique flip-deck



- Fully Sealed Gel Batteries Maintenance-free batteries to ensure the highest standard of operational life.
- On Board Charging Convenient and easy, just plug and go.
- Stainless Steel Chassis Strong, long life, low maintenance.
- Polyform Tanks Tough Polyform clean and dirty water tanks.



On-board charger

18 (See page 32 for full accessories)

### • Fully Adjustable Handle For the perfect working position.

#### • Hours Meter


Monitors operational hours for service intervals.

#### • Unique Flip Deck

Easy to change pads and brushes with the flip up deck feature.



Soft touch Nutronic controls



Traction drive option



Additional fill and filter point



# **TwinTec** Battery 50% More Capacity for bigger areas

### Easy-to-use controls combined with professional cleaning.

The 55cm (20") size of TwinTec is becoming more and more popular and, in support of this, we have introduced two new models with 60 litre capacity, a 50% increase over the 40 litre models and available in both traction and non-traction specifications.

Both models of TTB6055 have 60 litre capacity and a 55cm (20") single brush scrubbing path, dual brush pressure selection, built in battery charging, easy fill and easy emptying facilities, with added traction power drive for the 6055T model which would be essential if inclines or ramps are involved.



2.25Hrs 3-4hr

60L

4.2kpl

T= Traction drive



Plug-in charger system

- Simple Operator Controls Soft touch Nutronic control panel.
- Traction Drive System Makes the cleaning of inclines safer and easier (TTB6055T).
- On Board Charging Convenient and easy, just plug and go.
- Full Cleaning Control Individual speed and water flow rate settings for full control.
- Flexifill System Easy filling and emptying with flexifill system.
- Fully Sealed Gel Batteries Maintenance-free batteries to ensure the highest standard of operational life.

### ...50% More Capacity for bigger areas



Flexifill 1m filling hose

Simple to use Nutronic control panel TTB6055 shown

Security key

Water flow indicator

Hi / Lo mode

Vacuum only mode


Brush pressure indicator

Battery life indicator



20 (See page 32 for full accessories)

TTB6055/T



## **TwinTec** Vario Two Into One Does Go

#### The TwinTec Vario 4555 provides a smaller machine yet with all the advanced and time tested features of the bigger walk behind model.



The TwinTec Vario 4555 has taken the very best technology from other models in the Vario range and integrated these features into one of the most compact, hard working, professional floor maintenance machines with a choice of either 45cm or 55cm scrubbing widths by virtue of the adjustable dual setting Vario deck design.

What has been achieved, both in terms of performance and handling, is truly outstanding, resulting in a machine that will become the preferred choice of many contractors servicing medium size contracts where overall machine size is an important user consideration.



Adjustable 45/55cm scrub deck

TTV4555

- Adjustable Scrub Widths 45cm or 55cm scrubbing width by virtue of the adjustable dual setting Vario deck
- On Board Charging Convenient and easy, just plug and go.
- Complete Cleaning Control Simple one touch dosing and versatile variable speed control.
- Fully Sealed Gel Batteries Maintenance-free batteries to ensure the highest standard of operational life.
- Simple Operator Control Nutronic soft touch operator controls.
- Flexifill System Easy filling and emptying with flexifill system.
- Safety Features Built in emergency stop button and removable power off security key are just two of the many safety features.

Model	Brush M	otor	Power	Vac Mot	or Cleaning Speed	Pad/Brus Sizes	h	Net Weight	Run Time	Water Capacity	Nuchem Capacity
TTV4555	400	v	2 x 12V =100Ahr	400W	0 - 4.2kph	400/500n 450/550n		158kg	2.25hrs	60L	5L
Water Flo	w Rate		Nuchem N	<i>l</i> ix	Max Climbing Gradient	Scrub Widths	Bru	ish Speed	Dim	ensions (WxLx	:H)
0.5, 1, 2, 3	3 L/min	100	:1 75:1 50	:1 25:1	9%	450/550mm	1	00rpm	550×	1280x1160r	nm

With a full 60 litre capacity, built in dosing and dual brush pressure, true versatility is the principal objective, not to mention built in battery charging, easy fill and emptying systems adding to the high level of user convenience and satisfaction.

### Twintec Vario Two Into One Goes Again, Even Bigger

The TwinTec Vario 5565 represents, in every way, the optimum walk behind traction auto-scrubber with a range of advanced, yet practical, features that truly allow us to claim... "Best in Class".

This TwinTec gets its Vario name from the fact that this one machine can, by a no tools adjustment and simple brush change, be set to operate at either a 55cm or 65cm scrubbing width... two machine choices in one.



#### In the 65cm mode the scrubbing head is automatically expanded to a practical offset operating mode, providing a 100mm head extension to the right hand side. This simple arrangement allows improved edge cleaning especially in aisles with racking or other obstructions.


The operator controls are a separate feature in their own right with independent selection of speed, water flow and chemical dosing all built in to the basic unit, all of which can be set to provide total convenience and consistency of operation.



- Flexifill System Easy filling and emptying with the flexifill
- Complete Cleaning Control Simple one touch dosing control and versatile variable speed control.
- Adjustable Scrub Widths 55cm or 65cm scrubbing width by virtue of the adjustable dual setting Vario deck
- Spot Cleaning Heavy duty spot cleaning means operator can over-ride standard brush pressure to 50kg for extra performance.
- Easy Transportation Built in easy transit mode for easy transportation between areas.

### The unique Twintec 55cm/65cm dual brush system...

A simple, no tool adjustment and brush change allows a selection of either 55cm or 65cm scrubbing widths.



Model	Brush Mo	otor	Vac N
TTV5565	2x400\	N	600
Brush Speed	Water Capacity		Nuche Capaci
200rpm	85L	Ор	tiona

safety features.

TTV5565

Simple to use Nutronic control pane



Beneath the hinged dirty water tank sits the operating heart of the Vario with its 200Ahr gel battery and charging system, high performance suction unit and NuChem dosing facility... all easily accessible.

otor	Power	Run Time	Traction Drive	Drive Speed	Cleaning Speed	Climbing Gradient	Scrub Widths
N	4 x 12V (24V) = 200Ahr	3.5 Hrs	480W	4.2km/h	4.2km/h	9%	550mm 650mm
ı y	Water Flow Rate	Nu	chem Mix		Weight	Dimensi	ons (WxLxH)
5L	3, 2, 1, .5L/min	25:1, 50	:1, 75:1, 10	0:1	287kgs	585x14	00x1135mm

# Compact Ride-ON Compact "Go Anywhere"

### Not too big, not too small, good capacity, simple controls, excellent performance and very competitive in terms of price.

In truth the CRO8055 is competitive with most walk behinds of the same size. So now you can sit rather than walk and by virtue of the exceptional manoeuvrability, substantial time will be saved on middle size applications.

The CRO8055 also introduces the logic of two machines in place of something much bigger or, to put it another way, Two for the Price of One with added versatility and convenience.

The CRO will go into places where bigger machines are not suitable and anything smaller is just too small.

### ... The Compact "Go Anywhere" Ride-on

- Compact Design
- Anti Tip System when cornering on full lock.
- Easy and convenient, just plug and go. Fully sealed low maintenance Gel batteries.
- Easy filling and emptying with the flexifill system.
- With fully adjustable speed control.







Charger port





Model	Brush Diameter	Capacity	Battery Power	Run Time	Traction Dri
CRO8055	550mm	80L	2 x 12V (24V) = 120 Ahr 2 x 12V (24V) = 100 Ahr	3h 2h	400W





# TwinTec Ride-ON A Serious Workhorse

A more user friendly ride on scrubber dryer would be hard to find. Designed to provide long, simple and reliable service day in day out whatever the environment.

The TRO650 is based on the well established engineering of the Vario TTV678 model but simplified to provide a truly professional, cost effective workhorse. You can vary the water flow and the operating speed to suit a whole host of conditions from big areas lightly soiled to heavy duty scrubbing in more arduous conditions.

### • Twin Brush

650 twin brush power head cleaning system.

...A Serious Two Brush Workhorse

- Easy Brush Access Easy side access to brushes for maintenance.
- Controlled Cleaning Fully adjustable water flow rate.
- On Board Charging Easy and convenient, just plug and go. Fully sealed low maintenance Gel batteries.
- Simple Operator Control Full dashboard control with soft touch Nutronic controls.
- Safety Features Emergency stop button, power off removable key, horn button and hazard warning light and built in reversing alarm are just a few of the many safety features included.
- Easy Maintenance Easy access to batteries and fuses fo maintenance.



Full control dashboard

A full 120 litre capacity with a fixed 650mm twin brush power head the TRO650 is ready to go.




asy brush access

The TRO650 is blessed with a commanding

traction drive, a magnificent turning circle and one pass performance that really will ensure you get the standard you want,

operator driving position, front wheel

exactly when you want it... and fast.





TRO Aluminium / Polyurethane floor tool

650 200rpm 120L 3. 2. 1. 0.5L/min

later Canac

Vac Moto

400W



365kgs


11%

aning Spee

3.5km/h

ıs (WxLxH)

944x1676x1425mm



28 (See page 32 for full accessories)

Brush Spe

Brush Moto

2 x 400W

Model

TRO650

Scrub Width

TRO650



Drive wheel protector



# **TwinTec** Vario Three Into One Does Go

A comfortable, driver friendly, 120-litre, front wheel drive machine with a fantastic turning radius, gets in and out of places other machines just won't go.

The TwinTec Vario "three in one" (3 in 1) design has proved itself to be almost the perfect balance between sound common sense engineering and innovative and truly functional technology.

Yes, one machine which can be set to 3 different working widths: 650, 750 and 850 and all at the flick of a simple selection lever. This doesn't even need tools - anybody can do it at any time. You want it wide fine...

you want it narrow - 30 seconds is all that it takes.

### The Vario TTV678, three brush widths in one system

The unique arrangement of 3 independent scrubbing heads which, by virtue of a simple adjustment mechanism, can provide a choice of scrubbing widths which, with the addition of a selection of brushes and pads, can provide customised performance on almost any surface application.





TTV678



### As unique today as when it started - patented technology

0

- Vario 3 In 1 Brush System Simple adjustment mechanism provides a choice of scrubbing widths suitable for almost any surface.
- Easy Dosing Pre-sets Correct chemical dosing for every task.
- Complete Cleaning Control Operator has full control of cleaning speed, brush speed, water flow and chemical dosing.
- Simple Operator Control Soft touch dashboard control system.
- Easy Maintenance Easy access to batteries and fuses for service purposes and brush change is simple with the swing out brush cover.
- On Board Charger Simple and convenient, just plug and go. Fully sealed low maintenance Gel **batteries**
- Small Turning Radius Means great cleaning even in tight spaces.
- Safety Features Emergency stop button, power off removable key, horn button and hazard warning light and built in reversing alarm are just a few of the many safety features included.
- Easy Maintenance Easy access to batteries and fuses for maintenance.





Dosing controls

3x24V 400W 24V 400V TTV678 650mm 50/100/ 150/200rpi



### Vario, the machine that gives you what you want.

In many applications changing circumstances change specific needs, so with the Vario you can change the specification to suit your exact requirements. It's not only the working widths that can be changed; it's the full operating performance that is under the driver's complete control - cleaning speed, brush speed, water flow and chemical dosing, nothing left to chance.



Easy brush change

	Power		Run Time		Traction Drive	Drive Speed	Cleaning Speed	Climbing Gradient	
,	6 x 12V (24V) = 300Ahr 8 x 12V (24V) = 400Ahr (Optional)		3.5 Hrs 4.5 Hrs		600W	7.0km/h	3.5km/h	11%	
ate ac		Water Flow Ra		Nuchen Mix	n Gross \	Veight (full)	Dimen	Dimensions (HxLxW)	
201	Optional 5L	4L/mii 3L/mii 2L/mii 1L/mii	n n	25:1 50:1 75:1 100:1		/+620kgs /+684kgs		676x1054mm	

## **Brushes** and Pad Drive

Careful selection of quality brushes and pads will ensure your Floorcare machine always operates at its best.



Polyscrub Brush General scrubbing duties suitable for most floor types.

Longlife Light Scrubbing Brush

Flexi PadLoc Drive Board For 300rpm Machines

Flexi specification provides optimum stability

needed for 300rpm speed machines.

Flexi NuLoc 2 Drive Board

offers an alternative to PadLoc.

Flexi specification provides optimum stability

needed for 300rpm speed machines. NuLoc2

scrubbing and polishing.

5

9



Nyloscrub / Shampoo Brush Suitable for when lighter scrubbing is required. Can be used for shampoo cleaning.

Nyloscrub Cylinder / Longlife Cylinder Brush

High Speed Spider PadLoc Drive Board

Spider design specification provides optimum

stability needed for 450rpm speed machines.

6

10

Can provide extended cleaning life in comparison to alternative light scrubbing brushes. Suitable for light available in two material specifications.



Union Mix Polish Brush Ideal for polishing uses a well-proven mix of high quality bristles for optimum results.

Longlife Heavy Duty Scrubbing/Stripping Brush

comparison to alternative heavy duty scrubbing

Alternative to PadLoc that may be required when

using a rotary machine in certain circumstances.

brushes. Suitable for heavy duty scrubbing.

Can provide extended cleaning life in

7

11

15

Nuplex Pad

NuLoc 2 Drive Board

Suitable for general use.



Longlife / Scrubbing Brush Can provide extended cleaning life in comparison to standard scrubbing brushes. Suitable for general scrubbing.



PadLoc Drive Board A simple, effective and easy to use system Pads are located securely and perfectly centred every time. Suitable for general use.



High Speed Spider NuLoc 2 Drive Board Spider design specification provides optimum stability needed for 450rpm speed machines. NuLoc2 offers an alternative to PadLoc.



NuShine Topline Speed Burnish Pad Burnishing pad for use with Nushine HNS1550 (500mm). Supplied as pack of 5.





Wire Scarifying Brush Suitable for scarifying a range of floor surfaces, typically used in preparation of concrete flooring.



Can be used as an alternative pad drive board

Porcupine Pad Holder

when required.

Sandotex Disc Drive Highly abrasive disc for use on rotary machine.



Low water, chemical free maintenance suitable

for a wide range of applications.


Carbotex Grinding Disc Carbon based discs provide high abrasive properties with long life.



Heavy Duty Scarifying Disc - Spirotex 6 Head Heavy duty scarifying board fitted with 6 wire Spirotex heads.

Image No.	Description	Brush / Pad Size mm	Part Number	HFM1015 HFM1515 /1523
		280	606029	
		330	606033	
1	Polyscrub brush	400		
		450		•
		550	0         606029           0         606033           0         606105           0         606203           0         606028           0         606028           0         60652           0         606550           0         606550           0         606550           0         606550           0         606550           0         606551           0         606553           0         606551           0         606551           0         606551           0         606551           0         606551           0         606172           0         606172           0         606172           0         606172           0         606172           0         606175           0         606172           0         606172           0         606172           0         606173           0         606175           0         606326           0         606327           0         606328	
⊢		650 280		
2		330		
	Nyloscrub brush	450		•
		550		
		650		
		330		
3	Union mix polish brush	400	606102	
		450	606202	•
		280	606553	
		400	606302	
4	Longlife brush	450		•
		550		
		650		
		280		
1	Octo Polyscrub brush	300		
H		330         606174           280         606171           300         606151		
2	Octo Nyloscrub brush			
2				
H		280		
2	Octo high density Nyloscrub brush	330		
		280		
4	Octo longlife brush (green)	300		
		330	300         606153           330         606176	
		280	606326	
5	Octo longlife brush (red)	300	606327	
		330		
		400		
5	longlife light scrubbing brush (red)	450		•
	1525 Nulagarub aulindar brush	550		
6	1535 Nyloscrub cylinder brush 1535 Floortec cylinder brush			
6	Floortec scrubbing /stripping brush (black)	450		
1	r loortee serubbing / stripping brush (black)	400	000303	•
		360	606400	
		400		•
8	Padloc drive board (black)	500		
		600		
		280	606405	
8	Padloc octo drive board	330	606407	
		300	606406	
9	Padloc flexi-drive board for 300 rpm	400	606411	
10		400	606412	
8	Twin PadLoc drive board	280	606409	
_				
		280	900713	
		360	900524	
111	Nul oc2 drive board	400	900525	•

NuLoc2 drive board 900525 400 500 900526 600 900717 280 900718 Octo NuLoc 2 drive board 300 900719 330 900720 12 High speed spider NuLoc 2 drive board (HFM/NR) 400 900527 13 Flexi NuLoc 2 drive board for 300rpm machines (HFM/NR) 400 900528



Guidance only - Each application should be assessed before selection of brush / pad. Specification subject to change without prior notice.

32

Supplied with standard machine

## Accessories

#### Using genuine Numatic accessories will ensure you achieve the best results from your Floorcare machine.

Each accessory is developed with professional cleaners in mind, good quality design makes all the difference when a task is repeated day after day.

### Hurricane and NuSpeed Accessories











NR 10Kg Weight For NR 1500S PN:606113 HFM 10Kg Weight For HFM 1500S PN:606077



NR Dustrol Kit (Grey) PN:606056 HFM/NR Dustrol Control Brush Ring (Also Standard With Dustrol Kits) PN:606079

### TwinTec / Vario Blade Sets





ET4045 / ETB4045 Replacement Rubber Blade Set, 785mm Working Width. PN:606037



Replacement Rubber Blade Set (4 pieces) PN:606057



ET4045 / ETB4045 Optional Polyurethane Blade Upgrade Kit 785mm Working Width PN:606074



Optional Replacement Polyurethane Blade Set (4 pieces) PN:606091

NR Optional Spraytec Kit PN:606054

HFM/HNS Optional Spraytec Kit PN:606325

NLL Solution Tank PN:606101



TT4045 / TTB4045 / TTV678 Replacement Polyurethane Blade Set, 805mm Working Width TT4045/TTB4045/CR08055/TTV678 PN:900518 TT4055/TTB4055/TTB6055/TTV4555 PN:900519 TTB6650/TTV5565/TTV678 PN:900520







ET4055 / ETB4055 Optional Large Structofoam Floor Tool, Rubber Blade, 845mm Working Width. PN:606310

### TwinTec / Vario Accessories





All TT/TTB Machines Wander Floor Kit (32mm) (Except TT / TTB1840) PN:607250

All TTB Machines Wander Floor Kit (38mm), (Except TT / TTB1840) PN:606193





Twintec / Vario Aluminium Floor Tool Wide Angle Adjustable Castor Plate Upgrade Kit. PN:606319


Twintec / Vario 38/32mm Hose Adaptor PN:237220





Twintec / Vario Floor Tool Detent Pin PN:206953

TT / TTB4045 / 4055 Floor Tool Bracket Assembly PN:304466



38mm Dosing Tank Cap PN:303827





TTV USB Preset Locking Key PN:606279

34





TTV678 38mm Emptying Hose Extension PN:606186



Generic 20m Cable Roll Extension UK PN:612002 20m Cable Roll Extension Euro PN:612003



TT / TTB6055 / TTV4555 / 5565 Floor Tool Bracket Assembly, PN:304479



TTV678 Battery LED Front Light Kit PN:606170



Twintec / Vario Emptying Hose Extension Kit PN:609100



TRO650 / TTV678 Floor Tool Bracket Assembly. PN:303795



TTV4555 / TTV5565 Dosing Tank PN:606278



TTB1840 Battery & Charger Pack UK PN:606266, EUR PN:606267, CH PN:606268, USA PN:606269, SA PN:606270, AUS PN:606271

TTB1840 Charger Pack UK PN:606272, EUR PN:606273, CH PN:606274, USA PN:606275, SA PN:606276, AUS PN:606277 (Boxed) PN:606260




### Numatic International Limited,

Chard, Somerset, TA20 2GB, UNITED KINGDOM

Tel: 01460 68600 Fax: 01460 68458

www.numatic.co.uk



13/17 rue du Valengelier, EAE la Tuilerie, 77500 Chelles, FRANCE

Tel: 01 64 72 61 61 Fax: 01 64 72 61 62

www.numatic.fr



#### Numatic International BV

BeNeLux Distribution Numatic International BV Postbus 101 2400 AC Alphen aan den Rijn NEDERLAND

Tel: 0172 467 999 Fax: 0172 467 970

#### www.numatic.nl



Numatic International GMBH

Fränkische Straße 15-19, 30455 Hannover DEUTSCHLAND

Tel: 05 11 98 42 16 0 Fax: 05 11 98 42 16 20

#### www.numatic.de



#### Numatic International Schweiz AG.

Sihlbruggstraße 142 6340 Baar, SCHWEIZ

Tel: 041 768 07 60 Fax: 041 768 07 69

www.numatic.ch



### Numatic International

Centro de Negócios da Maia Rua Albino José Domingues n.º 581 4470 - 034 Maia PORTUGAL

Tel: 351 220 047 700

#### www.numatic.pt



Numatic International (Pty.) Ltd.

16th & Pharmaceutical Roads, Midrand, Gauteng, S.A. 1685.

Tel: 0861 686 284 Fax: 0861 686 329

www.numatic.co.za



Specification subject to change without prior notice. 901450/0815 ©Numatic International Limited 2015