

PAREX
Building expertise, together



**THE IDEAL
SURFACE FOR A
PERFECT FINISH!**

www.parex.co.uk

WHY USE A LEVELLING COAT?

GUARANTEE OF A HIGH PERFORMANCE SUBSTRATE

- The levelling coat prepares the substrate to receive the desired floor finish
- The levelling coat creates an even, smooth surface
- The levelling coat corrects any discrepancies in surface regularity

CONDITIONS TO CONSIDER

- Type of use of premises
- Thickness of levelling coat
- Type of substrate
- Type of covering
- Delay before return to use

PRODUCTS

172 SOLCLASSIC

- Light Traffic, domestic, offices, schools
- Suitable for concrete floors including those encasing hot water underfloor heating
- Rapid setting - walk on in 3 hours in suitable conditions
- Up to 20mm thickness in one pass
- Primer free application on new cement based substrates



184 SOLFIBRE

- Light Traffic, domestic, offices, schools
- Flexible and fibre reinforced
- Suitable for wooden floors and flexible substrates
- Suitable for concrete floors encasing hot water or electric underfloor heating
- Up to 10mm thickness in one pass



176 SOL 4000

- High traffic use, airports, hospitals, supermarkets
- Up to 20mm in a single pass
- Pumpable or hand application
- Rapid setting - walk on in 3 hours in suitable conditions
- Primer free application on new cement based substrates



ALWAYS APPLY A PRIMER BEFORE A LEVELLING COAT

165 PROLIPRIM UNIVERSEL

Multiple substrates, doesn't stain. White when applied translucent when dry.

163 OMNISOL

Thick renovation primer for all substrates
Ideal for wood floors and flexible substrates.



PRODUCT GUIDE

	Levelling Compound			Primer	
Substrate	172 SOLCLASSIC	176 SOL 4000	184 SOLFIBRÉ	165 POLYPRIM UNIVERSEL	163 OMNISOL
Cement/concrete	✓	✓	✓	✓	✓
Wood substrates			✓		✓
Existing well bonded tiles	✓	✓	✓	✓	✓
Sanded paintwork on solid floors	✓	✓	✓	✓	✓
Anhydrite screeds - <i>Primer must be applied</i>	✓	✓	✓	✓	✓
Concrete floors encasing hot water under floor heating	✓	✓	✓	✓	✓
Electric under floor heating			✓	✓	✓
Use	Indoor	Indoor	Indoor	Indoor	Indoor
Location	light traffic, domestic, offices, classrooms	high traffic, airports, hospitals, supermarkets	light traffic, domestic, offices, classrooms	light traffic, domestic, offices, classrooms	light traffic, domestic, offices, classrooms
Thickness (mm)	1 to 20	3 to 20	3 to 20	n/a	n/a

FOR A FULL PRODUCT RANGE OR FOR APPLICATIONS NOT COVERED PLEASE CONTACT PAREX



PRIME



MIX & POUR



LEVEL

OUR MULTI-PURPOSE HIGH PERFORMANCE FLOOR PREPARATION AND SELF-LEVELLING PRODUCTS



www.parex.co.uk

PAREX LTD - Holly Lane Industrial Estate, Atherstone, Warwickshire. CV9 2QZ

Tel: +44 (0)1827 711755 Fax: +44 (0)1827 711330

Email: enquiries@parex.co.uk