

# GÖLZ®



## Table saws

[www.golzgroup.com](http://www.golzgroup.com)

## Bridgesaws for tiles and natural stones



## Professional tile cutting machines!



**TS200 - Blade Ø 200 mm**

**Cutting length 720 mm**

**TS250 - Blade Ø 250 mm**

**Cutting length 1.140 mm**

- Cutting head adjustable up to 45° (Jolly cutting)
- Removable water tub, easy for cleaning
- Foldable legs
- Adjustable cutting length
- Removable cutting table, easy for cleaning
- Electric water pump with quick coupling, easy for changing the pump
- Pluggable blade guard for easy changing of diamond blade



45° miter-cut built-in



extension working table  
(optional accessory)



removable water tub



transport handles



foldable legs



quick coupling of water  
pump



transport wheels



removable cutting table

Specifications	GÖLZ TS200	GÖLZ TS250
Motor	Electric, 230V, 50Hz, IP54	
Power	1,3 kW	
Max. cutting depth	40 mm	65 mm
Max. blade size	200 mm	250 mm
Arbor hole	25,4 mm	25,4 mm
Cutting length	560 mm (720 mm)	980 mm (1140 mm)
Shaft speed	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>
45° miter-cut	Built-In	Built-In
Water pump	S2, 230 V, 50 Hz, 55 Watt	
Blade flange size Ø	64 mm	64 mm
Transport wheels	yes	yes
Cutting table (LxW)	720 x 480 mm	1.140 x 480 mm
Dimensions (LxWxH)	1.220 x 540 x 1.299 mm	1.640 x 540 x 1.299 mm
Weight	57 kg	72 kg
Order number	0289 200 1000	0289 250 1000

Accessories	Order number
Side table	0289 250 9002
Spare water pump with connector plug	0289 400 9002

**Robust bridge saw for the stone industry.  
Precise cutting of granite, marble, terrazzo and tiles.**



transport handles



foldable legs



quick coupling of water pump



transport wheels



45° miter-cut built-in



adjustable cutting length



front protection shield



removable water tub

## Bridge Saw Cutting length 1.200 mm Blade-Ø 350 mm

- Cutting head adjustable up to 45°
- Diamond blade Ø 350 mm
- Max. cutting depth 110 mm
- Removable water tub, easy for cleaning
- Electric water pump with quick coupling, easy for changing the pump
- Foldable legs
- Transport wheel, easy for moving and loading
- Adjustable cutting length
- Removable cutting table, easy for cleaning
- The front shield prevents operator against water spray
- Embedded cable protection chain, protects cables against damage
- Special water nozzle for optimized water cooling

Specifications	GÖLZ GS350
Motor	Electric, 230V, 50Hz, IP54
Power	2,2 kW
Max. cutting depth	110 mm
Max. blade size	350 mm
Arbor hole	25,4 mm
Cutting length	1.000 mm (1.200 mm)
Shaft speed	2.800 min <sup>-1</sup>
45° miter-cut	Built-In
Water pump	S2, 230 V, 50 Hz, 55 Watt
Blade flange size Ø	90 mm
Transport wheels	yes
Cutting table (LxW)	1.200 x 530 mm
Dimensions (LxWxH)	1.710 x 700 x 1.360 mm
Weight	95 kg
Order number	0289 350 3000

Accessories	Order number
Spare water pump with connector plug	0289 400 9002
Set of Transport wheels	0289 400 9068

**Professional aluminium bridge saw!**  
**The professional solution for long granite and natural stones.**



transport handles



foldable legs



handle wheel feeding system



transport wheels



45° miter-cut built-in



adjustable cutting length



front protection shield



removable water tub

**Aluminium Bridge Saw**  
**Cutting length 2.000 mm**  
**Blade-Ø 350 mm**

- Much more stronger aluminium structure
- Cutting head adjustable up to 45°
- Max. cutting length up to 2 meter
- Removable water tub, easy for cleaning
- Electric water pump with quick coupling, easy for changing the pump
- Foldable legs
- Transport wheel, easy for moving and loading
- Adjustable cutting length
- The front shield prevents operator against water spray
- Embedded cable protection chain, protects cables against damage
- Pluggable blade guard for easy changing of diamond blade
- Handle wheel feeding system, easy for long cutting
- Special water nozzle for optimized water cooling
- Removable cutting table, easy for cleaning

Specifications	GÖLZ GS350A-M	GÖLZ GS350A-XL
Motor	Electric, 230V, 50Hz, IP54	
Power	2,2 kW	2,2 kW
Max. cutting depth	110 mm	110 mm
Max. blade size	350 mm	350 mm
Arbor hole	25,4 mm	25,4 mm
Cutting length	1.500 mm (1.650 mm)	1.850 mm (2.000 mm)
Shaft speed	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>
45° miter-cut	Built-In	Built-In
Water pump	S2, 230 V, 50 Hz, 55 Watt	
Blade flange size Ø	90 mm	90 mm
Transport wheels	yes	yes
Cutting table (LxW)	1.650 x 529 mm	2.000 x 529 mm
Dimensions (LxWxH)	1.810 x 740 x 1.490 mm	2.310 x 740 x 1.490 mm
Weight	113 kg	135 kg
Order number	0289 350 4000	0289 350 5000

Accessories	Order number
Spare water pump with connector plug	0289 400 9002

High performance bench- and block-  
saws for the construction site



## Ultra compact and light-weight masonry saw Cutting length 560 mm

- Compact design, easy for moving
- Removable water tub, easy for cleaning
- Electric water pump with quick coupling, easy for changing the pump
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving



removable water tub



special water nozzle

Specifications	GÖLZ MS350C
Motor	Electric, 230V, 50Hz, IP54
Power	2,2 kW
Max. cutting depth	110 mm
Max. blade size	350 mm
Arbor hole	25,4 mm
Cutting length	560 mm
Shaft speed	2.800 min <sup>-1</sup>
45° miter-cut	No, Miter-block optional
Water pump	S2, 230 V, 50 Hz, 55 Watt
Blade flange size Ø	90 mm
Transport wheels	yes
Cutting table (LxW)	400 x 400 mm
Dimensions (LxWxH)	960 x 640 x 1.250 mm
Weight	56 kg
<b>Order number</b>	<b>0289 350 1000</b>

Accessories	Order number
45° Miter-block	0289 350 1900
Set of Transport wheels	0289 400 9002
Spare water pump with connector plug	0289 400 9068

## Compact and light-weight masonry saw Cutting length 700 mm

- Compact design, easy for moving
- Removable water tub, easy for cleaning
- Electric water pump with quick coupling, easy for changing the pump
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving



transport wheels



quick coupling of water pump

Specifications	GÖLZ MS350L
Motor	Electric, 230V, 50Hz, IP54
Power	2,2 kW
Max. cutting depth	110 mm
Max. blade size	350 mm
Arbor hole	25,4 mm
Cutting length	700 mm
Shaft speed	2.800 min <sup>-1</sup>
45° miter-cut	No, Miter-block optional
Water pump	S2, 230 V, 50 Hz, 55 Watt
Blade flange size Ø	90 mm
Transport wheels	yes
Cutting table (LxW)	600 x 530 mm
Dimensions (LxWxH)	1.100 x 640 x 1.250 mm
Weight	63 kg
<b>Order number</b>	<b>0289 350 2000</b>

Accessories	Order number
45° Miter-block	0289 350 1900
Set of Transport wheels	0289 400 9002
Spare water pump with connector plug	0289 400 9068

**Compact and universal masonry saw with 45° tilting head!**



**Cutting length 700 mm**

**Blade-Ø 400 mm**

**Cutting depth 137 mm**

- Huge cutting table: 600x530 mm
- Removable water tub, easy for cleaning
- Foldable legs
- Electric water pump with quick coupling, easy for changing the pump
- Max. cutting length up to 800 mm
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving



special water nozzle



cutting head adjustable up to 45°



removable water tub



transport handles



foldable legs



quick coupling of water pump



transport wheels

Specifications	GÖLZ MS400
Motor	Electric, 230V, 50Hz, IP54
Power	2,2 kW
Max. cutting depth	137 mm
Max. blade size	400 mm
Arbor hole	25,4 mm
Cutting length	700 mm
Shaft speed	2.800 min <sup>-1</sup>
45° miter-cut	Built-In
Water pump	S2, 230 V, 50 Hz, 55 Watt
Blade flange size Ø	90 mm
Transport wheels	yes
Cutting table (LxW)	600 x 530 mm
Dimensions (LxWxH)	1.100 x 842 x 1.290 mm
Weight	66 kg
Order number	0289 400 1000

Accessories	Order number
Spare water pump with connector plug	0289 400 9002
Set of Transport wheels	0289 400 9068



Professional universal aluminium masonry saw with 45° tilting head!



**Cutting length 800 mm**

**Blade-Ø 400 mm**

**Cutting depth 137 mm**

- Removable water tub, easy for cleaning
- Foldable legs
- Electric water pump with quick coupling, easy for changing the pump
- Much more stronger aluminium structure
- Max. cutting length up to 800 mm
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving



special water nozzle



aluminium cutting and structure



removable water tub



transport handles



foldable legs



quick coupling of water pump



transport wheels

Specifications	GÖLZ MS400A
Motor	Electric, 230V, 50Hz, IP54
Power	2,2 kW
Max. cutting depth	137 mm
Max. blade size	400 mm
Arbor hole	25,4 mm
Cutting length	800 mm
Shaft speed	2.800 min <sup>-1</sup>
45° miter-cut	Built-In
Water pump	S2, 230 V, 50 Hz, 55 Watt
Blade flange size Ø	90 mm
Transport wheels	yes
Cutting table (LxW)	560 x 560 mm
Dimensions (LxWxH)	1.390 x 750 x 1.330 mm
Weight	79 kg
Order number	0289 400 2000

Accessories	Order number
Spare water pump with connector plug	0289 400 9002
Set of Transport wheels	0289 400 9068

Powerful Aluminium-block saw with parallel guided cutting head, ideal for cutting bricks, poroton blocks and marble blocks!



**Cutting length 650 mm / 800 mm**  
**Blade-Ø 700 mm**  
**Cutting depth 280 mm**

- Optional electrical motor or gasoline engine
- Cutting head with elastic device, easy for operation
- Electric water pump with quick coupling, easy for changing the pump (electrical motor version)
- High efficient mechanical water pump (Honda motor version)
- Much more stronger aluminium structure
- Max. cutting depth up to 150 mm and 280 mm (double-sided cutting)
- Max. cutting length up to 800 mm
- Removable water tub, easy for cleaning
- Foldable legs
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving

Specifications	GÖLZ MS700A
Motor	Electric, 230 V, 50 Hz, IP54
Power	2,2 kW (3 HP)
Max. cutting depth	280 mm
Max. blade size	700 mm
Arbor hole	30 mm
Cutting length	650 mm (280 mm material height) 800 mm (50 mm material height)
Shaft speed	1.450 min <sup>-1</sup>
45° miter-cut	no
Water pump	S2, 230 V, 50 Hz, 55 Watt
Blade flange size Ø	140 mm
Transport wheels	no
Cutting table (LxW)	510 x 540 mm
Dimensions (LxWxH)	1.630 x 760 x 1.600 mm
Weight	115 kg
Order number	0289 700 2000



special water nozzle



transport handles



foldable legs



quick coupling of water pump



removable water tub



Cutting cart with steel bearing rollers

Accessories	Order number
Spare water pump with connector plug	0289 400 9002
Set of Transport wheels	0289 400 9068

Powerful and robust masonry saw, available with electric motor or Honda gasoline engine.

**Cutting length 800 mm**  
**Blade-Ø 400 mm**  
**Cutting depth 150 mm (280 mm)**

- Optional electrical motor or gasoline engine
- Cutting head with elastic device, easy for operation
- Electric water pump with quick coupling, easy for changing the pump (electrical motor version)
- High efficient mechanical water pump (Honda motor version)
- Max. cutting depth up to 150 mm and 280 mm (double-sided cutting)
- Max. cutting length up to 800 mm
- Removable water tub, easy for cleaning
- Foldable legs
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving



Honda gasoline engine



special water nozzle



transport handles



foldable legs



transport wheels



removable water tub



cutting depth up to 280 mm (double-sided cutting)

Specifications	GÖLZ BS400	GÖLZ BS400
Motor	electric, 230 V / 400 V, 50 Hz	Honda GX200
Power	2,2 kW	4,8 kW / 6,5 PS
Max. cutting depth	150 mm (double-sided cutting 280 mm)	
Max. blade size	400 mm	400 mm
Arbor hole	25,4 mm	25,4 mm
Cutting length	800 mm	800 mm
Shaft speed	2.650 min <sup>-1</sup>	2.550 min <sup>-1</sup>
45° miter-cut	No, Miter-block optional	No, Miter-block optional
Water pump	S2, 230 V, 50 Hz, 55 Watt	efficient mechanical water pump
Blade flange size Ø	90 mm	90 mm
Transport wheels	yes	yes
Cutting table (LxW)	600 x 530 mm	
Dimensions (LxWxH)	1.110 x 640 x 1.400 mm	
Weight	90 kg	93 kg
Order number	0282 400 1000 (230 V) 0282 400 1100 (400 V)	0282 400 1300

Accessories	Order number
Spare water pump with connector plug	0289 400 9002
Set of Transport wheels	0289 400 9068

Compact Block saw - with electric motor or Honda gasoline engine at your choice. Ideal for cutting bricks, poroton blocks and marble blocks



transport handles



foldable legs



transport wheels



removable water tub



Honda gasoline engine



special water nozzle



cutting depth up to 235 mm

**Cutting length 400 mm / 600 mm**  
**Blade-Ø 600 mm**  
**Cutting length 235 mm**

- Optional electrical motor or gasoline engine
- Cutting head with elastic device, easy for operation
- Electric water pump with quick coupling, easy for changing the pump (electrical motor version)
- High efficient mechanical water pump (Honda motor version)
- Max. cutting depth up to 150 mm and 280 mm (double-sided cutting)
- Max. cutting length up to 600 mm
- Removable water tub, easy for cleaning
- Foldable legs
- Removable blade guard for easy blade change
- Special water nozzle for optimized water cooling
- Transportation wheel, easy for moving

Specifications	GÖLZ BS600	GÖLZ BS600
Motor	230 V / 400 V, 50 Hz, IP54	Honda GX200
Power	2,2 kW	4,8 kW / 6,5 PS
Max. cutting depth	235 mm	235 mm
Max. blade size	600 mm	600 mm
Arbor hole	25,4 mm	25,4 mm
Cutting length	400 mm	400 mm
	(280 mm material height)	(280 mm material height)
	600 mm	600 mm
	(50 mm material height)	(50 mm material height)
Shaft speed	1.440 min <sup>-1</sup>	1.650 min <sup>-1</sup>
45° miter-cut	no	no
Water pump	S2, 230 V, 50 Hz, 55 Watt	efficient mechanical water pump
Blade flange size Ø	130 mm	130 mm
Transport wheels	yes	yes
Cutting table (LxW)	600 x 525 mm	600 x 525 mm
Dimensions (LxWxH)	1.100 x 870 x 1.480 mm	1.100 x 870 x 1.550 mm
Weight	95 kg	98 kg
Order number	0282 600 1000 (230 V)	0282 600 1300
	0282 600 1100 (400 V)	

Accessories	Order number
Spare water pump with connector plug	0289 400 9002
Set of Transport wheels	0289 400 9068

Powerful block saw for the long term use on the jobsite



**Cutting length 500 mm**  
**Blade-Ø 650 mm**  
**Cutting depth 260 mm**

- Torsion free chassis with 4 crane eyes
- Sprung cutting head
- Cutting depth adjustable by manual lever
- Cutting cart with steel bearing rollers
- Handle for moving the cutting cart
- Professional water pump
- Adjustable angle stop
- 4 transport wheels, 2 with parking break
- Removable water tub, zinc coated

Specifications	GÖLZ BS650
Motor	3-phase, 400 V, 50 Hz, 16 A, IP 54
Power	5,5 kW (7,5 PS)
Max. cutting depth	260 mm
Max. blade size	650 mm
Arbor hole	60 mm
Cutting length	500 mm
Shaft speed	1.020 min <sup>-1</sup>
45° miter-cut	no
Water pump	electric
Blade flange size Ø	120 mm
Transport wheels	yes
Cutting table (LxW)	610 x 670 mm
Dimensions (LxWxH)	1.600 x 800 x 1.500 mm
Weight	230 kg
Order number	0282 650 1000



cutting depth 260 mm  
(blade size 650 mm)



crane eye



powerful 5,5 kW motor



4 transport wheels - 2 with parking break



removable water tub, zinc coated

Accessories	Order number
Spare water pump	0282 650 0179
Forkliffframe	0282 650 9035

Powerful block saw for the long term use on the jobsite



**Cutting length 600 mm**

**Blade-Ø 1.000 mm**

**Cutting length 420 mm**

- Torsion free chassis with 4 crane eyes
- Cutting depth adjustable by manual lever
- Sprung cutting head for cutting depth adjustment
- Professional water tube
- Adjustable angle stop
- Cutting head with steel bearing rollers
- 4 transport wheels, 2 with parking break
- Removable water tub, zinc coated

Specifications	GÖLZ BS1000
Motor	3-phase, 400 V, 50 Hz, 32 A, IP 54
Power	7,5 kW (10 PS)
Max. cutting depth	420 mm
Max. blade size	1000 mm
Arbor hole	60 mm
Cutting length	600 mm
Shaft speed	990 min <sup>-1</sup>
45° miter-cut	no
Water pump	electric
Blade flange size Ø	160 mm
Transport wheels	yes
Cutting table (LxW)	610 x 840 mm
Dimensions (LxWxH)	2.000 x 1.100 x 1.550 mm
Weight	280 kg
Order number	0282 900 2020



sprung cutting head for easy cutting depth adjustment



removable water tub, zinc coated



blade size Ø 1000 mm cutting depth 420 mm



moving of the cutting head by hand wheel



powerful motor 7,5 kW



4 transport wheels - 2 with parking break

Accessories	Order number
Spare water pump	0282 650 0179

Specifications	Tile Saws		Bridge Saws		
	GÖLZ TS200	GÖLZ TS250	GÖLZ GS350	GÖLZ GS350A-M	GÖLZ GS350A-XL
Motor	Electric, 230V, 50Hz, IP54		Electric, 230V, 50Hz, IP54		
Power	1,3 kW		2,2 kW	2,2 kW	2,2 kW
Max. cutting depth	40 mm	65 mm	110 mm	110 mm	110 mm
Max. blade size	200 mm	250 mm	350 mm	350 mm	350 mm
Arbor hole	25,4 mm	25,4 mm	25,4 mm	25,4 mm	25,4 mm
Cutting length	560 mm (720 mm)	980 mm (1.140 mm)	1.000 mm (1.200 mm)	1.500 mm (1.650 mm)	1.850 mm (2.000 mm)
Shaft speed	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>
45° miter-cut	Built-In	Built-In	Built-In	Built-In	Built-In
Water pump	S2, 230 V, 50 Hz, 55 Watt		S2, 230 V, 50 Hz, 55 Watt		
Blade flange size ø	64 mm	64 mm	90 mm	90 mm	90 mm
Transport wheels	yes	yes	yes	yes	yes
Cutting table (LxW)	720 x 480 mm	1.140 x 480 mm	1.200 x 530 mm	1.650 x 529 mm	2.000 x 529 mm
Dimensions (LxWxH)	1.220 x 540 x 1.299 mm	1.640 x 540 x 1.299 mm	1.710 x 700 x 1.360 mm	1.810 x 740 x 1.490 mm	2.310 x 740 x 1.490 mm
Weight	57 kg	72 kg	95 kg	113 kg	135 kg
<b>Order number</b>	<b>0289 200 1000</b>	<b>0289 250 1000</b>	<b>0289 350 3000</b>	<b>0289 350 4000</b>	<b>0289 350 5000</b>

Specifications	Block Saws			
	GÖLZ BS400	GÖLZ BS400	GÖLZ BS600	GÖLZ BS600
Motor	230 V / 400 V, 50 Hz, IP54	Honda GX200	230 V / 400 V, 50 Hz, IP54	Honda GX200
Power	2,2 kW	4,8 kW / 6,5 PS	2,2 kW	4,8 kW / 6,5 PS
Max. cutting depth	150 mm (double-sided cutting 280 mm)		235 mm	235 mm
Max. blade size	400 mm	400 mm	600 mm	600 mm
Arbor hole	25,4 mm	25,4 mm	25,4 mm	25,4 mm
Cutting length	800 mm	800 mm	400 mm (280 mm material height) 600 mm (50 mm material height)	400 mm (280 mm material height) 600 mm (50 mm material height)
Shaft speed	2.650 min <sup>-1</sup>	2.550 min <sup>-1</sup>	1.440 min <sup>-1</sup>	1.650 min <sup>-1</sup>
45° miter-cut	No, Miter-block optional	No, Miter-block optional	no	no
Water pump	S2, 230 V, 50 Hz, 55 Watt	efficient mechanical water pump	S2, 230 V, 50 Hz, 55 Watt	efficient mechanical water pump
Blade flange size ø	90 mm	90 mm	130 mm	130 mm
Transport wheels	yes	yes	yes	yes
Cutting table (LxW)	600 x 530 mm		600 x 525 mm	600 x 525 mm
Dimensions (LxWxH)	1.110 x 640 x 1.400 mm		1.100 x 870 x 1.480 mm	1.100 x 870 x 1.550 mm
Weight	90 kg	93 kg	95 kg	98 kg
<b>Order number</b>	<b>0282 400 1000 (230 V)</b> <b>0282 400 1100 (400 V)</b>	<b>0282 400 1300</b>	<b>0282 600 1000 (230 V)</b> <b>0282 600 1100 (400 V)</b>	<b>0282 600 1300</b>

Specifications	Masonry Saws				
	GÖLZ MS350C	GÖLZ MS350L	GÖLZ MS400	GÖLZ MS400A	GÖLZ MS700A
Motor	Electric, 230V, 50Hz, IP54				Electric, 400 V, 50 Hz, IP54
Power	2,2 kW	2,2 kW	2,2 kW	2,2 kW	2,2 kW (3 PS)
Max. cutting depth	110 mm	110 mm	137 mm	137 mm	280 mm
Max. blade size	350 mm	350 mm	400 mm	400 mm	700 mm
Arbor hole	25,4 mm	25,4 mm	25,4 mm	25,4 mm	30 mm
Cutting length	560 mm	700 mm	700 mm	800 mm	650 mm (280 mm material height) 800 mm (50 mm material height)
Shaft speed	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>	2.800 min <sup>-1</sup>	1.450 min <sup>-1</sup>
45° miter-cut	No, Miter-block optional	No, Miter-block optional	Built-In	Built-In	no
Water pump	S2, 230 V, 50 Hz, 55 Watt				
Blade flange size ø	90 mm	90 mm	90 mm	90 mm	140 mm
Transport wheels	yes	yes	yes	yes	no
Cutting table (LxW)	400 x 400 mm	600 x 530 mm	600 x 530 mm	560 x 560 mm	510 x 540 mm
Dimensions (LxWxH)	960 x 640 x 1.250 mm	1.100 x 640 x 1.250 mm	1.100 x 842 x 1.290 mm	1.390 x 750 x 1.330 mm	1.630 x 760 x 1.600 mm
Weight	56 kg	63 kg	66 kg	79 kg	115 kg
<b>Order number</b>	<b>0289 350 1000</b>	<b>0289 350 2000</b>	<b>0289 400 1000</b>	<b>0289 400 2000</b>	<b>0289 700 2000</b>

Specifications	Block Saws	
	GÖLZ BS650	GÖLZ BS1000
Motor	3-phase, 400 V, 50 Hz, 16 A, IP 54	3-phase, 400 V, 50 Hz, 32 A, IP 54
Power	5,5 kW (7,5 PS)	7,5 kW (10 PS)
Max. cutting depth	260 mm	420 mm
Max. blade size	650 mm	1000 mm
Arbor hole	60 mm	60 mm
Cutting length	500 mm	600 mm
Shaft speed	1.020 min <sup>-1</sup>	990 min <sup>-1</sup>
45° miter-cut	no	no
Water pump	electric	electric
Blade flange size ø	120 mm	160 mm
Transport wheels	yes	yes
Cutting table (LxW)	610 x 670 mm	610 x 840 mm
Dimensions (LxWxH)	1.600 x 800 x 1.500 mm	2.000 x 1.100 x 1.550 mm
Weight	230 kg	280 kg
<b>Order number</b>	<b>0282 650 1000</b>	<b>0282 900 2020</b>





**GÖLZ® - Group**

**GÖLZ GmbH**

**Dommersbach 51 | 53940 Hellenthal-Blumenthal**

**Telefon +49 2482 12-0 | Fax +49 2482 12-222**

**info@goelz.de | www.goelz.de**

**ÖSTERREICH**

**Gölz Ges.m.b.H.**

**Samstr. 52 | A-5020 Salzburg**

**Telefon +43 662 438175 | Fax +43 662 430734**

**info@goelz.at | www.goelz.at**

**FRANKREICH**

**Gölz S.A.S.**

**Espace Laiterie | 1, rue de la Mairie | F-67370 Berstett**

**Telefon +33 3 88 59 43 00 | Fax +33 3 88 59 47 77**

**info@golz.fr | www.golz.fr**

**GROSSBRITANNIEN**

**Golz (UK) Ltd.**

**Unit A5 | Springhead, Enterprise Park**

**Northfleet | Kent DA 11 8HB**

**Telefon +44 1 474 321 679 | Fax +44 1 474 321 477**

**info@goelz.co.uk | www.golzuk.com**

**BENELUX**

**Gölz Benelux N.V. Belgien**

**Eupener Straße 61 | B-4731 Raeren-Eynatten**

**Telefon +32 87 55 23 49 | Fax +32 13 78 33 28**

**benelux@goelz.de | www.golzgroup.com**

**USA**

**Golz L.L.C.**

**5860 East Osage Ridge Lane | Columbia MO 65203-6018**

**info@golzusa.com | www.golzgroup.com**



**Your GÖLZ dealer**

