



## UL Online Certifications Directory CLB.V.R25047

### Wall and Partition Facings and Accessories

#### Wall and Partition Facings and Accessories

See General Information for Wall and Partition Facings and Accessories

Type Tuff-Mass Acoustic Barrier (1 lb/sq ft.) membrane for optional use on one side of wall designs of the U300, U400, and V400 series. Also for optional use in floor-ceiling constructions of the L500 series over the subfloor.

For U300, U400 and V400 series designs, one layer of membrane applied to one side of wood or steel studs between stud and gypsum board per manufacturer's recommendations. When installed, the membrane flex at midspan between the studs shall be max. 1 in. from the back of the gypsum board. Gypsum board layer(s) installed over membrane per the Design.

For L500 series designs, one layer of membrane applied over the subfloor with adhesive and/or nails per manufacturer's recommendations. Finish floor attached per manufacturer's instructions.

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc.®

---

Information herein pertains to Tuff Mass Acoustic Barrier, manufactured by Soundown Corporation 16 Broadway Salem MA 01970. Sound Isolation Company is a distributor of Tuff-Mass Acoustic Barrier.



#### Soundproofing Made Simple®

2900 Westinghouse Blvd. Suite 106 ■ Charlotte, NC 28273

Phone: (704) 504-1127 ■ Toll Free (888) 666-5090 ■ Fax (704) 504-1115 ■ [www.soundisolationcompany.com](http://www.soundisolationcompany.com)

---