

Work Platforms (WP)

Our best selling Stablemate Access Platforms offer the ideal solution to you needs, when elevation is needed during unscheduled emergency situations such as building repair, checking high level racking, light bulb changing etc.

To fit; simply drive the truck slowly into the platform sleeves, once the forks are fully sleeved simply re-fit the heel pin behind the truck forks, thus retaining the attachment.

Note: The truck parking brake must be applied when personnel are inside the platform. Vertical movement permitted only.


All Platforms comply to PM28.

.A superior platform manufactured to a high specification. All have safety harness rails and positive heel locking. Where gates are fitted, locks operate automatically when the platform is raised.





| Model Ref. | Weight | CofG | No. Of People | Capacity | |
|-------------|--------|-------|---------------|----------|--|
| WP-SP | 74kgs | 300mm | 1 | 300kgs | |
| WP-STD | 108kgs | 500mm | 2 | 500kgs | |
| WP-SPG | 99kgs | 427mm | 1 | 300kgs | |
| WP-GATED | 114kgs | 496mm | 2 | 500kgs | |
| WP-ULTIMATE | 148kgs | 469mm | 2 | 500kgs | |



| Model Ref. | Access | A | В | С | D | E |
|-------------|--------------|--------|--------|-------|--------|--------|
| WP-SP | Lift Up Bar | 800mm | 800mm | 794mm | 1860mm | 1070mm |
| WP-STD | Through Bars | 1220mm | 1000mm | 794mm | 1860mm | 1070mm |
| WP-SPG | Front Gate | 1000mm | 1000mm | 794mm | 1860mm | 1070mm |
| WP-GATED | Side Gate | 1220mm | 1000mm | 794mm | 1860mm | 1070mm |
| WP-ULTIMATE | Side Gate | 1220mm | 1000mm | 794mm | 1860mm | 1070mm |

Е